

4th CLIC Advisory Committee (CLIC-ACE)

26-May-2009

CLIC Drive beam RF system including phase and intensity stabilisation systems

Erk Jensen, BE-RF

What I'll talk about:

- Which size and how many power sources?
- Which size modulators?
- The issue phase jitter and ideas to address it.

What I'll not talk about:

- Thanks to CTF3, many issues have already been addressed and feasibility demonstrated: e.g. full beam loaded operation, beam pulse compression ...

I acknowledge:

- I report on work of many others, in particular D. Schulte, A. Andersson and in Jonathan Sladen. Jonathan passed away last week – we are all immeasurably saddened about this.



CLIC Drive Beam RF System


- The CLIC Drive Beam RF system as such is not considered a feasibility issue and consequently has not been designed.
- However, some parameters are unprecedented and require attention; we are only starting to address these *issues*:
 - **Very large total power** (≈ 23 GW peak, 170 MW average)
 - What power source?
 - Optimum size (and number) of the power source “modules”?
 - related with the above: reliability, operability, maintainability, noise!
 - **Phase stability (jitter < 50 fs)** ; phase errors are multiplied with combination scheme. Origins of phase noise and their propagation through the klystrons, accelerating structures and combining scheme. Can this be done? Mitigation?
 - **Overall efficiency!** Two-beam scheme has more stages than single-beam scheme!
 - **Cost!** Considering the above, the drive-beam generation scheme and its RF system are a non-negligible cost driver.

Reminder: what does CLIC need?

- Recent parameter changes:
 - Nov. 2006: 937 MHz (30 GHz/32) → 1.333 GHz (12 GHz/9)
 - Sep. 2007: 1.333 GHz → 999.52 MHz (12 GHz/12)
- Total peak RF power required per linac is about 11.5 GW (from $4.21 \text{ A} \cdot 2.38 \text{ GV} / 93.5\% / 93.2\%$).
- With a rep. rate of 50 Hz and an RF pulse length of – say – 150 μs (total CLIC length/c), we get:
- Duty factor $150 \mu\text{s} \cdot 50 \text{ Hz} = 0.75 \%$ → av. power 86 MW *)!
- Of major importance for the RF power source in the specifications are
 - the phase stability,
 - the power conversion efficiency.

*) See next page

Average powers from CLIC 2008 Parameters



Klystrons or something else?

- Could it be magnetrons?
 - Injection-locked oscillators
 - Potentially better efficiency, but phase noise requirement would either be a show-stopper or at least require longer RF pulses for phase to stabilize and thus decrease the effective efficiency. **no**
- Could it be IOT's?
 - Present day IOT's are around 100 kW. They're less reliable today. They have much less gain! I don't see a clear advantage for the R&D required. **no - maybe reconsider later**
- Pencil-beam klystrons?
 - Why not? You need a much larger number (say 10'000) but that would be extremely well studied and reliable objects. Sprehn noted the advantages in 2004 (1.7 MW tubes à 27.5 k\$):
 - Several tube companies would participate. Competition combined with quantity would drive costs down.
 - Simplified cavity waveguide feeds (maybe not true in our case)
 - Graceful system degradation (!)
 - Higher reliability
 - For n tubes replacing 1, uncorrelated noise decreases by factor \sqrt{n} ! **yes**
- Multi-beam klystron?
 - Definitely the closest to existing, ready-to-use technology! I would put my money on these! Say 12 beams, 140 kV, 10 to 15 MW. **yes**
- Sheet-beam klystrons?
 - They promise to be much cheaper for larger quantities, but there is no demonstration today that would support this claim **yes - later**

Existing: ILC 1.3 GHz MBK's (10MW, 1.5 ms, 10 Hz)

1. CPI: VKL-8301B (6 beam): 10.2 MW, 66.3 %, 49.3 dB gain
2. Thales: TH 1801 (7 beam): 10.1 MW, 63%, 48 dB gain
3. Toshiba: E3736 (6 beam): 10.4 MW, 66 %, 49 dB gain

1.



2.




3.




Existing idea for a high power, high efficiency MBK:

- Cf. [Jensen, Syrathev: "CLIC 50 MW L-Band Multi-Beam Klystron", CLIC-Note-640](#)



- The main idea: use a mode like the one depicted as #4 (whispering gallery mode) for many beams; the advantage of this mode: It can be made very pure!
- The problem: This device became really big: how do you braze this? Imagine a little problem in one of the ≈ 22 beams!
- There is a study ongoing in collaboration with Thales and Lancaster University (PhD work).



What's in the 2008 parameter list

- Given the total peak power, it had been assumed that 33 MW peak could be made available at the input of each accelerating structure. This resulted in 326 klystrons and 326 accelerating structures per linac.
- The accelerating structures were scaled from the existing 3 GHz structures and not optimized for 1 GHz.
- The number of cells is then adjusted to be fully beam-loaded for the nominal current and power.
- Keeping the beam current at its nominal value of 4.21 A, here the input power requirements for structures with different cell numbers:
- Importance of the group delay: the structure will “filter out” noise from the klystron and from the beam.

Input power for full beam loading for different cell numbers

# cells	P_{in} [MW]	η	length [m]	r [ns]	acc [MV]	# struct	total length [km]	P_{tot} [GW]
15	6.33	98.81%	1.500	142.0	1.49	1602	2.402	10.139
16	7.21	98.73%	1.600	151.4	1.69	1407	2.251	10.146
17	8.14	98.66%	1.700	160.8	1.91	1247	2.119	10.154
18	9.12	98.58%	1.800	170.2	2.14	1114	2.005	10.162
19	10.2	98.51%	1.900	179.5	2.38	1000	1.900	10.170
20	11.3	98.43%	2.000	188.9	2.64	901	1.802	10.150
21	12.4	98.36%	2.100	198.3	2.90	821	1.724	10.185
22	13.6	98.28%	2.200	207.7	3.18	749	1.647	10.193
23	14.9	98.21%	2.300	217.1	3.48	685	1.575	10.201
24	16.2	98.13%	2.399	226.5	3.78	630	1.512	10.208
25	17.6	98.06%	2.499	235.9	4.10	580	1.450	10.216
26	19.1	97.98%	2.599	245.3	4.45	535	1.391	10.224
27	20.6	97.91%	2.699	254.7	4.79	497	1.342	10.232
28	22.1	97.84%	2.799	264.0	5.14	463	1.296	10.239
29	23.7	97.76%	2.899	273.4	5.50	432	1.253	10.247
30	25.4	97.69%	2.999	282.8	5.89	404	1.212	10.255
31	27.1	97.61%	3.099	292.2	6.28	379	1.175	10.263
32	28.9	97.54%	3.199	301.6	6.70	355	1.136	10.270
33	30.8	97.47%	3.299	311.0	7.13	334	1.102	10.278
34	32.7	97.39%	3.399	320.4	7.57	315	1.071	10.286
35	34.6	97.32%	3.499	329.8	8.00	298	1.043	10.294
36	36.6	97.25%	3.599	339.2	8.46	281	1.011	10.302
37	38.7	97.17%	3.699	348.6	8.93	266	0.984	10.309
38	40.8	97.10%	3.799	358.0	9.41	253	0.961	10.317
39	43.0	97.03%	3.899	367.3	9.91	240	0.936	10.325
40	45.3	96.95%	3.999	376.7	10.43	228	0.912	10.333

$$\approx 28.3 \text{ kW} \cdot n_{\text{cell}}^2$$

present
"nominal"




Conclusion (from this table)

- The number of cells can be adapted to the available RF power.
- Shorter accelerating structures are more efficient (less ohmic losses – small effect)
- With shorter structures, the linac overall length gets large.
- These are preliminary structures, just scaled from CTF3. As a consequence, the beam aperture is a factor 3 larger than at 3 GHz (34 mm -> 102 mm, while the beam current is only 20 % larger (3.5 -> 4.2 A).
Re-optimization of the accelerating structures is in progress.


Efficiency

- The CLIC 2008 Parameters assume a tube efficiency of 70%, existing tubes reach 66%. For the CDR, 66% should be used.
- It is generally accepted that maximum obtainable efficiency is a function of the perveance $I/V^{3/2}$. Using an empirical model, here is what one could expect (numbers for 13 MW DC):
- For practical reasons, the voltage should be kept moderate (say below 140 kV).
- To limit the complexity, the number of beamlets should remain reasonable.
- I marked a point which I find interesting: 12 beams, 140 kV; it could reach above 70%.



How does the cost of a klystrons scale with peak power?

- Probably: cost per klystron proportional to (peak power)^{1/2} (*)
- At a level of around 15 MW peak, the slope will become steeper due to increased system complexity.
- This leads to the following model:




- Blue: present state of the art
- Red: assuming a major investment into the development of a dedicated 30 MW tube

(*) rule of thumb given by T. Habermann/CPI. Rees/LANL estimates $P^{0.2}$ for 0.5 to 5 MW tubes.

Cost per MW

- Using the above model, here's the klystron cost per MW (peak)



- Blue: present state of the art
- Red: assuming a major investment into the development of a dedicated 30 MW tube

Tube lifetime

- In spite of its price, a klystron is a consumable!
- A klystron has a finite lifetime; this will also depend on its internal complexity (and on the peak power!).
- The lifetime will depend on many parameters, primarily the current density, but here's one estimate ...

MIL-HDBK-217F
NOTICE 1

7.1 TUBES, ALL TYPES EXCEPT TWT AND MAGNETRON

Alternate* Base Failure Rate for Pulsed Klystrons - λ_b

P(MW)	F(GHz)						
	.2	.4	.6	.8	1.0	2.0	6.0
.01	16	16	16	16	16	16	16
.30	16	16	17	17	17	18	20
.80	16	17	17	18	18	21	25
1.0	17	17	18	18	19	22	28
3.0	18	20	21	23	25	34	51
5.0	19	22	25	28	31	45	75
8.0	21	25	30	35	40	63	110
10	22	28	34	40	45	75	
25	31	45	60	75	90	160	

$$\lambda_b = 2.94 (F)(P) + 16$$

F = Operating Frequency in GHz, $0.2 \leq F \leq 6$

P = Peak Output Power in MW, $.01 \leq P \leq 25$ and $P \leq 490 F^{-2.95}$

*See previous page for other Klystron Base Failure Rates.

Learning Factor - π_L

T (years)	π_L
≤ 1	10
2	2.3
≥ 3	1.0

$$\pi_L = 10(T)^{-2.1}, 1 \leq T \leq 3$$


$$= 10, T \leq 1$$

$$= 1, T \geq 3$$

T = Number of Years since Introduction to Field Use

Environment Factor - π_E


Environment	π_E
G	50



What about an MBK?: is the tube dead if one of n beams fails? If the design is good, the n beams would fail at around the same time ...

Cost per 100,000 operating hours and per MW

- Even if this model may be wrong, there will be a cost per MW and per operating hour: With the above model, this becomes:




- Blue: present state of the art
- Red: assuming a major investment into the development of a dedicated 30 MW tube

Conclusion (from the cost per tube per operating hour)

- The lifetime model presented here may be wrong; the scaling for the unit cost may be wrong, but for a correct cost estimate, both these influences must be included.
- Assuming that the models used above are somehow reasonable, the optimum size of an individual tube would be not significantly above 10 MW. This conclusion may change depending on a better model.
- It may also change after dedicated R&D, but in my opinion this R&D should rather address the reliability, cost and lifetime than the peak power.
- Anticipating from the phase noise analysis:
 - The klystron phase pushing gets better for shorter tubes and higher voltage (see below)
 - n individual sources instead of 1 will decrease the (uncorrelated) noise by a factor \sqrt{n}

Concerning modulators

- R&D is going on for ILC, SPL, ... we should take full advantage!
- Our CERN modulator experts explain:
 - A classical "bouncer" type modulator for a size of 12 kV, 2 kA can be considered feasible.
 - It would look like this (just the topology, picture taken from ILC):



- A larger modulator would combine a number of these; its cost would scale at best linearly with peak power – the "modular modulator" – no saving from making it bigger. This (20 MW peak or so) seems to be the natural module size. A modulator with 3 modules would cost around 1 MCHF.
- The numbers given here would be consistent with a 15 MW MBK.

Modulator

This is some really big object!

Some ILC examples:

HVPS and pulse forming unit:



IGCT stack:



Pulse transformer:



ILC estimate:
300 ... 400 k\$/unit



Commercial modulator 20 MW,
average power around a factor 10 too
small.

One would need 1 of those every 2 to 3 m for the total length of the DBL!

Conclusion (modulators)

- Base line: bouncer type modulator is quasi “commercial”.
- 12 kV/2kA is a natural module size (24 MW DC);
- pulse transformer 12:1, → 140 kV/160 A
- Larger modulators of this type would not be cheaper per MW.
- Modulators of other types require R&D!
- With a 70% efficient klystron, this would correspond to 15 MW RF.
- Anticipating from phase noise analysis:
 - Feed-forward to compensate for systematic voltage variation (droop) must be provided!
 - Stabilisation of the voltage to the 10^{-5} level is hard!
 - Again: the noise from more, smaller modulators will add only as \sqrt{n} .

Phase stability/stabilisation

- Drive beam phase jitter leads to luminosity drop.
- $\Delta\varphi$ at 1 GHz causes 12 $\Delta\varphi$ at 12 GHz!
- Any R_{56} transforms drive beam energy jitter to phase jitter.
- With full beam loading, drive beam current error transforms to energy error (and then phase error).
- Requirement (order of magnitude):
 - drive beam phase jitter $< 0.02^\circ$ (3.5E-4, 50 fs)
 - drive beam energy jitter $< \mathcal{O}(1E-4)$(With a feed-forward, this may be relaxed by a factor 10!)
- Accelerating structures and recombination scheme act as filters for the noise.

Origins of noise


- We look at “noise”, which is meant to include both amplitude and phase noise. The difference is the correlation between sidebands.
- Strictly speaking, noise is characterized with its spectral power density S (W/Hz), so the jitter specification should be called “integrated jitter”

$$\sigma_{\phi} = \sqrt{\int S_{\phi\phi}(f)df}$$

- Principal origins of noise:
 - Drive beam Gun: intensity variations
 - Phase reference generation and distribution *)!
 - SH pre-buncher (500 MHz, flips phase every 244 ns ! → creates also systematic error at 2.05 MHz!)
 - Klystrons (modulator, temperature, drive ...)

- Propagation of noise:
 - Noise propagates like any other signal, the analysis is similar (uses $|H(f)|^2$)

total area under integral	phi rms (radians)	rms (s)
1.70512E-05	0.004129311	4.22582E-12



*) See next page



Global timing distribution: ongoing R&D efforts

Two major R&D efforts are ongoing on the development of optical clock systems:

...

Both systems are fully consistent: each of them fulfils the requirements for a complete fs timing system.


[M. Ferianis, "Timing and Synchronization in Large Scale Linear Accelerators", LINAC 2006, Knoxville, Tennessee USA]




The distribution of ultrafast optical pulse trains across **300 meters** of fiber with **sub-femtosecond timing jitter** and 83 fs of drift over 25 hours, as measured between the outputs from two independent links, is demonstrated.

[J. A. Cox et. al, "Sub-femtosecond Timing Distribution of an Ultrafast Optical Pulse Train over Multiple Fiber Links", OSA / CLEO/QELS 2008]

Alternate CLIC timing scheme



Commercially available **Sapphire Loaded Cavity Oscillator** with 3...5 fs integrated phase noise.



Use low frequency global timing signal to compensate for slow frequency drifts. Use outgoing main beam for precision synchronization of phase. I.e. measure average phase between RF extracted from the outgoing main beam, and subtract from the later measurement for the drive beam phase.

See also: A. Andersson, J.P.H. Sladen: "Precision beam timing measurement system for CLIC synchronization", EPAC 2006;
 A. Andersson, J.P.H. Sladen: "First tests of a precision beam phase measurement system in CTF3", PAC2007

High precision phase detector

- For this feed-forward scheme: in order to correct, first you have to detect to at least the same precision!
 - The phase monitors are part of the work-package “NCLinac” inside the European FP7 project “EuCARD”.
 - Collaboration CERN, PSI, INFN/LNF
 - Estimated resources: 5.1 FTE-y, 0.95 M€.
- Here an excerpt from the task definition:

... a monitor able to detect the longitudinal position of the bunches with a resolution of the order of 20 fs. The coupling impedance of the monitor has to be very low due to the high beam current. RF noise and wake fields in the beam pipe must not affect the measurement and have to be rejected by proper designed filters. This device will find applications in other machines where precise high frequency beam phase detection is required.

Two possible solutions will be investigated at the same time. A low impedance RF phase monitor with an integrated noise filter will be designed and built by CERN and INFN. It will be tested in CTF3 where it will also play an important diagnostic role in the optimization of the machine performances. An electro-optical monitor using periodic train of laser pulses to sample signal from wide bandwidth beam pickup will be developed and built by PSI and will be tested at the existing facilities at PSI.


Klystron phase pushing

- Phase pushing denotes the phase variation resulting from voltage variation. It transforms modulator noise to phase noise

- Phase pushing of a klystron:
$$\delta\varphi = -2\pi \frac{L}{\lambda} (V(2+V))^{-3/2} \delta V$$

(where V is in units of 511 kV)

L : Length of klystron



E.g.: at 120 kV, one gets a phase pushing of $-0.018^\circ/V L/\lambda$, i.e. to stabilize the output phase to 0.2° for a klystron of $L = 10 \lambda$, the voltage must vary for less than 1 V or 10^{-5} !

➔ For small phase pushing: stable modulator, short klystron, high voltage!

Other parameters influencing the RF phase noise

- via klystron:

- Voltage $\delta\phi = -\frac{L}{\lambda} (V(2+V))^{-3/2} \delta V$

- Klystron body temperature: $\delta\phi \approx 1^\circ \frac{\delta T}{K}$

- Drive power $\delta\phi \approx 2.3^\circ \frac{\log \delta P_{in}}{\text{dB}}$

- ... filament current, magnet current, waveguides...

- via the beam:

- Beam current changes acceleration!

at full loading: $\frac{\delta V}{V} = -2 \frac{\delta I}{I}$

$$\frac{\delta V}{V} = -\frac{R}{V_0/I - R} \frac{\delta I}{I}$$


- Phase jitter from the source

- ...

The accelerating structure as filter


- filtering the klystron signal:

$$\left| \frac{V_{acc}}{\sqrt{P_{klystron}} / (33 \text{ MW})} \right|$$



- filtering the beam signal:

$$\left| \frac{V_{acc}}{I_{beam} / (4.21 \text{ A})} \right|$$



Approximation used: linearized dispersion $\beta(\omega) = \frac{\omega_0}{c} + \frac{\omega - \omega_0}{v_g}$

Delay loop and combiner rings as filter

- Laplace transform of recombination scheme:


$$(1 + e^{-p\tau_{DL}}) (1 + e^{-p\tau_{CR1}} + e^{-2p\tau_{CR1}}) (1 + e^{-p\tau_{CR2}} + e^{-2p\tau_{CR2}} + e^{-3p\tau_{CR2}})$$

DL (243.5 ns)

CR1 (x3, 487.5 ns)


CR2 (x4, 1461.8 ns)

- Transfer function




Applying those filters together

- With the accelerating structure unchanged:



- Acc. structure adjusted to $\tau_{fill} = \tau_{DL}$:



Compare also: D. Schulte, E.J.N. Wilson, F. Zimmermann: "The Impact of Longitudinal Drive Beam Jitter on the CLIC Luminosity", LINAC 04

My conclusions

1. For CDR, stay with 10 MW MBK's – we know (from ILC) that they can be done. Reducing pulse width is trivial – but extrapolating to higher peak power requires some dedicated R&D.
2. → Concentrate R&D on a modular RF system with peak powers of 10...15 MW peak, addressing – in addition to the RF parameters – cost, reliability, tube lifetime, serviceability, graceful degradation, and phase stability.
3. → Include the modulator in this design.
4. Only some of this R&D is required for CDR, but most for TDR.
5. For reference, → re-evaluate the potential of SBK's and PBK's!
6. The numbers presented above for cost scaling and MTBF are the result of some emails, telephone calls and google searches; I believe however that they indicate which way to go ... → One should dig deeper and improve the simplified models I've used – maybe this will even change the conclusions I've made!
7. → Re-adapt the beam pipe diameter of the accelerating structure for higher impedance to stay below say 1 km. (Considering the probable size of the modulators, this may not help too much)
8. It is not clear whether the required phase stability can be reached. The main suspects: modulator voltage jitter, SH pre-buncher, source!