



Improvement in Training Performance by Enhancing Coil Mechanical Support in Beam Separation Dipole Model Magnet for the HL-LHC Upgrade

Michinaka Sugano

K. Suzuki, T. Nakamoto, N. Higashi, M. Iida, H. Ikeda, Y. Ikemoto,
H. Kawamata, N. Kimura, T. Ogitsu, H. Ohhata, N. Okada, R. Okada,
K. Sasaki, N. Takahashi, K. Tanaka

KEK

A. Musso, E. Todesco

CERN

Outline

- **MBXF for HL-LHC**
- **Mechanical support in MBXFS3**
- **Test result of MBXFS3**
 - **Training performance**
 - **Coil stress in the straight section (SS)**
 - **Quench start location**
 - **Field quality**



MBXF for HL-LHC

MBXF for HL-LHC

High Luminosity LHC (HL-LHC)

Peak luminosity : $5 \times 10^{34} \text{ cm}^{-2}\text{s}^{-1}$ (a factor of 5)

Integrated luminosity : 3000 fb^{-1} (a factor of 10)



Courtesy of P. Fessia

KEK is in charge of developing **beam separation dipole (D1 magnet, MBXF)**.


- **Large aperture** to obtain smaller β^* : **Coil aperture**: $\phi 70 \text{ mm} \rightarrow \phi 150 \text{ mm}$
- **Stronger kick** to accommodate shorter distance between D1 and D2 (recombination magnet) : **Field integral**: $26 \text{ Tm} \rightarrow 35 \text{ Tm}$

Normal conducting D1 in the current LHC will be replaced by

Nb-Ti based superconducting magnets.

Design parameters

	A series production (7m) MBXFS2 (2 m)	
Coil aperture	150 mm	
Field integral	35 T m	9.5 T m
Field (3D)	Nominal: 5.60 T, Ultimate: 6.04 T	
Peak field (3D)	Nominal: 6.58 T, Ultimate: 71.4 T	
Current	Nominal : 12.05 kA, Ultimate 13.14 kA	
Operating temperature	1.9 K	
Field quality	$<10^{-4}$ w.r.t B_1 ($R_{\text{ref}}=50$ mm)	
Load line ratio (3D)	Nominal: 76.5%, Ultimate: 83.1% at 1.9 K	
Differential inductance	Nominal: 4.0 mH/m	
Conductor	Nb-Ti: LHC-MB outer cable	
Stored energy	Nominal: 340 kJ/m	
Magnetic length	6.26 m	1.67 m
Coil mech. length	6.58 m	2.00 m
Magnet mech. length	6.73 m	2.15 m
Heat load	135 W (Magnet total) 2 mW/cm³ (Coil peak)	
Radiation dose	> 25 MGy	



Large-aperture single layer coil →

Mechanical support of a coil is challenging

Production magnet: 7 m-long

Three 2 m model magnets have been fabricated at KEK



Model magnet development in KEK

MBXFS1

- **Insufficient training performance** due to **lack of azimuthal pre-stress**
- Field quality could not be evaluated at nominal current due to low quench current

MBXFS1b

- **Re-assembled magnet with enhanced coil pre-stress**
- **Significant improvement of training performance**
- Field quality could not be quantitatively discussed due to shim insertion

MBXFS2



- Significant change in yoke design → Magnetic and mechanical design update
- Wet-winding at coil end for coil end support
- Successful validation of QPH with meandering heater strips
- **Large b_3 offset** of 19 unit from calculation
→ Incorrect way of wedge oversizing (thicker cable insulation in ROXIE calc.), coil deformation

MBXFS3

- Same basic design as MBXFS2 → **Reproducibility check**
- Same wedge design as MBXFS2 → Similar large b_3 offset is expected
- Further enhancement of mechanical support at coil end
- 1st cold test cycle has been completed

Mechanical support in MBXFS3

Mechanical support in the SS in MBXFS3



Strain gauges on collar pole


GFRP oversize and coil pre-stress

	MBXFS1	MBXFS1b	MBXFS2	MBXFS3
Total GFRP arc length w.r.t MBXFS1 (mm)	—	0.8	1.14	1.14
Target azimuthal pre-stress (MPa)	80	110	115	115
Measure pre-stress after yoking (MPa)	65	100	111	114



Mechanical support at coil end

Cable deformation

MBXFS1



Max displacement
3.4 mm in MBXFS1
→ ~1 mm in MBXFS2




Mechanical support at coil end



	MBXFS1	MBXFS1b	MBXFS2	MBXFS3
Oversize of end spacers (mm)	—	0.9	1.14	1.14
Additional shim on end saddle	—	—	—	t0.7 mm at max
Wet-winding	No	No	Yes	Yes
Tightening torque of bullets (Nm)	14	14	20	24
Gap filing with epoxy resin	No	No	No	Yes


Test result of MBXFS3

Training history








- Number of quenches to nominal (12.05 kA): 8 in MBXFS2 → 2 in MBXFS3
Significant improvement in training up to nominal current in MBXFS3
- The ultimate current (13.14 kA) was achieved at the 16th quench.
- Current holding: 12.3 kA for 1 hour, 13.3 kA for 35 min
- 4.4 K training: $I_{q,4.4K}=12.3$ kA up to short sample limit
→ Quench current at 1.9 K is limited by mechanical support

Coil stress in the straight section



Strain gauges
on collar pole








Sufficient azimuthal coil pre-stress in MBXFS3 same as MBXFS2

Quench start location


TC: Thermal cycle

T=1.9 K if not stated



- CB1, 2 → Low field coil blocks, CB3, 4 → High field coil blocks
- Quench start location moves from lower field (CB1, 2) in MBXFS1 to higher field coil blocks (CB3, 4) in MBXFS2 and 3 by wet-winding at coil end and end spacer oversizing.



Longitudinal quench start location



- Longitudinal quench start location was identified by voltage tap signals and quench antennas.
- In MBXFS2 and 3, training started from quench at **LE side**.
- Stress and strain measurements during excitation suggest that lower azimuthal coil pre-stress at LE can be one of the reasons of frequent quench at LE.


Summary of improvement in training by enhanced mechanical support

- MBXFS1 → MBXFS1b
 - Max. quench current > ultimate current
 - Increase in coil pre-stress both in the SS and at coil end
- MBXFS1, 1b → MBXFS2
 - Quench start location from lower field to higher field coil blocks
 - Wet-winding at coil end and end spacer oversizing
- MBXFS2 → MBXFS3
 - Improvement in training up to the nominal current
 - Coil end shimming and gap filling



Field quality of MBXFS3

At magnet center




		MBXFS2*	MBXFS3*	Δb_3
b_3 (units)	3 kA (Geometric)	20.89	24.03	3.1
	12.05 kA (Saturation)	36.04	37.32	1.3

(*) Average of ramp-up / down

- $\Delta b_3 = 3$ unit at 3 kA is taken into consideration as fabrication error in magnetic design of a full-scale prototype magnet
- $\Delta b_5, \Delta b_7$ are less than 1 unit.

Summary

- Third 2 m-long model magnet of beam separation dipole (MBXFS3) for the HL-LHC upgrade was fabricated and tested at KEK.
- Quench current reached nominal current after the second quench. Current-holding above the ultimate current was also successful.
- Quench started more frequently at LE than RE and SS.
- Coil end shimming and gap filling can improve training performance up to the nominal current.
- Measured field harmonics in MBXFS3 reproduced the results of MBXFS2 within $\Delta b_3=3$ unit at 3 kA.
- A 7 m-long prototype (MBXFP) will be constructed by Hitachi in 2020. KEK has completed modification of coil cross-section to fulfill the requirement of field quality. Preparation for prototype construction is ongoing.



Acknowledgement

- This work was supported by the High Luminosity LHC Project at CERN, and also in part by JSPS KAKENHI Grant 16H06489.
- The authors would like to express their gratitude to Profs. K. Tokushuku, K. Hanagaki and S. Yamaguchi at KEK and L. Rossi at CERN for their strong support in this project. The authors are also very grateful to their colleagues at KEK and CERN, particularly, B. Auchmann, A. Ballarino, L. Bottura, P. Fessia, P. Francois-Oliver, S. Izquierdo Bermudez, G. Kirby, J.C. Perez, G. de Rijk, F. Savary, C. Scheuerlein and R. van Weelderen for their helpful suggestions and discussions. The authors also thank T. Kawashima and O. Kobayashi for their technical support.