## TIPP 2011 - 2nd International Conference on Technology and Instrumentation in Particle Physics



Contribution ID: 504

Type: Oral Presentation

## **R&D** of neutron beam monitor based GEM detector

Monday, 13 June 2011 16:00 (20 minutes)

A thermal neutron beam monitor with Gas Electron Multiplier (GEM) as a detector is developed to meet the needs of the next generation neutron facilities. A prototype chamber has been constructed with two 50mm x 50mm GEM foils. Enriched boron-10 is coated on one surface of aluminum cathode plate as the neutron convertor. 96 channel pads with area 4 mm x 4mm each are used for fast signal readout. In order to study the basic characteristics of boron-coated GEM detector, several irradiation tests were carried out with  $\alpha$  source 239Pu and neutron source 241Am(Be). The signal induced by neutron has high signal-to-noise ratio. A clear image obtained from  $\alpha$  source 239Pu is presented, which shows that the GEM-based detector has good two-dimensional imaging ability.

Primary author: SUN, Zhijia (Institute of High Energy Physics, CAS)Presenter: SUN, Zhijia (Institute of High Energy Physics, CAS)Session Classification: Machine Det. Interface and Beam Instr.

Track Classification: Machine Detector Interface and Beam Instrumentation