

ProtoDUNE Physics and Results

Wenjie Wu (UCI), on behalf of the DUNE collaboration

APS DPF Meeting 2021


July 12, 2021



UCIRVINE



DUNE




See Jose Maneira's talk @ Plenary on 13 July

- DUNE: next generation neutrino experiment using LArTPC technology
 - New neutrino beam at Fermilab (1.2 MW, upgradeable to 2.4 MW), 1300 km baseline
 - 4 modules for Far Detector at Sanford Underground Research Facility, South Dakota, 1.5 km underground
 - Multiple technologies for the Near Detector (ND)
- $\nu_e/\bar{\nu}_e$ appearance and $\nu_\mu/\bar{\nu}_\mu$ disappearance \rightarrow Neutrino CP violating phase and mass ordering
- Large detector, deep underground, high intensity beam \rightarrow Supernova burst neutrinos, atmospheric neutrinos, nucleon decay and other BSM, etc
- Excavation started in 2017, start Far Detector installation in the middle of 2020s


ProtoDUNEs at CERN

- ProtoDUNE-SP and DP are DUNE's large scale prototypes (~1 kton-scale) of its far detector modules at CERN Neutrino Platform
 - Use components identical in size to those of the full-scale module
 - Critical to demonstrate viability of LArTPC technology



ProtoDUNE Dual Phase (DP)


- LArTPC 6 m vertical drift + charge amplification in gas Ar + photon detection
- Cosmic-muon data in 2019 - 2020



ProtoDUNE Single Phase (SP)

- LArTPC 3.6 m horizontal drift + photon detection
- Beam data taken in 2018 & cosmic data in 2018 - 2020
- ProtoDUNE-SP Phase II in 2022


ProtoDUNE-SP: Operating Principle



- Charged particles ionize argon atoms
- Ionized electrons drift horizontally opposite to the E field in the LAr and are collected on the anode wire planes (\sim ms) \rightarrow 2D spatial location
- Electron drift time projection \rightarrow enable 3D spatial location
- Argon scintillation light (\sim ns) detected by photon detectors, providing event start time t_0
- Key factors: **LAr purity** and **noise on the readout electronics**

ProtoDUNE-SP at CERN Neutrino Platform

- Tertiary beam
- Spectrometer to measure the particle momenta
- Particle ID from time of flight and two Cerenkov detectors
- Over 4 million triggers over the momentum range 0.3 to 7.0 GeV (positrons, pions, muon, kaons and protons)



B. Abi et al 2020 JINST 15 P12004

Journal of Instrumentation

OPEN ACCESS


First results on ProtoDUNE-SP liquid argon time projection chamber performance from a beam test at the CERN Neutrino Platform

B. Abi¹⁴², A. Abed Abud^{21,118}, R. Acciarri⁶¹, M.A. Acero⁸, G. Adamov⁶⁵, M. Adamowski⁶¹, D. Adams¹⁷, P. Adrien²¹, M. Adinolfi¹⁶, Z. Ahmad¹⁸² [+ Show full author list](#)

Published 3 December 2020 • © 2020 CERN


[Journal of Instrumentation](#), Volume 15, December 2020

Citation B. Abi et al 2020 JINST 15 P12004



ProtoDUNE-SP Detector


- TPC
 - Two drift volumes, 3.6 m drift distance (2.25 ms) @ 500 V/cm
 - Cathode Plane Assembly (CPA) on middle plane
 - Anode Plane Assemblies (APAs) on both sides
 - Cold electronics attached to the top of APAs
- Photon detectors (PDS)
 - SiPM readouts
 - Wavelength shifter converts VUV to visible light
 - 3 designs integrated into APA frame bars
- Cryogenic instrumentations: measure argon purity, temperature, liquid level and tag cosmic rays




Schematic of ProtoDUNE-SP

ProtoDUNE-SP: Detector Calibration


Run 5759, Plane 2



dQ/dx vs. drift distance of cathode-crossing cosmic muons




Stopping muon dE/dx




- Individual effects are measured and corrected for
 - SCE (Space charge effect), attenuation, electronic gain, diffusion, recombination, etc
 - Detector response is uniform in space and over time after the corrections
- Absolute energy scale is determined using stopping muons


ProtoDUNE-SP: dE/dx Measurements



Precise dE/dx leads to excellent μ^+/p separation




Good e/γ separation crucial for electron neutrino ID




- The calibration constants applied to test beam particles and yielded good data and MC agreements
 - Excellent μ^+/p separation: crucial for cross section measurements
 - Good e/γ separation: crucial for DUNE's neutrino oscillation measurements

ProtoDUNE-SP: LAr Purity




3 purity monitors at different heights to measure LAr purity




- Liquid Argon purity is routinely measured by three Purity Monitors
- High purity reached thanks to the gas/liquid recirculation & filtering
 - Lower limit of 30 ms lifetime over the majority of run period → 7% signal reduction over the entire 3.6 m drift distance (2.25 ms drift time)

ProtoDUNE-SP: Detector stability




- TPC signal strength: The average charge per channel from cosmics
 - A monitor of overall detector response
 - Sensitive to amplifier/digitizer response, cathode voltage, LAr purity and other detector conditions
- Response has been stable over the 22 months of operation

ProtoDUNE-DP: Operating Principle




- Ionized electrons drift vertically upward in LAr
- Electrons are extracted from liquid into gas phase above the liquid
- Charge signal amplified and read out at the top
- PMTs detect scintillation light at the bottom
- Challenge: the overall design increases the possible drift length which requires a correspondingly higher voltage

ProtoDUNE-DP Detector




- Charge Readout Planes (CRP)
- Field Cage
- Cathode (300 kV)
- Ground grid
- Photomultipliers




ProtoDUNE-DP: Cosmic Ray Events

- Events with LEM ΔV of 31–32 kV (Oct. 2019)


- Horizontal muon track



- Electromagnetic shower + 2 muon decays



- Multiple hadronic interactions in a shower





Summary and Prospect

- The successful performance of ProtoDUNE-SP LArTPC using large samples of data from a test-beam run at the CERN Neutrino Platform demonstrates the effectiveness of the single-phase detector design and the execution of the fabrication, assembly, installation, commissioning, and operation
 - The data collected by ProtoDUNE-SP during beam runs and cosmic-ray runs will allow more detailed studies of detector characteristics and the measurement of argon-hadron cross sections
 - ProtoDUNE-SP Phase II, to improve detector with lesson learned from Phase I, is expected to start in late 2022
- ProtoDUNE-DP is the largest dual-phase TPC ever built and operated
 - Plenty of data to be analyzed and many interesting results to be share with a wider community interested in large LAr TPCs


Stay tuned!

Backup

SP: Beam electron energy reconstruction




- Electron energy resolution is crucial for DUNE's oscillation measurements
 - $E_{\nu_e} = E_e + E_{had}$
- Two analyses to measure beam electron energy resolution
 - TPC charge information
 - Photon detector information with only one ARAPUCA bar






SP: Beam electron energy resolution

TPC



Photon Detector




$$\sigma_E / \langle E \rangle = \sqrt{a^2 + (b/\sqrt{E})^2 + (c/\langle E \rangle)^2}$$



- Good linearity seen in both analyses
- Constant term dominated by spread of beam momenta
- Noise term dominated by fluctuation in the energy loss upstream
- Stochastic term characterizes the intrinsic detector resolution
 - $\sim 2\%$ for TPC and 9.9% for PD
 - Better than the design requirements

SP: Electronic noise and S/N ratios

- Electronic noise level measured by pedestal ENC (equivalent noise charge) before noise filtering: Collection (X): 550 e⁻, Induction: 650 e⁻ (DUNE goal < 1000 e⁻)
- Noise filter reduces both by ~ 100 e⁻
- Noise-filtered signal-to-noise ratio measured by cosmic muons: Collection: 48.7:1, Induction: 21.2:1





SP: Photon Detector Performance



- Good energy linearity for contained beam electrons in the detector
- Working on geometry, attenuation and efficiency corrections


DP: Operating Principle



- Homogeneous 0.5 kV/cm drift field (cathode + field cage)
- Extraction field ~ 2.5 kV/cm between grid and LEM bottom
- Amplification ~ 20 in LEMs holes
- Readout in two directions (3.125 mm pitch) by collection on anode via field between LEM top electrode and anode

DP: Charge Readout Plane gain measurement

- Measurements between Sept. 2019 and Jan. 2020 with cosmics
- Operating conditions: 1045 mbar and ~ 90 K
- CRP gain: $\epsilon_{\text{extraction}} \times \epsilon_{\text{LEMs, amplification}} \times \epsilon_{\text{Qcollection}}(E_{\text{induction}})$
- $\epsilon_{\text{extraction}}$ estimated to be well above 90%



- Sept. \rightarrow Nov: Reduction by at least a factor of 2 due to LEM charging up effects
- Nov. \rightarrow Jan.: very small reduction, charging up completed
- Gain a factor of 2 lower than extrapolated from previous prototypes
- Discrepancy not yet understood, dedicated study to come