



Rucio deployment: Managing MAGIC data

A. Bruzzese (bruzzese@pic.es) on behalf of ESCAPE-PIC working group





Institut de Física

d'Altes Energies























WP2 Use case: Long haul ingestion and replication

Description/Goal: Ingestion of MAGIC data from a remote site to the ESCAPE's data lake. Data Transfer and replication in off-site and after replication deletion of the data at the origin.



















Deterministic RSEs

WP2 Use case: Long haul ingestion and replication

Description/Goal: Ingestion of MAGIC data from a remote site to the ESCAPE's data lake. Data Transfer and replication in off-site and after replication deletion of the data at the origin.

ESCAPE's Rucio results
















WP2 Use case: Long haul ingestion and replication

Description/Goal: Ingestion of MAGIC data from a remote site to the ESCAPE's data lake. Data Transfer and replication in off-site and after replication deletion of the data at the origin.

















WP2 Use case: Long haul ingestion and replication

Description/Goal: Ingestion of MAGIC data from a remote site to the PIC's data lake. Data Transfer and replication in off-site and after replication deletion of the data at the origin.

















Rucio: Kubernetes Cluster

Deployed with:


- The Rucio server and daemon services are fully packaged with Helm
- Available in: https://rucio.github.io/helm-charts/

Monitoring:

Will be using Prometheus for all our monitoring needs

Logging:

- Were currently writing the logs using hermes2 in our own
- Elasticsearch centralized instance
- Limitation of current deployment:PIC's File Transfer system
 - Test instance




















Rucio web-ui:





Rucio: Kubernetes Cluster










cherenkov telescope





Daemon Name

- ludae
- Automatix
- Conveyor
- Undertaker
- Hermes2
- Kronos
- Reaper Necromancer
- Transmogrifier
- Abacus

Daemon activity

- replication rule engine
- generates fake data and upload it on a RSE
- handles requests for data transfers
- obsoleting data identifiers with expired lifetime
- delivers messages to an asynchronous broker
- consumes tracer messages and updates replica last access time accordingly
- deletion of the expired data replicas
- tries to repair erroneous rules, by selecting different replica destinations
- is responsible to apply subscriptions and to generate replication rules











cherenkov telescope

Rucio: Kubernetes Cluster

Deployed with:

The Rucio server and daemon services are fully packaged with Helm

Available in: https://rucio.github.io/helm-charts/)

Monitoring:

Will be using Prometheus for all our monitoring needs


Logging:

Weare currently writing the logs using hermes2 in our own

Elasticsearch centralized instance

Limitation of current deployment:

Test instance










PIC-CTA Rucio instance:

Orchestration of rule creation and automatic removal

PROGRESS:

- 1) Data is injected from the storage system located at the source (ORM La Palma):
 - a) Currently testing a non-deterministic RSE configuration at la Palma that allows to register files with their original path in the detector.
- 2) By means of the RUCIO API, we automate the orchestration of the data: using replication rules:
 - a) Files are replicated through different research facilities among the Data Lake.
 - b) Once replicated, source files are removed.


























MAGIC Workflow - Roadmap



Configuration:

- Storage Element 1: IT Container Endpoint
- Storage Element 2: PIC Endpoint

RUCIO and auxiliary code will run on PIC side except the Onsite DB and Onsite DB registration procedure.










cherenkov telescope array

File creation, discovery, replication and deletion cycle














cherenkov telescope array

File creation, discovery, replication and deletion cycle












PIC's Rucio internal monitoring dashboard



Results

The results obtained in the PIC's rucio instance and activity files transfer dashboards show similar patters to those obtained wih the ESCAPE rucio instance












MAGIC Workflow - Acomplished goals



Conclusions

 Using the rucio instance of the PIC, we have been able to transfer data from the Palma to the PIC from symbolic links to the gamma ray telescope observations via PIC's FTS.












MAGIC Workflow - Further steps



Next steps:

- We still need to feed the onsite database to change the replication states.
- Migrate the current test Rucio instance to a production environment.