



The EP/DT Quality Assurance and Reliability Testing Lab

Alessandro La Rosa (CERN EP/DT)

RSA Working group meeting
June 17, 2021

Detector Technology Group

The **mandate of the EP-DT** group comprises development, construction, operation and maintenance of **particle detectors for the experiments** at CERN. The group also offers a range of **services and infrastructure** for experiments and detector R&D

Services

Infrastructure for experiments:

- Gas systems
- Detector cooling systems
- Instrumentation and controls

Infrastructure for Detector R&D:

- Thin film & glass Lab
- Silicon facility
- Wire-bonding
- **QART Lab**
- Micro-Pattern Technologies
- Irradiation facilities
- Specialized labs (optics, gluing...)
- Scintillator production

Engineering office

R&D Projects

- Radiation tolerant silicon detectors (RD-50)
- Gaseous detectors (RD-51)
- Scintillating fibre detectors
- Micro-systems engineering


Joint Projects

- M&O and Upgrades of the LHC experiments
- AEgIS, CAST, CLOUD, NA62
- R&D for Linear Collider Detectors

In 2008 the **Quality Assurance and Reliability Testing (QART)** lab was founded to help with the LHC detector upgrade projects.


Since then, the following services are maintained by the EP-DT group in B186 :

- **Common cleanroom area** for experiments and projects working on silicon detector development
<https://ep-dep-dt.web.cern.ch/department-silicon-facility-dsf>
- **Bond lab** providing micro-connection service and advice for detector connectivity
<https://ep-dep-dt.web.cern.ch/wire-bonding-lab-bondlab>
- **QART lab** providing support and advise for detector QA matters
<https://ep-dep-dt.web.cern.ch/quality-assurance-and-reliability-testing-lab-qartlab>



QA and **Reliability Testing** are important in large projects as the **silicon detector upgrades**, where there are:


- **Huge number** of identical or similar components (~20'000 modules)
- **Extreme environmental conditions** (radiation, operating temp)
- **No access** → **no chance to repair** the devices
- **Mass production** with **tight time scale**
- **Limited budget**




The QART lab



- Provides resources concerning **quality assurance** to the CERN detector technology community
 - Provides equipment and expertise in order to perform **reliability testing** and **visual inspection**
 - Provides also advice and assistance in many aspects of silicon detector design, construction, and operations
-
- Team: A. La Rosa (contact person), R. Costanzi, F. Manolescu, I. McGill





Two climatic chambers

- Temp range: -70C to +180C
- Humidity range: 10% to 90%

Stereo microscope
Continuous magnification:
7x to 45x

Electromagnet


- Magnetic field: 0-2T

Freezer
Constant temp at -40C

Bond Lab DSF cleanroom QART Labs Air Treatment Plant room SSD Lab Meeting room

Vibration system

- Mono-axial shaker, up to 6.3kHz



Cleanroom ISO7 accessible via DSF cleanroom

3D digital microscope

- CMOS 2.4 MPixel captor
- x35-x5'000 triple objective zoom lens, including auto-calibration system and dual illumination mechanism with both coaxial- and ring-lighting
- 2D and 3D stitching application
- 3D profiling & roughness measurements (Ra, Rz), and angle & radius measurements

Stereo-microscope

- revolving nosepiece with two objectives (1.0x and 1.6x)
- continuous magnification range from 7.8x to 384x
- 5M pixel HD Camera (MC170) and measurement sw kit
- manual 6x4" XY stage

 Bond Lab

 DSF cleanroom

 QART Labs

Equipment and examples of use-case

Equipment and example of use-case

Climatic chambers



ESPEC (380L)


- Temp range: -70C to +180C
- Humidity range: 10% to 95%
- Max heating speed: 15C/min
- Max cooling speed: 11C/min




CLIMATS (140L)

Expected use:

- Thermal cycling, Accelerated lifetime,
- Humidity tolerance, Cold tolerance,
- Stress screening, Environment simulation



Principle diagram of the cabinet with double air flow ventilation



Equipment and example of use-case

Climatic chambers


Some tests recently made:

- ATLAS NSW: 1'000 elect cards th. cycling
- ATLAS ITK: encapsulated wire bonds th. Cycling
- ATLAS ITK: silicon/flex heaters temp calibration
- ALICE ITS: upgrade module accelerate lifetime
- CMS Tracker: 2S module thermal cycling
- CMS ECAL: elct cards accelerate lifetime (high temp)
- EP-ESE: > 12'000 DC-DC converters th. cycling
- LHCb RICH: upgrade elect cards th. cycling
- TE-MPE control module of beam energy extraction system th. cycling





Equipment and example of use-case

Vibration Tester



Mono-axial shaker with control system and analysis tools for Random, Sine, Shock, and Recorded vibration inputs. It can perform:

- Destructive testing
- Stress screening
- Playback of transport and handling vibrations and shocks





- Mono-axial shaker
- Frequency range: DC -6300 Hz
- Max acceleration - sine peak: 100G
- Max displacement: 25mm
- Armature diameter 110cm

Equipment and example of use-case

Vibration Tester

Playback of transport and handling vibrations






Equipment and example of use-case

Vibration Tester






Some other tests recently made:

- EN & BE: 10G shock-test and random truck transport profile excitation for a RF antenna cavity for HL-LHC upgrade
- EN/MME: measurement of ground motion condition due to HL-LHC civil engineering works as validation of survey equipment for measurement in the LHC tunnel



Equipment and example of use-case

3D digital microscope






- CMOS 2.4 MPixel captor
- x35-x5'000 triple objective zoom lens
- 2D and 3D stitching application
- 3D profiling & roughness measurements

Some inspection recently made:

- ATLAS ITK Pixel module flex inspection and bowing measurements
- CMS Tacker 2S Front-End Hybrids visual inspection
- RD50 silicon sensors inspection
- STREAM MALTA chip visual inspection
- ATTRACT-SWaP temp sensors inspection
- TE-MSK PCB inspection and 3D profiling and roughness measurements

Equipment and example of use-case

High Field Magnet



Electromagnet:

- Pole diameter: 38 mm
- Variable pole gap: 0-86 mm
- Magnetic field: 0-2T

Some tests made:

- ATLAS IBL: study of wire-bonds operation in 2T magnetic field
- ALICE CPV: operation validation of electronic modules in 0.5 T magnetic field

Equipment and example of use-case

IR thermal imaging Video Camera

High sensitivity (0.1°K) thermal imaging IR video camera 160 x 120 pixels.

Measurement range: -20°C to $+250^{\circ}\text{C}$.



Expected uses:

- Identifying hot spots in detectors
- Heat flow study on front-end PCBs and detector modules

Some example of tests made:

- CMS Inner Tracker (RD53 module)
- ATLAS ITK (Heaters)
- ATLAS Pixel (FEI4 chip on PCB)



Summary

- Projects that require **High Levels of Reliability** should carefully evaluate the operation and environmental conditions of the devices in the final functioning system and testing for long-term reliability
- The **QART lab** is a dedicated lab with a variety of **reliability test** and **visual inspection equipment**
- The lab provides services to the CERN community supporting projects working mainly on novel detectors
- All the 4 main LHC experiments have upgrade projects that used the lab facilities as well as groups in as EN, TE and BE depts.

Summary

- Projects that require **High Levels of Reliability** should carefully evaluate the operation and environmental conditions of the devices in the final functioning system and testing for long-term reliability
- The **QART lab** is a dedicated lab with a variety of **reliability test** and **visual inspection equipment**
- The lab provides services to the CERN community supporting projects working mainly on novel detectors
- All the 4 main LHC experiments have upgrade projects that used the lab facilities as well as groups in EN, TE and BE depts.

You are welcome to make use of our facility !!!

<https://qartlab.web.cern.ch/home>