

An aerial photograph of a large, open field with a river winding through it. In the background, there are several buildings, including a prominent white, curved structure. The sky is clear and blue.

Project X Cryomodule Status

Jim Kerby
(w/ thanks to the Project X team)


SPL Meeting

CERN
19 October 2010



Fermilab is the sole remaining U.S. laboratory providing facilities in support of accelerator-based Elementary Particle Physics

⇒ ***The Fermilab strategy is to mount a world-leading program at the intensity frontier, while using this program as a bridge to an energy frontier facility beyond LHC in the longer term.***




Evolution of the Fermilab Accelerator Complex



- A multi-MW Proton Source, Project X, is the linchpin of Fermilab's strategy for future development of the accelerator complex.
- Project X provides long term flexibility for achieving leadership on the intensity and energy frontiers
 - Intensity Frontier:
NuMI → NOvA → LBNE/mu2e → Project X → Rare Processes → NuFact
 - Continuously evolving world leading program in neutrino and rare processes physics; opportunities for applications outside EPP
 - Energy Frontier:
Tevatron → ILC or Muon Collider
 - Technology alignment
 - Fermilab as host site for ILC or Muon Collider



Project X website:
<http://projectx.fnal.gov/>



- 3 GeV CW linac provides greatly enhanced rare process program
 - ~3 MW; flexible provision for beam requirements supporting multiple users
- Preferred option for 3-8 GeV acceleration: 1.3 GHz pulsed linac
- Reference Design Report in final edit

Project X Performance Goals





Linac

Requirement	Description	Value
L1	Delivered Beam Energy, maximum	3 GeV (kinetic)
L2	Delivered Beam Power at 3 GeV	3 MW
L3	Average Beam Current (averaged over >1 μ sec)	1 mA
L4	Maximum Beam Current (sustained for <1 μ sec)	10 mA
L5	The 3 GeV linac must be capable of delivering correctly formatted beam to a pulsed linac, for acceleration to 8 GeV	
L6	Charge delivered to pulsed linac	26 mA-msec in < 0.75 sec
L7	Maximum Bunch Intensity	1.9×10^8
L8	Minimum Bunch Spacing	3.1 nsec (1/325 MHz)
L9	Bunch Length	<50 psec (full-width half max)
L10	Bunch Pattern	Programmable
L11	RF Duty Factor	100% (CW)
L12	RF Frequency	325 MHz and harmonics thereof
L13	3 GeV Beam Split	Three-way

3-8 GeV Pulsed Linac


Requirement	Description	Value
P1	Maximum beam Energy	8 GeV
P2	The 3-8 GeV pulsed linac must be capable of delivering correctly formatted beam for injection into the Recycler Ring (or Main Injector).	
P3	Charge to fill Main Injector/cycle	26 mA-msec in <0.75 sec
P4	Maximum beam power delivered to 8 GeV	300 kW








- ~4% duty factor, 200 1300MHz cavities operating at 25 MV/m
- 25 ILC-type (Type IV) Cryomodules
- Existing design, CM1 cooldown next week, CM2-6 following (in addition to XFEL pre-production / production experience)
- Technical R&D into injection into Main Injector at lower energies






FNAL vertical test result 21.May 2010:
 34.6 MV/m maximum gradient with
 $Q_0=1.2E10$ (quench)
 No field emission measured above
 background


TB9RI029 is first FNAL/ANL-
 processed production-style cavity to
 reach ~35 MV/m
 Bulk-EP was at RI

[AES003 after a long history was also
 light-EP'd recently at FNAL/ANL and
 reached 32.2 MV/m (some FE);
 TB9RI024, also with FNAL/ANL light-
 EP, reached 33.9 MV/m; some FE]




JLab vertical test data 7.Oct 2009:
TB9AES009 maximum gradient
36.0 MV/m with $Q_0=9.1E9$
(quench)

FNAL HTS data April/May 2010:
TB9AES009 maximum gradient
35 MV/m with $Q_0=6.6E9$ (quench)




3GeV cw Linac Technology Map



Section	Freq	Energy (MeV)	Cav/Mag/CM	Type
SSR0 ($\beta_G=0.11$)	325	2.5-10	26 /26/1	SSR, solenoid
SSR1 ($\beta_G=0.22$)	325	10-32	18 /18/ 2	SSR, solenoid
SSR2 ($\beta_G=0.4$)	325	32-160	44 /24/4	SSR, solenoid
LB 650 ($\beta_G=0.61$)	650	160-520	42 /21/7	5-cell elliptical, doublet
HB 650 ($\beta_G=0.9$)	650	520-2000	96 /12 /12	5-cell elliptical, doublet
ILC 1.3 ($\beta_G=1.0$)	1300	2000-3000	64 /8 /8	9-cell elliptical, quad


3GeV cw Linac Technology Map



Section	Freq	Energy (MeV)	Cav/mag/CM	Type
SSR0 ($\beta_G=0.11$)	325	2.5-10	26 /26/1?	SSR, solenoid
SSR1 ($\beta_G=0.22$)	325	10-32	18 /18/ 2	SSR, solenoid
SSR2 ($\beta_G=0.4$)	325	32-160	44 /24/4	SSR, solenoid
LB 650 ($\beta_G=0.61$)	650	160-487	36 /24/4?	5-cell elliptical, doublet
HB 650 ($\beta_G=0.9$)	650	487-3000	160 /38 /20	5-cell elliptical, doublet



- Identify maximum achievable surface (magnetic field) on basis of observed Q-slope “knee”
- Select cavity shape to maximize gradient (subject to physical constraints)
- Establish Q goal based on realistic extrapolation from current performance
 - Goal: <25 W/cavity
- Optimize within (G, Q, T) space



(Initial) Performance Goals

Freq (MHz)	B_{pk} (mT)	G (MV/m)	Q	@T (K)
325	60	15	1.4E10	2
650	72	16	1.7E10	2
1300	72	15	1.5E10	2

SRF Technology Development




← Single Spoke Resonators
(325 MHz)
Roark, Zanon, IUAC...

→ Elliptical Cavities
(650 and 1300 MHz)
AES, RI, Jlab, Cornell, Niowave-
Roark, RRCAT, Pavac....






- Roark and Zanon SSR have been tested successfully
- Two in process at IUAC
- 10 more ordered from Roark
- SSR0, SSR2 designs following
- Ultimately a prototype SSR1 Cryostat will be assembled






- 1 CM of SSR0, 18 – 26 cavities




Vent pipes every 6 - 8 cavities, 40+ mm thermal contraction, assembly



- 2 CM of SSR1, Minimize of the inter-cryostate drift space



- 4 CM of SSR2, Provide drift space by missing cavity




From Nikolay Solyak
Project-X, CW Linac (ICD-2+)
Lattice Design, 16 Mar 2010





- Prototype design being developed to test 3 SSR1 and 4 solenoid magnets

650 Low and High Beta Optics







- Individually segmented, each with ~250W to 2K
- Design options range from “Spaceframe” to “TESLA” derivatives
- Discussion on the effect of vapor and liquid volumes fractions and flow rates on pressure regulation



CM-650-3
(48" Pipe VESSEL)



CM-650-2
(48" Pipe VESSEL)





-
- The optics design of the 2-3 GeV portion of the Project X CW Linac is under review.
 - The dynamic heat load per cavity, and per cryomodule, has individually segmented cryomodules under serious consideration for the CW linac
 - Initial alignment tolerances are 0.5mm rms, with a 1mm limit. The use of multiple correction elements and BPMs is motivating the numbers
 - 650 Beta = 0.9 optics are more settled than Beta = 0.61 optics on a 'cryomodule' basis
 - Warm and cold magnet options are under consideration.
 - Inclusion of heat exchangers and cryogenic bayonets in the interconnect or directly from the vacuum vessel in discussion



U.S. Fiscal Year	2008	FY09	FY10	FY11	FY12	FY13	FY14	FY15
1.3 GHz								
CM1 (Type III+)		CM Ass'y	Install CM	CM1 Test				
CM2 (Type III+)	Omnibus Delay	Process & VTS/Dress/HTS			CM Ass'y swap?			Operate Complete RF Unit @ Design Parameters
CM3 (Type IV)		Design	Order Cav & CM Parts			2CM ?		
CM4 (Type IV)							RF unit at low rep rate?	
CM5 (Type IV)							swap?	
CM6 (Type IV+) CW Design				Design CM ? 1.3 GHz CW				Install in CMTF
NML Extension Building		Design	Construction					
NML Beam				Move injector/install beam components	Beam Available to RF Unit test except during installation periods (contingent upon cryogenic load/capacity)			
CMTF Building			Design	Construction				
650 MHz								
Single Cell Design & Prototype								
Five Cell Design & Prototype								
CM650_1				Design	Order 650 Cav & CM Parts	Process & VTS/Dress/HTS	650 CM Ass'y	
325 MHz								
SSR0/SSR2 Design & Prototype			Design (RF & Mechanical) all varieties of Spoke Reonators		Prototype (as required)	Process & Test (as required)		
SSR1 Cavities in Fabrication (14)			Procurement (already in progress)	Process & VTS/Dress/STF				
CM325_SSR1_proto CM				Design	Procure 325 CM Parts	325 CM Ass'y		

Design
Procure
Process & VTS Dress & HTS
Assemble
Install
Commission & Operate



-
- Project X is central to Fermilab's strategy for development of the accelerator complex over the coming decade
 - World leading programs in neutrinos and rare processes
 - Aligned with ILC and Muon Accelerators technology development;
 - Potential applications beyond elementary particle physics
 - The machine design is converging, though iterations of the optics are underway (and expected) at this conceptual stage
 - At a minimum with respect to SPL cryogenics, alignment, and component thermal performance all appear to be areas of useful cross-calibration if not collaboration
 - Fermilab Director and CERN DG signed a letter of intent on future cooperation last friday