# Future facilities in muon research at J-PARC

#### Takayuki YAMAZAKI,

N. Kawamura<sup>1</sup>, K. Shimomura<sup>1</sup>, Y. Miyake<sup>1</sup>, Y. Oishi<sup>1</sup>, T. Adachi<sup>1</sup>, P. Strasser<sup>1</sup>, A. Koda<sup>1</sup>, H. Fujimori<sup>1</sup>, T. Yuasa<sup>1</sup>, Y. Ikedo<sup>1</sup>, Y. Kobayashi<sup>1</sup>, K. Sasaki<sup>1</sup>, T. Mibe<sup>1</sup>, T. Ushizawa<sup>2</sup>, Y. Higashino<sup>3</sup>, D. Nagao<sup>3</sup>, M. Aoki<sup>3</sup>, K. Hase<sup>4</sup>, S. Kaneko<sup>4</sup>, R. Tagawa<sup>4</sup>, T. Uematsu<sup>4</sup>, Y. Seiya<sup>4</sup>, S. Uetake<sup>5</sup>, T. Masuda<sup>5</sup>, H. Tada<sup>6</sup>, S. Sugiyama<sup>6</sup>, and K. Suzuki<sup>6</sup>

<sup>1</sup>KEK, <sup>2</sup>SOKENDAI, <sup>3</sup>Osaka University, <sup>4</sup>Osaka Metropolitan University, <sup>5</sup>Okayama University, <sup>6</sup>Nagoya University


#### Contents

- J-PARC muon facility
- New beamlines for fundamental physics
  - H1 area of H-line
  - S2 area of S-line
- Extension of the H-line (near future)
  - H2 area and an extension building for muon g-2/EDM and transmission muon microscope
- Future program: 2<sup>nd</sup> target station of the MLF

# J-PARC muon facility


#### J-PARC

J-PARC (Japan Proton Accelerator Research Complex)



## J-PARC muon facility

MUSE (MUon Science Establishment) in the MLF



#### H-line

- surface  $\mu^+$  (10<sup>8</sup>  $\mu^+$ /s), cloud  $\mu^+/\mu^-$  (up to 120MeV/c)
- for high intensity & long beamtime experiments
- H1 for MuSEUM & DeeMe, started operation in Jan. 2022!
- H2 for g-2/EDM & TμM, under construction


#### D-line

- decay μ+/μ-, surface μ+
- D1 area for μSR
- D2 for variety of science


# New beamlines for fundamental physics

#### New two beamlines since JFY2021

- H1 area (1st branch of the H-line): MuSEUM & DeeMe
- S2 area (2<sup>nd</sup> branch of the S-line): Mu 1S-2S




#### H-line



- H-line is a high intensity muon beamline which can deliver both of surface  $\mu^+$  and cloud  $\mu^+/\mu^-$ .
- Beamline optics
  - HS1 : large acceptance (108mSr) capture solenoid
  - HB1,2 : wide gap (300mm) bending magnet
  - HS2,3: Two superconducting solenoid with opposite polarities
  - HSEP: Wien filter to reduce e<sup>+</sup>/e<sup>-</sup> background (not installed yet...)
  - HQ123: Q-triplet for final focusing
- Surface muons of  $10^8 \, \mu^+/s$  are expected to the H1 area with a graphite target and 1MW proton beam.
- First beam on 15<sup>th</sup> Jan. 2022!

### $\pi/\mu$ capture solenoid of the H-line

Most important to get intense beams



Spec.	Rating	Now
HS1-1: 0.37T	(3000A)	1500A
HS1-2: 0.31T	(3000A)	1500A
HS1-3: 0.60T	(2600A)	900A



- The solenoids are wound with normal conducting Mineral Insulation Cables (MIC) to get enough radiation resistance.
- Due to the failure of the power supplies, maximum currents are limited now...

## H-line construction history

JFY2012 Frontend devices




JFY2020 Install magnets



JFY2016 Radiation shield




JFY2021 Cabling, plumbing






JFY2017~2019: Electric sub-station \* For the NC capture solenoid






## H-line commissioning: Surface μ

#### **Beam intensity measurement**





- Number of detected positrons per pulse (25Hz) = 1.6 e<sup>+</sup>/pulse
- Detector acceptance (sim.) =  $7 \times 10^{-7}$
- Detection efficiency of scintillators = 0.89
- Transmission efficiency of Kapton window (sim.) = 0.87



The thickness of Kapton =  $50 \mu m$ , but it is a mesh window to withstand atmospheric stress.

• Proton beam power = 730 kW

9.9 x  $10^7 \,\mu^+/s \,@1MW$  (*Preliminary*), almost the same as our expectation.

~10% increase is expected if we fix the power supplies of the capture solenoid.


# H-line commissioning: Surface μ

#### **Momentum measurement**

- Almost the same setup as the intensity measurement
- Al target in a magnetic field of 23.85 G
- Beat amplitude of wiggle plot
  (∞number of stopped muons) is
  plotted as a function of Al thickness



#### Range measurement




From μ<sup>+</sup> range in Al target, we estimated


P = 28.0 MeV/c (RMS 1.2 MeV/c) in the beamline as expected.


# H-line commissioning: Surface μ

#### Beam profile measurement




- BG and decay positrons are blocked by the acrylic block.
- Cherenkov lights from the acrylic block cannot pass through the UV filter.
- To select surface μ<sup>+</sup>, we adjusted the shutter timing.





# H-line commissioning: Cloud μ<sup>-</sup>

- We measured intensities of cloud  $\mu^{-}$  up to 80 MeV/c.
  - ✓ Upgrade of the power supplies, which is scheduled in this JFY, is necessary for higher momentum.




Consistent with Geant4 and G4beamline simulation (Model: QGSP\_INCLXX)


#### MuSEUM @H1 area

Muonium (Mu)

→ Next talk by K. Shimomura



Precise measurement of the hyperfine structure of muonium






Previous experiment: 4 463.302 765 (53) MHz (LAMPF1999)

Precision of 8 Hz will be reached by a high field measurement at the H-line.

A Wien filter to eliminate e<sup>+</sup> BG is inevitable for this experiment and will be installed in this JFY.

#### DeeMe @H1 area


- Search for  $\mu$ -e conversion (sensitivity ~ 10<sup>-14</sup>)
  - Pilot RUN was conducted at the H1 area in July 2022.



Production target










#### S2 area and Mu 1S-2S


→ Next talk by K. Shimomura



- 2<sup>nd</sup> branch of S-line dedicated to Mu 1S-2S spectroscopy
  - ✓ Surface muon beamline:  $2 \times 10^6 \,\mu^+/\text{s}$  (single bunch)







# Extension of the H-line (near future)

#### Further extension of the H-line


At the 2<sup>nd</sup> branch of the H-line, ultra slow muons will be re-accelerated up to 200 MeV to obtain a low-emittance (1  $\pi$  mm\*mrad) muon beam.

#### Muon g-2/EDM experiment

The low-emittance muon beam enables us not to use a strong focusing E-field.


Complementary method to check the


discrepancy



#### **Transmission muon microscope (TμM)**

Dobserve bulk samples utilizing the strong penetrative power of re-accelerated muons







#### Further extension of the H-line


At the 2<sup>nd</sup> branch of the H-line, ultra slow muons will be re-accelerated up to 200 MeV to obtain a low-emittance (1  $\pi$  mm\*mrad) muon beam.

#### Muon g-2/EDM experiment

The low-emittance muon beam enables us not to use a strong focusing E-field.


Complementary method to check the


discrepancy



#### **Transmission muon microscope (TμM)**

Dobserve bulk samples utilizing the strong penetrative power of re-accelerated muons









#### Schedule of the H-line extension

• This JFY: construction of the 2<sup>nd</sup> branch (H2 area)



# Manufacturing its concrete shields






# Schedule of the H-line extension


 Apparatuses to produce ultra slow muons (25 meV) and accelerators up to 4.5 MeV will be installed from the next JFY.

> 1x 122 nm (1S-2P) or 2x 244 nm (1S-2S) + 355 nm (ionization)



#### Schedule of the H-line extension

Construction of a new building will be started from the next JFY



#### Preparatory works before construction


Geotechnical investigation



Research of buried cultural properties



Survey of the construction site




..., and the relocation of buried cables is ongoing now.


# Future program: 2<sup>nd</sup> target station of the MLF

# J-PARC MLF 2<sup>nd</sup> target station

Conceptual Design report v1.2



## Muon beam optics



## Summary

- New beamlines (H1 and S2) joined the J-PARC muon facility.
  - H-line is a high intense muon beamline (surface  $\mu^+ > 10^8$  /s)
  - H1 area: MuSEUM and DeeMe experiments
  - S2 area: Mu 1S-2S
- Further extension of the H-line is ongoing.
  - H2 area is going to be constructed in this JFY.
  - Construction of the low emittance beamline will start from the next JFY, and preparatory works are underway.
- Conceptual design of the 2<sup>nd</sup> target station of the MLF is in progress.
  - >50 times more intense muons could be available.