

# Neural Networks for Estimation of Gamma-Ray Burst Redshifts

*Tuesday 11 October 2022 10:38 (1 minute)*

A wealth of Gamma-Ray Burst (GRB) data is available today with known redshifts (observed up to  $z=9.4$ ), provided by different instruments with well-measured prompt gamma-ray flux and spectral information. In order to estimate redshifts of GRBs using a theoretical estimate (so-called pseudo-redshifts) from spectral relations, several phenomenological relations have been developed. Amati relation between the peak energy  $E_{i\_peak}$ , in the cosmological rest frame of the GRB at which the  $\nu f_\nu$  spectrum peaks and the total isotropic-equivalent radiated energy in gamma rays  $E_{iso}$  is one such example. Another example is the Yonetoku relations between the  $E_{i\_peak}$ , and isotopic luminosity  $L_{iso}$ . In this work, we adopt a machine learning technique (Neural Networks) to estimate redshifts from different observable GRB properties with a large sample of data collected by the Gamma-ray Burst Monitor (GBM) onboard the Fermi Gamma-ray Space Telescope. Such a technique is useful to explore any hidden, non-linear relations between the parameters. Estimation of pseudo redshift is useful to standardize GRBs as cosmological probes.

## Track

GRBs

**Primary author:** ALDOWMA, Tamador (Johannesburg University, Omdurman Islamic University)

**Co-author:** RAZZAQUE, Soebur

**Presenter:** ALDOWMA, Tamador (Johannesburg University, Omdurman Islamic University)

**Session Classification:** Poster session