# Status GEM Detectors

Dmitri Schaab / Bernhard Ketzer

COMPASS/AMBER Technical Board 08.02.2022

## COMPASS GEM-3G (CG3G)

- Size of active area:  $30.7 \times 30.7 \text{ cm}^2$
- Strips divided in center to reduce occupancy
- Triple GEM, foils sectorized on top (13 sectors)
- No spacer grids
- Gas in/out on drift plate, internal distribution



- Stabilized voltage divider: 3 +1 cards
- 6 × 4 front-end cards, 4 supply cards (bus cards)



### Status of detector parts (drift foils + GEMs + R/O-foils)

- CERN Batch 1: shipped 20.10.2020
  - -~ 6 GEM foils (2µm Cu)  $\Rightarrow$  1 bad (high current), 5 good
  - 3 drift foils (2µm Cu)  $\Rightarrow$  3 good
  - 2+1 R/O foils  $\Rightarrow$  3 good
- CERN Batch 2:
  - 10 GEM foils (2µm Cu), shipped 30.8.2021  $\Rightarrow$  1 bad (high current), 7 good, 2 not yet tested
  - 2 drift foils (2µm Cu), shipped 30.8.2021  $\Rightarrow$  2 good
  - 2+1 R/O foils, shipped 27.10.2021  $\Rightarrow$  2 good, 1 bad (known)
- CERN Batch 3: ordered  $\Rightarrow$  to be finished by end of February
  - 7 GEM foils (minor design improvements)
  - 1 drift foil
  - 1 R/O foil
- > **GEMs:** 12 good + 2 unknown + 7 ordered  $\Rightarrow$  ≥6 detectors
- > Drift: 5 good + 1 ordered  $\Rightarrow$  6 detectors
- > R/O: 5 good + 1 ordered  $\Rightarrow$  6 detectors

## **Status of Production**

- Honeycomb plates (Piekenbrink)
  - Batch 1a: 2 drift plates, 2 R/O plates (potted, bent)  $\Rightarrow$  re-treated, flattened
  - Batch 1b: 2 R/O plates (GFK frame)  $\Rightarrow$  good
  - Batch 2: 2 R/O plates, 2 drift plates,  $\Rightarrow$  good
  - Batch 3: ordered 2 sets of R/O and drift plates
- **GEM frames** (local workshop):
  - full frame sets for 3 detectors available (drift, transfer, induction)
  - 10 parts for 2.5 transfer frames available
  - spare material for segmented frames available
  - ordered material for 10 drift frames + 20 transfer/induction frames
- Currently: Material for 5 detectors total (incl. backup material)
- ➤ Mid March (supply bottlenecks): Material for ≥8 detectors total
- **QA improved:** intersegment test automated (J. Paschek)
- Production database set up for COMPASS (taken over from ALICE / P. Glässel)

2 detectors (avail./spare)

4 detectors (available)

2 detectors (ordered→mid March)

- 3 detectors (available)

~2 detectors (backup material)

≥6 detectors

(ordered→mid March)

## **Database for Production**

step (link) status

1 1

2

3

6

7

8 8

9 9

20 20

25

3

6

7

15 QA-

A

25

(hover cursor

quick defect m

intersegment to

leakage curren

absolute humid spark map uple

9 9 possibility to up map
10 QA-E Lleak histo da

long term leaka

frame glueing

quality

spark map

2 HV cleaning

- Stock keeping integrated
- QA steps/files included
- Trackable construction chain

		(Datc	h 1) c	ontains	(only	next	level	):		
type	prefix	num	serial	no batch	da	ite	status	link o	comm	
	GMS	0	GMS-	01 1	2022-	01-28		X		
	RP	0	RP-01		2022-	01-28		Δ		
dify /GM	<mark>conta</mark> IS-01	<mark>ined</mark> (bate	parts :h 1) (	contains	s (only	y next	t leve	l):		
	type	prefix	num	serialno	batch	da	ıte	status	link	comm
		DP	0	DP-01		2022-	01-28		X	
		GM1	0	GM1-01	1	2022-	01-28	0	X	
GEM	l I	GM2	0	GM2-01	1	2022-	01-28	0	X	
		GM3	0	GM3-01	1	2022-	01-28	0	Ă	
<mark>lify c</mark> 2/GN	<u>:ontai</u> 12-01	ined j (bato	p <mark>arts</mark> ch 1)	contains	s (onl	y nex	t leve	l):		
уре р	refix 1	num	serial	no batcl	h d	ate	statu	s link	com	nent
	dify /GM GEM lify c	GEM GEM CGM2-01	GMS 0 RP 0 dify contained /GMS-01 (batc type prefix PP GEM 2-01 (batc /GM2-01 (batc	GMS0GMS-RP0RP-01dify contained parts/GMS-01(batch 1)/gms-1(batch 1)typeprefixnum0GM10GEMGM20GEMGM30lify contained partsgmt/GM2-01(batch 1)	GMS0GMS-011RP0RP-01Idify contained partspartstype prefix num serialnotypepPefixnum serialnoGMGM10GM1-01GEMGM20GM2-01GEMGM30GM3-01lify contained partskgM2-01(batch 1) contained parts	GMS0GMS-0112022-RP0RP-012022-dify contained parts/GMS-01 (batch 1) contains (onlytype prefix num serialno batchQMDP0DP-01QMGM10GM1-01GEMGM20GM2-01GEMGM30GM3-01Ifty contained partsparts	GMS0GMS-0112022-01-28RP0RP-012022-01-28dify contained parts///////////////////////////////////	GMS   0   GMS-01   1   2022-01-28     RP   0   RP-01   2022-01-28     dify contained parts     /GMS-01 (batch 1) contains (only next level     type   prefix   num   serialno   batch   date     Q   QP   0   DP-01   2022-01-28     type   prefix   num   serialno   batch   date     Q   QP   0   DP-01   2022-01-28     GEM   GM1   0   GM1-01   1   2022-01-28     GEM   GM3   0   GM3-01   1   2022-01-28     Ifity contained parts   GM3   0   GM3-01   1   2022-01-28	GMS   0   GMS-01   1   2022-01-28   X     RP   0   RP-01   2022-01-28   X     dify contained parts     /GMS-01 (batch 1) contains (only next level):     type   prefix   num   serialno   batch   date   status     0   GM1   0   GM1-01   1   2022-01-28   0     GEM   GM1   0   GM1-01   1   2022-01-28   0     GEM   GM2   0   GM2-01   1   2022-01-28   0     GEM   GM3   0   GM3-01   1   2022-01-28   0     Itity contained parts   GM3   0   GM3-01   1   2022-01-28   0	GMS   0   GMS-01   1   2022-01-28   X     RP   0   RP-01   2022-01-28   X     dify contained parts     /GMS-01 (batch 1) contains (only next level):     type   prefix   num   serialno   batch   date   status   link     Q   Q   DP   0   DP-01   2022-01-28   X   X     GM1   Q   GM1-01   1   2022-01-28   X   X     GEM   GM2   0   GM2-01   1   2022-01-28   X   X     GEM   GM3   0   GM3-01   1   2022-01-28   X   X     GEM   GM3   0   GM3-01   1   2022-01-28   X   X     Ilify contained parts   GM3-01   1   2022-01-28   0   X   X     X/GM2-01   (batch 1) contains (only next level):   X   X   X   X   X

#### HISKP Compass production database, category Compass

link color codeserial nobarcodeunnumberedprefix color code:parent partdaughter partbothpart color code:QA defined

								unnumbered stock at institutes			numbered stock		
	link	category	part	batch	type	prefix	ordered	sent	Bonn	used	inventory	finished	used
	X	Compass	Drift foil			CD3G-nn					5		1
	X	Compass	Drift frame	1		D-frame			2				
	<u>X</u>	Compass	Drift GEM			GM1-nn							1
	<u>X</u>	Compass	Drift plate			DP-nn							1
	X	Compass	GEM foil			CG3G-nnn					13		3
	<u>X</u>	Compass	GEM stack			GMS-nn							1
	<u>X</u>	Compass	honeycomb plate large	1		HCL			1				
	<u>X</u>	Compass	honeycomb plate large	2		HCL			3				
	X	Compass	honeycomb plate small	1		HCS			1	- 1			
	X	Compass	honeycomb plate small	2		HCS			1				
	<u>X</u>	Compass	intermediate frame	1		I-frame			4	2			
	<u>X</u>	Compass	intermediate GEM			GM2-nn							1
	<u>X</u>	Compass	R/O foil			CR3G-nn					5		1
	X	Compass	R/O frame	1		R-frame			2				
	<u>X</u>	Compass	R/O GEM			GM3-nn							1
	X	Compass	R/O plate			RP-nn							1
	<u>X</u>	Compass	readout chamber			G3Mnn					1		
a field for explanations)			value	n		date			QA step/file comme	nt	author	condition	true?
					2022-	01-25	ok						
ар	defectmap.txt show		11:22:		26	0 0 0 2 defe	ects	Karl	file txt				
	done			2	2022-	01-26 :07					Karl	eq done	
est										4		eq ok	
t [pA] at 500 V	15				2022-	01-26					Karl	<= 167	
	do the sp	ark map			15.52	.21						file txt	
liter from \$73	2800	Ir-			2022-	01-26					V - 1	- 6000	
uty [ppm v ]	2800				13:32:	:27					Kari	<= 0000	
bad	Upload da	atafile:	Detai augustikit				file comme	nt:					
load existing spark	upload file	after cho	osing file!							4		file ok	
ta	06 CG30 evaluate	<u>G 01 03 N2</u>	framed_corrected.txt		2022- 13:31:	01-26 59	no commer	nt			Karl	file txt	
age current data	04_CG30 evaluate	<u>G 01 03 N2</u>	longterm_corrected.txt		2022- 13:31:	01-26 41	no commer	nt			Karl	file txt	
	ok			3	2022- 13:33	01-26 12					Karl	eq ok	
	A				2022-	01-26 36					Karl	le C	

## Status of Stabilized Voltage Divider (SVD)

- Single channel stabilized voltage divider (test):
  - 3 PCBs in use, one as **P**assive **V**oltage **D**ivider (PVD)
  - $_{\circ}$  Calibration done  $\Rightarrow$  voltage measurement working
  - Next Step: Test with detector  $\Rightarrow$  measure gain stability (B. Roth/Bachelor)
  - $_{\circ}$  5 more PCBs ordered  $\Rightarrow$  to be assembled
- Detector scale stabilized voltage divider
  - <sup>o</sup> updated version with minor fixes ready to be ordered, once needed
  - $_{\circ}$  HV cable between SVD boards  $\Rightarrow$  flex PCB (prototypes available)
- Passive voltage divider (PVD)
  - New PCBs in use, a few spare PCBs available
- Measurements / simulations with SVD/PVD ongoing
  - ⇒ results expected by end of February (C. Honisch, B. Roth)
- > See also: Talk on SVD by C. Honisch RD51-Meeting 07.02.2022

## Status of detector production

	Support plates	Frames	Drift foil	GEM foils	Readout PCB	HV board	Assembly	Calibration	Installation
CG3G01	✓	✓	✓	✓	✓	SVD	✓	~	Prototype
CG3G02	✓	✓	✓	~	✓	PVD	GAS		
CG3G03	✓	~	✓	~	✓		QA		
CG3G04	~	ordered	~	~	✓		QA		
CG3G05	ordered / spare material	/ spare material	~	ordered / spare material	~				

Assembly steps:

- QA: quality assurance
- G1, G2, G3: GEM i framed
- RO: R/O PCB glued
- D: drift foil glued
- S1, S2, S3: stack i glued
- DET: detector assembled
- GAS: gas pipes + tight
- HV: HV board assembled

Stations to be replaced for 2022: GM05, GM08 (GM04?) Installation: April/May 2022

## Timeline



## Front-end and readout electronics

- Front-end cards (APV):
  - APVs available for all detectors
  - 56 cards ready and tested (24 per det., 2 at TUM)
  - Components and PCBs for 100 cards available, some delay in assembly
- Supply cards (bus cards):
  - 2 produced and being tested (at TUM) / 6 PCBs in production  $\Rightarrow$  PCB + stencil + compontents available
  - bugfix for new PCBs: capacitor too high  $\Rightarrow$  add cut-outs
  - mating test with connectors to APV FE needs to be done  $\Rightarrow$  then ready to be assembled.
- ADC cards:
  - 2 produced, 1 working (at TUM), tested with IFTDC
  - 3rd assembled (solder process optimized)  $\Rightarrow$  to be tested by I. Konorov
  - after successful test: assemble more PCBs / PCBs + components still to be provided
  - components for 10-15 cards available, 2 per det. needed, delay in assembly (Covid)
  - full system test with APV to be performed at CERN (DAQ lab)
  - 9 IFTDC cards produced
  - ADC firmware ported to Artix FPGA (S. Huber) / Slow control implemented in config\_server (V. Frolov)

## AMBER PRM readout requirements

Starting point: 30x30 cm<sup>2</sup> with divided strips and active central sector / self-triggering VMM

- Readout of all 4 sides (1 detector)
- 768 channels per side (1 detector)
- 2 detectors per station in 6 stations

#### Requirements

- number of channels per projection: 2x768= 1536
- number of projections per station: 4
- number of stations: 6
- number of bits per hit: 38 raw from VMM / 48 with additional time stamp
- in progress: amount of information produced by one projection for nominal PRM beam (conditions in streamed mode ⇒ noisy hits + induced by charged particles)