EP-DT
Detector Technologies

CERN, 9 December 2021

ALICE

EP-DT contribution to ALICE

Massimo Angeletti

Yannick, Pieter, Philippe, Jaap, Gregory, Didier (DT-CO),
Paolo (DT-TP), Petra (DT-DD), Giovanna(DT-DI), Corrado (DT-EO)

DSF QART and Bonding lab, Composite lab, Micropattern lab, Workshop 162, Magnet M&O, GasSystem M&O, Irradation Facilities.



Outline

Long Shutdown 2

Detector installation

MFT



ITS Outer Barrel



ITS Inner Barrel

Long Shutdown 3

R&D Inner Tracking System

Inner detectors: MFT, ITS OB, ITS IB



Inner detectors: MFT, ITS OB, ITS IB



MFT

MFT Top inserted



MFT Bottom insertion

Dry insertion test



3D scan, metrology

Installation

MFT Top inserted

MFT Bottom insertion





ITS2 Outer Barrel

OB bottom insertion



OB Top rotation

Dry insertion test





OB Top insertion

OB Bottom inserted

ITS2 Outer Barrel



I/F verification

Minimum nominal gap 1.4mm

STAGE
TRANSPORT

ITS2 Outer Barrel

Installation

OB in its final position



Closing the gap



ITS2 Inner Barrel

Dry insertion test



ITS2 Inner Barrel



Inspection I/F verification

3D scan, metrology

ITS2 Inner Barrel

Installation



IB bottom inserted





Back side view

EP-DT CONTRIBUTION TO ALICE: (ITS2 FOR RUN3)

Detector design and construction and pre-commissioning (EP-DT-DD/TP/EO/CO).
Development of the entire installation sequence around the beampipe. (EP-DT-EO/CO).
Installation in ALICE of the two ITS OB H-barrels followed by the two ITS IB H-barrels

ITS2 safety system (ITS2S)



ITS2S main panel

Safety interlocks

1st Acquisition



First pp event reconstructed with ITS2

EP-DT CONTRIBUTION TO ALICE: (ITS2 FOR RUN3)

Safety system for the new ALICE ITS protected against over temperatures (EP-DT-DI)

Inner Tracking System 3 (ITS3) – LS3

R&D Directions towards unprecedented vertex minimum layers materials

(unprecedented low material budget of 0.05%)



➔ minimum material support and gas cooling

L0 L1 L2

➔ Wire bonding
at the edge side



➔ Chip stitching



➔Curved Silicon sensors



Inner Tracking System 3 (ITS3) – LS3

ALICE

Metrology assessment on the first prototype model



➔ Gluing optimisation





Baseline:
Carbon foam material

Support

ERG Carbon
@Duocel

ρ = 0.06 kg/dm³

K = 0.033 W/m·K

Support & **cooling**



Allcomp K9
Standard Density

ρ = 0.2-0.26 kg/dm3

K = >17 W/m·K

Inner Tracking System 3 (ITS3) – LS3

NEXT: wind tunnel thermal test of new dummy model with **carbon foam radiators**

Heat dissipation is non-uniform

L0 Matrix= 1W

L0 Periphery= 5.1W



Allcomp K9 standard density





EP-DT CONTRIBUTION TO ALICE: (ITS3 FOR RUN4)

Development of the mechanics and cooling system of a novel vertex detector, the ITS3. (EP-DT-EO/CO, MPT, TFG lab)

Thank you for your attention