

# Geodetic Deformation Measurement and Analysis of the ATLAS Experimental Cavern at CERN

Presentation: Witold NIEWIEM BE/GM/ESA

Project: Dirk MERGELKUHL, Witold NIEWIEM, Vitaly BATUSOV

10.12.2021

# Content

## 1. Introduction

Main subject

Monitoring and research motivation

## 2. Object

Introduction of objet

Floor presentation

Walls presentation

## 3. Methodology

Introduction of the measurement technique

Equipment

Survey monuments

Network

## 4. Measurement

Data extend

Floor deformation

Walls deformation

Systematic of movement


## 5. Conclusion

Designs in presentation are coming from [www.cern.ch](http://www.cern.ch)  
or own sources. Otherwise, it is explicitly marked

# Main subject of presentation

The project takes into consideration the following topic:

- Geometrical behaviour of the ATLAS cavern from July 2003 to Dec 2019
- Relationship between the cavern deformation and position of the experiment
- Movement causing factors, their direction and characteristic
- Conclusions concerning the ATLAS experiments and other underground facilities with high precision alignment demands




# Why is the monitoring going on?




In this context it should be considered that the civil engineering specification of the ATLAS experimental cavern **did not** include any limits for the deformation of the cavern.

# Why is it relevant for future?






# ATLAS cavern region – geology



sandstone





marl




<https://en.wikipedia.org/wiki/>

# LEP and LHC upgrade






# ATLAS cavern - geometry





# Overview of the ATLAS cavern





Measurements of USA and US wall in the perpendicular direction to the wall plane

Measurements of the base slab in 3D. Analysis separately for 1D (vertical) and 2D (horizontal) direction

# Base slab – the floor



<https://www.google.com/maps>




● Position of the survey points on the base slab



# USA wall – survey network


Area of connection of USA and US wall by direct measurement Side A





# USA wall – survey network


Survey gallery on level 4 A-side



Survey gallery on level 4 C-side

# US wall – survey network

Area of connection of USA and US wall by direct measurement Side C




Area of connection of USA and US wall by direct measurement Side A



# ATLAS cavern stability prediction


The civil engineering predictions for the ATLAS base slab:

- ↓ 2.0 mm down before ATLAS installation
- ↓ 5.5 mm down due to ATLAS installation
- ↑ 1.0 mm/year up caused by ground pressure
- ↑ < 1.0 mm/year up to stabilisation period







# Detector position requirements



# Vertical reference



# Horizontal reference






# HLS and WPS system

**WPS:** Monitoring a 'long' direction, 2D measurements

- conducting stretched wire (carbon peek)

**HLS:** Monitoring a 'large' plane



- water surface (communicating vessels)



# HLS bedplates monitoring

HLS  
Bedplate  
System

Old picture







# Coordinate system

The most important factors taken into account during network calculation

- Local geoid model
- Curvature of Earth
- Difference Ellipsoid to Geoid
  - up to 100 mm due to Jura and lake





# Measurement principle – 3D polar trigonometry


Measurement of :

- *Horizontal angle*  $\alpha$
- *Vertical angle*  $\beta$
- *3D distance*  $d$



Allows to find:

- *Coordinate difference*  $\Delta X$
- *Coordinate difference*  $\Delta Y$
- *Coordinate difference*  $\Delta Z$



# Measurement principle – optical levelling


Measurement of :

- Height of point  $H1$
- Height of point  $H2$



Allows to find:

- The height difference  $\Delta H$



# Measurement equipment



Wild NA2

Standard deviation for 1km  
double run levelling  $\pm 0,2$  mm



Wild TC2002

Angle (Hz, Vz)  $\pm 1.5$  cc  
Distance  $\pm 1$  mm + 1 ppm  
After 150  $\mu$ m calibration for the indoor measurements





Leica AT401

Angle (Hz, Vz)  $\pm 1.5$  cc  
Distance  $\pm 10$   $\mu$ m  
Distances measure up to 80 m

<https://shop.wild-heerbrugg.com/>



# Survey monuments




# Survey monuments



# Data extend and sorting

Overview of the measurement epochs in the time for the floor and the walls






# Displacement of the base slab points 1D (I)

The difference of height epoch DEC19 - DEC18

Statistic (mm): Min = 0.16, Max = 0.73, Mean = 0.38




- Heave detected for majority of epochs (exceptions in period 2003-2009)
- Maximum vertical deformation **4.9 mm**
- Average accuracy of points  $\pm 0.09$  mm (period 2006-2019)
- Average accuracy of points  $\pm 0.18$  mm (period 2003-2005)
- Average accuracy of points  $\pm 0.35$  mm (July 2003)
- Largest deformation in central part
- Relatively stable areas in the corners

# Displacement of the base slab points 1D (II)

The difference of height epoch DEC19 - DEC18


Statistic (mm): Min = 0.16, Max = 0.73, Mean = 0.38



- The base slab deformation has a significant influence on the experiment position
- The centre of the floor is the most interesting due to proximity of ATLAS feet
- The cluttered area of the measurement in certain periods
- Influence of asymmetric layout of trenches
- ATLAS feet shifted towards US wall

# Displacement of the base slab points 1D (III)

Vertical displacement of chosen points on the base slab in the period Aug03 - Feb20





# Displacement of the base slab points 1D (IV)



- Three phases of ATLAS monitoring
  - a) **Concrete setting**
  - b) **Detector construction**
  - c) **Operation period**
  
- Three different phenomena have impact on the cavern floor deformation
  - a) Concrete setting
  - b) Upward earth-pressure
  - c) Experiment load


# Displacement of the base slab points 1D (V)



# Displacement 2D of the base slab points (I)

Horizontal displacement of the points on the floor diff = DEC18 - DEC17

The scale of ellipses and arrows - 1:5000




- Maximum movement not exceeding 1.4 mm excluding Aug 2003
- Average movement 0.3 mm in the period from 2004 to 2019 near ATLAS feet
- A-side and C-side tend to move towards the US wall and the centre
- Radial alignment more important than along the beam



# Displacement 2D of the base slab points (II)

Horizontal displacement of the points on the floor diff = DEC18 - DEC17

The scale of ellipses and arrows - 1:5000




- The most important part - centre is stable
- Movement of points on A and C sides in the direction of the US lateral wall
- Scaling factor observed 2005 – 2008
- Poor measurement conditions during ATLAS construction
- Progress in the measurement techniques

# Displacement of the USA wall

Y-direction displacement on the USA wall diff = DEC18 - DEC17

Statistic (mm): Min = 0.08, Max = 0.57, Mean = 0.31




- Deformation is larger on USA wall
- Access to points only from platforms
- Fewer points on the walls than on the floor
- Maximum deformation on USA wall 14.5 mm
- Direction of vector towards the cavern centre
- Displacement higher in the centre than in the corners

# Displacement of the US wall

Y-direction displacement on the US wall diff = DEC18 - DEC17

Statistic (mm): Min = -0.48, Max = 0.07, Mean = -0.11



- Deformation is smaller on US wall
- Access to points only from platforms
- Fewer points on the walls than on the floor
- Maximum deformation on USA wall 10.1 mm
- Direction of vector towards the cavern centre
- Displacement higher in the centre than in the corners



# Conclusion (I)

- **Maximum floor deformation is 4.9 mm towards the centre of the cavern**
- **Maximum deformation US wall 14 mm**
- **Maximum deformation USA wall 10 mm**
- **Wall deformation 3 times higher than the base slab**
- **Maximum deformation in the center**
- **Geometrical asymmetry of deformation**
- **Constant direction of the movement \***
- **Accelerator and experiment move up**

# Conclusion (II)

- **Floor stability fundamental for ATLAS**
- **3 main phases of the base slab movement**
- **Vertical deformation lower than the forecast**
- **The predicted vertical heave of 1 mm/year has never been reached**
- **The highest average heave since beam start has been 0.33 mm/year**
- **Horizontal stability of the floor in operation phase**
- **Maximum horizontal deformation in the floor centre 0.3 mm**
- **Asymmetry of the heave could provoke the radial displacement of the detector**

# Bibliography (I)

- Zhuab, W.S., Lic, X.J., Zhanga, Q.B., Zhenga, W.H., Xina, X.L., Suna, A.H., Lia, S.C., A study on sidewall displacement prediction and stability evaluations for large underground power station caverns., *International Journal of Rock Mechanics and Mining Sciences*, Volume 47, Issue 7, Pages 1055-1062, 2010
- Tatiya, R., *Civil Excavations and Tunnelling: A practical guide*, Second edition, 2017
- Dai, F., Li, B., Xu, X., Fan, Y., Zhang, C., Deformation forecasting and stability analysis of large-scale underground powerhouse caverns from microseismic monitoring, *International Journal of Rock Mechanics and Mining Sciences*, Volume 86, 2016
- Pitthan, R., *Re-alignment: It is the Tunnel Floor which moves, isn't it ?*, 4<sup>th</sup> International Workshop on Accelerator Alignment, Tsukuba, Japan, 1995
- Goddard, B., Hillerer, N., Placidi, M., Poole, J., Quesnel, J.-P., Rammer, H., de Rijk, G., Roy, G., Spinks, A., Verdier, A., *Final Report on the Consequences of the LHC Civil Engineering for the SPS and LEP*, CERN-SL-97-066-DI, CERN, Geneva, Switzerland, 1997
- Evans L., Bryant, P., *The CERN large hadron collider: accelerator and experiments. LHC Machine*, Geneva, Switzerland, 2008
- Rammer, H., *Two new caverns for LHC experiments: ATLAS and CMS*, 1st ST Workshop, Chamonix, France, 1998
- Lasseur, C., *Alignment of the LHC machine and experiments – Part 2) The experiments. Engineering/Technical Note CERN, Lemic, EDMS: 330354*, CERN, Geneva, Switzerland, 2001
- Apollinari, G., Béjar Alonso, I., Brüning, O., Lamont, M., Rossi, L., *High-Luminosity Large Hadron Collider (HL-LHC) : Preliminary Design Report*, Geneva, Switzerland, 2015
- Wilson, I, *The compact linear collider CLIC*, *Physics Reports Volumes 403–404*, Pages 365-378 CERN, Geneva, Switzerland, 2004
- ATLAS Cavern Network at CERN: Kinematic and Adaptive Adjustment Techniques. Ingenieurvermessung 07*, Graz, Austria, 2007
- Abada, A., Abbrescia, M., AbdusSalam, S.S. et al. *FCC-ee: The Lepton Collider. Eur. Phys. J. Spec. Top. 228*, 261–623, Geneva, Switzerland, 2019
- ATLAS collaboration, ATLAS Technical Design Report (TDR)*, CERN, Geneva, Switzerland, 1999
- Aad, G., Abat, E., Abdallah, J., et al., *The CERN large hadron collider: accelerator and experiments. The ATLAS Experiment at the CERN Large Hadron Collider*, Geneva, Switzerland, 2008
- Guillon, C., *Etude des Ouvrages Souterrains ATLAS*, 1st CERN ST Workshop, Chamonix, France, 1998



# Bibliography (II)

Rammer, H., LEP Tunnel Movements at Point 1 caused by LHC Civil Engineering, 4<sup>th</sup> ST Workshop, Chamonix, France, 2001

Butin, F., Bachy, G., Nicquevert, B., Price, M., Support Structures System Analysis: Results of Second Iteration, EDMS: ATC-T-ER-0002, CERN, Geneva, Switzerland

Geotechnique Appliquee Deriaz S.A., References profondes LHC - Lever geologique des forages et evaluation de tassements, CERN – Division ST/CE, Geneva, Switzerland, 2004

Jones, M., Geodetic Definition (Datum Parameters) of the CERN Coordinate System, CERN Internal Note EDMS: 107981, Geneva, Switzerland, 1996

M. Barbier, Q. Dorléat, M. Jones, LGC: A New Revised Version, IWAA, Grenoble, France, 2016

Lasseur, C., Mayoud, M., Quesnel, J.-P., Géométrie du LHC : Points caractéristiques, Formules des Transformation, LHC Project Note 95 (EDMS : 108124), CERN, Geneva, Switzerland, 1996

Ibarrola, N., Jones, M., Analysis and Evaluation of the CERN Reference Systems, International Workshop on Accelerator Alignment, Grenoble, France, 2016

Jones, M., Geodetic and Astronomical Reference & Coordinate Systems. CERN Internal Note, EDMS: 107906, 1999

Lippitsch A., A Deformation Analysis Method for the Metrological ATLAS Cavern Network at CERN. Dissertation TU Graz, Austria, 2007

Raymond, M., Gayde, J.-C., Mergelkuhl, D., Summary of requirements for ATLAS Detector Positioning System, EDMS: ATL-HT-ES-0001, CERN, Geneva, Switzerland, 2012

Leica Geosystems AG, Wild NA2/NAK2 User Manual Version 2.0, Heerbrugg, Switzerland, 2004

Leica AG, Wild N3 User Manual, Heerbrugg, Switzerland, 1995

Leica AG, WILD T2002, TC2002 and T3000 User Manual, Wild, Heerbrugg, Switzerland, 1996

Leica Geosystems. Leica AT401 User Manual V 2.0. , 2013.

Leica Geosystems. Leica Absolute Tracker AT401 White Paper, 2010

H. Mainaud Durand, A. Herty, A. Marin, M. Rousseau, M. Sosin, Remote Qualification of HLS and WPS Systems in the LHC Tunnel CERN, Geneva, Switzerland, 2015

Zimmermann, S., High Rate and Ageing Studies for the Drift Tubes of the ATLAS Muon Spectrometer, CERN, Geneva, Switzerland, 2004.

Cressie, N., The origins of kriging. *Mathematical Geology* volume 22, 239-252, 1990

Linnik, Yu. V., *Method of Least Squares and Principles of the Theory of Observations*, London, Great Britain, 1961



Witold NIEWIEM BE/GM/ESA

Geodetic Deformation Measurement and Analysis of the  
ATLAS Experimental Cavern at CERN

[home.cern](http://home.cern)