


# **RF Solid State Amplifiers for MINERVA General Architecture and Main Challenges**

# MYRRHA – Applications



\*SNF = Spent Nuclear Fuel

- Demonstrate ADS concept at pre-industrial scale
- Transmutation demonstration
- Multipurpose & flexible irradiation testing facility




\*SNF = Spent Nuclear Fuel

- An attractive tool for education and training of young scientists and engineers
- A medical radioisotope production facility

# MYRRHA – Phases

- **Phase 1** (approved, financed by Belgium Govt.)
  - 100 MeV LINAC + PTF & FPF implementation
  - Design and pre-licensing of the reactor
  - R&D for 600 MeV linac




Phase 2: extension of the LINAC to 600 MeV

Phase 3: reactor implementation (2034 = start)

# Phase 1 – MINERVA

## Objectives

- Demonstrate reliability as required for ADS
- Reliability goal evaluation
- Fault tolerant schemes implementation



----- Existing inject test stand

## Applications

- Fundamental research
- Develop new medical isotopes
- Include design considerations for upgrade use with fusion material research

# MINERVA LINAC - Requirements

- **High reliability** requirements (\*)
  - Mean Time Between Failures (MTBF) > 250hrs
    - Allowed beam trips > 3 sec – Max. 10 per 90 day operation
    - Allowed beam trips > 100 ms – Max. 100 per day
    - Allowed beam trips < 100 ms – “unlimited”
- **High availability** requirements
  - Low Mean Time To Recover (MTTR)
  - Failure detectability mechanisms

## Achieving reliability


- Conservative design: Use mature technologies and components, not pushing their technological limits
  - Solid State (SS) RF amplifiers
  - Modular DC power supplies
  - Digital Low Level RF (LLRF) control
- Serial redundancy in the main LINAC

## Achieving availability

- Modular design for key elements
  - Solid State (SS) RF amplifiers
  - Modular DC power supplies
  - Digital Low Level RF (LLRF) control
- Hot swappable elements
- Low average corrective maintenance time
- Predictive maintenance


(\*) MYRRHA requirements

# HP RF System – 17MeV Injector architecture



## Additional system elements

- RF distribution system -> Coaxial rigid line
- Monitoring elements -> RF monitoring Couplers



**RFQ:** Radio-Frequency **Q**uadrupole

**CH:** **C**ross-bar **H** mode cavity


**QWR:** Quarter **W**ave **R**esonator

**CHR:** **CH** cavity used for **R**ebunching

# HP RF System – 17MeV Injector architecture

## RF Gallery to injector

- Up to 22 SSA racks distributed along the RF gallery
  - Freedom on rack distribution
  - Coaxial rigid line used as TXL




# HP RF System – 17MeV Injector Power Needs

	Driving cavity	Quantity	Single P <sub>out</sub> range Min-Max[kW] <sup>(*)</sup>	Estimated # of cabinets
176,1 MHz	RFQ	1	168	3
	QWR1 & QWR2 <sup>(**)</sup>	2	6	4
	CH1 & CH2 <sup>(**)</sup>	2	24	
	CH3&CH4 <sup>(**)</sup>	2	36	
	CH5&CH7 <sup>(**)</sup>	2	48	
	CH6 <sup>(**)</sup>	1	60	
	CH8-CH15	8	59-62	15
	CHR1 & CHR2	2	13-15	
	Amplifiers to be newly procured	11	---	18

<sup>(\*)</sup> Peak power at the output combiner connector on the rack.  
<sup>(\*\*)</sup> Already procured  
 Amplifiers should support operation on both CW and CW\_P




# HP RF System – 100MeV LINAC Architecture



## Additional system elements



- High power RF circulators + Loads
- RF distribution system -> Coax rigid line
- Monitoring elements -> RF monitoring Couplers



# HP RF System – 100MeV LINAC Architecture

## RF Gallery to the tunnel

- Up to 32 racks distributed along the RF gallery
  - About one rack each two cavities
- 62 circulators distributed along the gallery
  - One circulator per cavity
  - Coaxial rigid line used as TXL



# HP RF System – 100MeV LINAC Power Needs

	Driving cavity	Quantity	Single P <sub>out</sub> range Min-Max[kW] <sup>(*)</sup>	Estimated cabinet availability #
352,2 MHz	SSR1-2 & SS1-14	16	4-9	25
	SS15-22	8	10-12	
	SS23-46	24	13-14	
	SS47-60 <sup>(**)</sup>	14	15-20	7
	Total amplifiers to be procured without options	48	---	25
	Total amplifiers to be procured with options	62	---	32
	(*) Peak power at the output combiner connector on the rack. (**) Option amplifiers Amplifiers should support operation on both CW and CW_P			

- Two operation modes, two nominal powers @352 MHz-> Efficiency must be maximized for both operation modes

# HP RF System – Specifications & Requirements

## Design

- Reliable design ensuring high MTBF figures
- Stable design for any Gamma,  $P_{OUT}$  &  $V_D$
- High efficiency over large  $P_{OUT}$  range
- Custom design
- Modular & redundant

## Installation & Commissioning

- Final on-site installation will also be within the scope of the delivery

## Serialization


- Quality assurance plan
- Quality control plan
- High volume production capability

## O&M

- Full documentation package to ensure maintenance, repair and amplifier upgrades
- Dedicated hands-on trainings on operation and maintenance
- Spare parts long term availability

# HP RF System – NCRF/SRF allowed P<sub>dB</sub>

## Gain & Phase variation over P<sub>fwd</sub>




## Maximum P<sub>dB</sub> allowed

- Impact on Gain and phase linearity AM/AM & AM/PM
  - Investigating impact on LLRF regulation loop
  - Exploring use of Digital Pre-Distorsion (DPD)
- Impact on RF power provision

# HP RF System – SRF series redundancy

## FFT estimated RF power levels




## SRF Series redundancy

- Adjacent cavities compensating for the failure of one cavity.
- SSAs will operate at 2 different power levels:
  - Standard Fault Tolerance (SFT)
  - Full Fault Tolerance (FFT)
- SFT 3dB Back Off (BO) from FFT!
  - Degraded Drain efficiency (Deff) of about 15%

# HP RF System – SRF BO Efficiency Optimization

## Drain voltage impact on efficiency and gain




## Vds Efficiency optimization is the current path

- Two different setting modes FFT and SFT
  - Investigating feasibility and integration with LLRF
  - Assessing operational concept
- But still few question marks
  - Can be done without stopping RF?
  - What is the impact on the gain variation?
  - How to deal with internal SSA failures?
  - Stability across all voltage range

# HP RF System – SRF BO MTBF

## Efficiency/Junction Temp/ $P_{diss}$



## MTBF at SFT

- Without efficiency optimization MTBF will only be better
  - Junction temperature does not increase
  - Breakdown voltage much lower (Lower RF power)
  - Rest of components working at conservative ratings e.g. combiners, PSUs
- With efficiency optimization MTBF will only be better
  - Junction temperature will be drastically reduced
  - Breakdown voltage much lower (Lower RF power + Lower DC voltage)
  - Rest of components working at conservative ratings e.g. combiners, PSUs like without efficiency optimization

Thermal resistance  $R_{THj - c} = \frac{T_{junction} - T_{case}}{P_{diss}}$  [K/W]



# HP RF System – Other Challenges

## NCRF SSA without circulators

- Proof of concept had been carried for the RFQ at the Injector Test Stand (ITS)
  - Due to the small beam loading on NCRF cavities in combination with CW operation not high VSWR expected
  - Cavity filling and “discharge” time plays a crucial role and needs to be further investigated
  - For CW\_P operational mode cavity filling and “discharge” times needs to be carefully investigated
  - Output impedance load pull

# Conclusions

- MINERVA is the 1<sup>st</sup> phase of MYRRHA implementing a 100 MeV SRF linac
- MINERVA requires 20 SSAs at 176.1 MHz and 60 SSAs at 352.2 MHz CW and CW\_P capable.
- Experience from available SSAs@ITS is the basis for the technical specifications
- Technical specifications for the SSAs are being prepared.
- High availability requirement, SFT & FFT, is THE main challenge for the SSA specification
- Drain voltage control impact is under investigation.

## Copyright © SCK CEN

### PLEASE NOTE!

This presentation contains data, information and formats for dedicated use only and may not be communicated, copied, reproduced, distributed or cited without the explicit written permission of SCK CEN.

If this explicit written permission has been obtained, please reference the author, followed by 'by courtesy of SCK CEN'.

Any infringement to this rule is illegal and entitles to claim damages from the infringer, without prejudice to any other right in case of granting a patent or registration in the field of intellectual property.

### **SCK CEN**

Belgian Nuclear Research Centre

Stichting van Openbaar Nut  
Fondation d'Utilité Publique  
Foundation of Public Utility

Registered Office: Avenue Herrmann-Debrouxlaan 40 – BE-1160 BRUSSELS

Operational Office: Boeretang 200 – BE-2400 MOL