

Production schedule and cost estimation of the BINP full-scale prototype wiggler

Alexey Bragin,
Budker Institute of Nuclear Physics,
Novosibirsk, Russia

December 2010

Tested short prototype. Review.

Short prototype of NbTi wiggler was tested in August 2010.

Its parameters are:

Period – 50 mm


Gap – 20 mm

Peak magnetic field – 2.5 T

Ratio I_{op}/I_{cr} – 95%

Number of turns – 341

SC cable with high NbTi/Cu ratio – 1.5 (0.72 - typically)





Main parameters of the NbTi ANKA wiggler

- ◆ Period – 56 mm
- ◆ Total cryostat length – 2.5 m
- ◆ Magnet length – 2 m
- ◆ Peak magnetic field – 3.0 T
- ◆ Pole gap – 18 mm
- ◆ Beam aperture – 13 mm
- ◆ Ratio $I_{op}/I_{cr} \sim 83\%$
- ◆ Num. of vertical coils in two halves – 142

- ◆ Easy disassembling cryostat in two weeks
- ◆ Proposed wiggler cooling saves the gap space

Design of the wiggler coils




Grove sizes - 18 mm x 18 mm

Number of turns - 333

Number of layers - 18

Current - 600 A

Magnetic field on coils - 5.3 T



Scope of work

1. Magnet system (iron, coils) manufacturing
2. Cryostat manufacturing
3. Wiggler training in LHe cryostat at 4.3. K
4. Tests of the wiggler in the cryostat (60 W on the beam tube?)
5. Magnetic field measurements
6. Assembling and testing the wiggler in ANKA

Schedule

Items	2011												2012											
	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D
1. Contract signed	█	█																						
2. Manufacturing drawings	█	█	█	█	█																			
3. Materials and SC cable		█	█	█	█	█	█	█	█	█														
4. BINP workshop						█	█	█	█	█	cryostat													
5. Winding tools	█	█	█	█	█	█	█	█	█															
6. Coils winding and impregnating										█	█	█	█											
7. Assembling and training															█	█	█							
8. Cryostat assembling and testing																	█	█	█					
9. Wiggler at ANKA																				█				
10. Wiggler installed																					█			

Equipment

- ◆ Current leads – HTSC, 1.1 kA - ?
- ◆ Power supplies (1.1 kA, ~20 A correction) - ?
- ◆ Quench protection electronics - ?
- ◆ Magic fingers correction - ?
- ◆ Temperature sensors - ?
- ◆ Vacuum pumps, gauges - ?

Cost estimation

1. BINP workshop estimation according to calculated hours of work \sim \$10/h. Cryostat, magnet \sim 20 000 hours. So, BINP workshop - **\$200 000**
2. Beam tube - **\$50 000**
3. SC cable, (3 euros/m, N. Mezentsev*) - **\$105 000**
4. The total cost of the SC magnet can be estimated according to (**) - **\$950 000** without cryogenics
5. The final price should be approved by BINP administrators after discussing the scope of work and supplying equipment.

*) Previously, I thought that the cable costs 2 euros/m.

***) M. Green, B. Strauss " ", IEEE Transactions on Applied Superconductivity, 2008

Conclusions

- ◆ BINP is ready to start working on the new prototype of the CLIC wiggler which will be installed in ANKA.
- ◆ Technical specification should be discussed.
- ◆ The preliminary price is stated with an accuracy 20 %.