

23rd International Workshop on Radiation Imaging Detectors 26-30 June 2022

Riva del Garda, Italy

iWoRiD 2022

Contribution ID: 214

Type: Oral

INVITED: Timepix detectors in Space: From radiation monitoring in low earth orbit to astroparticle physics

Tuesday 28 June 2022 08:30 (30 minutes)

Hybrid pixel detectors (HPD) of Timepix [1,2] technology have become increasingly interesting for space applications. While up to date, common space radiation monitors rely on silicon diodes, achieving particle (mainly electron and proton) separation by pulse-height analysis, detector stacking, shielding or electron removal by a magnetic field, the key advantage of HPDs is that, in addition to the energy deposition measurement, particle signatures in the sensor are seen as tracks with a rich set of features. These track characteristics can be exploited for identification of particle type, energy, and its trajectory. Determining these pieces of information on a single layer bypasses the need for sensor stacking or complex shielding geometries, so that HPD based space radiation devices provide science-class data with a large field of view at an order of magnitude lower weight and approximately half of the power consumption compared with commonly used space radiation monitors.

The first Timepix (256 x 256 pixels, 55 µm pitch) used in open space is SATRAM (Space Application of Timepix Radiation Monitor), attached to the Proba-V satellite launched to low earth orbit (LEO, 820 km, sun-synchronous) in 2013. Up to now, 9 years after its launch, it provides data for mapping out the fluxes of electrons and protons trapped in the Van-Allen radiation belts [3]. Noiseless detection of individual particles allows to detect even rare signatures of highly ionizing events.

In the present contribution, I will discuss different data analysis methodology, relying on track feature analysis, novel machine learning approaches (e.g. [5]) and using statistical interpolation.

Based on the success of SATRAM, advanced and miniaturized space radiation monitors based on Timepix3 [2] and Timepix2 [4] technology have been developed for the European Space Agency (ESA). These will be flown on the GOMX-5 mission (launch in 2023) and used within the European Space Radiation Array. Large area Timepix3 detectors (512 x 512 pixels, 55 µm pitch) were developed for the demonstrator of the penetrating particle analyzer [5] (mini.PAN), a compact magnetic spectrometer (MS) to precisely measure the cosmic ray flux, composition, spectral characteristics and directions. Mini.PAN employs position-sensitive (pixel and strip) detectors and (fast) scintillators to infer the particle type and velocity of GeV particles (and antiparticles) passing through the instrument's magnetic field by measuring their bending angles, charge deposition and time-of-flight.

I will describe the mini.PAN development status, challenges imposed by the space environment, and outline how a MS purely relying on Timepix4 would reduce the PAN mass budget.

References:

- [1] X. Llopart et al., NIM A 581 (2007), pp. 485-494.
- [2] T. Poikela et al., JINST 9 (2014) C05013.
- [3] St. Gohl et al., Advances in Space Research 63 (2019), Issue 1, pp. 1646-1660.
- [4] W. Wong et al., Rad. Meas. 131 (2021), 106230.
- [5] M. Ruffenach et al., in IEEE TNS 68 (2021), Issue 8, 1746-1753.
- [6] X. Wu et al., Advances in Space Research, 63 (2019), Issue 8, pp 2672-2682.

Presenters: BERGMANN, Benedikt; BERGMANN, Benedikt Ludwig (Czech Technical University in Prague (CZ))

Session Classification: Sensors