


LEP₂ and LHC Interlock System

- The Past
 - The “LEP₂” System
 - Structure, Layout, Beam Dump, Hw, Sw, Diagnostic etc..
- The Present
 - The Evolution
 - Structure, Layout, Hw Modules, PLC, Sw, Tests etc..
- The Future
 - Final “LHC” version
 - Structure, Layout, PLC, Sw, Tests etc..
- Conclusions

The “LEP” Interlock System


- LEP RF was 288 SC Cavities in 4 Points and a total of ~8000 interlocks RF and HV
- Full hardwired logic (TTL) implementation no software interlocks
- Interlock Interface&Module on the Cavity, Klystron and High Voltage Equipment Controller
- Helium Pressure and Gauges directly connected to the Beam Dump line (~570 relay connections)
- Communication with the control via G64 and GPIB Bus

The “LEP” ½ unit Interlock Structure



Luca Arnaudon LEP2 and LHC Interlock System

The “LEP” Interlock Hardware



The “LEP” Interlock Conclusion

GOOD


- TTL Logic was a reliable and simple solution vs. relay contact solution
 - Modular system with local display (LEP was accessible)
 - Full remote read-out
 - Always a very reliable equipment protection during operation
-

LESS GOOD

- Unreliable and slow communication (GPIB) with unit controller
- Interlocks faults names coded in the EC software and sent to the unit controller in ASCII format, human readable strings, leading to high communication load
- Poor Beam Dump diagnostic and time stamping (new system added in 99)
- Full hardware solution ... not enough flexibility
- Interlock information spread in different Equipment Controllers
- No information on Hw forced interlocks (specialists discipline needed !!)

The Evolution ...


- The Interlock Module Hardware
 - Keep a modular and TTL hardware approach (reaction time < 3µSec)
 - Redesign the diagnostic Hw with µC and FPGA for a gain in flexibility
 - Interlocks can now be software forced
 - I2C communication bus between modules and Interlock Controller (! ISP)
- The Interlock Module Software
 - First Fault, All Faults and Forced Faults are stored in the µC and sent to supervision
 - Remote µC program download via RS232↔Ethernet interface




Luca Arnaudon LEP2 and LHC Interlock System

... The Evolution

- The Interlock Controller Hardware
 - Modular design (COTS mezzanines on custom motherboard)
 - One µC mezzanine (C51 based)
 - One communication mezzanine (HMS Anybus Modbus/TCP)
 - Hardware watchdog
- The Interlock Controller Software
 - First level of data formatting, Interlock code generation and system alarms
 - Ethernet communication with the supervision (PLC IoScan)
 - First Fault, All Faults and Forced Faults are stored in the µC and sent to supervision




H112 Test Interlocks layout



Interlock code example	
System data in 8 bit blocks	
First Module	First Fault
Ex. 11111011	11111011
Module 4 data in 8 bit blocks	
All	Latched
Ex. 11111110	11111010
Forced	Status
Ex. 00000000	11111111

Luca Arnaudon LEP2 and LHC Interlock System

Interlock Screen




Luca Arnaudon LEP2 and LHC Interlock System

The proposed “LHC” interlock system

- The LHC RF will be 16 cavities/klystron Line and 4 HV bunkers with a total of ~1000 interlocks
- Slow (~20mSec) interlocks will be treated by the PLC (Ex. Temperature, water flows)
- Only Fast (<3μSec) interlocks will be connected directly to the interlock system
- This will result in ~600 fast interlocks and ~400 slow interlocks so ~ 5 interlock Modules per Line
- The PLC has a “sum of faults” output to the interlock system
- A common time stamping system (GPS/IrigB) will be triggered by one dedicated interlock output
- The PLC will read back the Interlock system status and provide a comprehensive code for the supervision (first fault, all faults, forced faults)
- Interface to the BIC system from Helium (later from HV and RF trips)

“LHC” interlock system diagram

This will be tested
next year in
the SM18
Cavity test stand



Will be tested
next year in
SM18
Cavity test stand