

Future Facilities and Instrumentation


Luciano Musa (CERN)

Quark Matter 2023, Houston, 9 September 2023



The evolution of AA Facilities






Future e-A colliders



e-p/A colliders for precision studies of cold-QCD

Facility	Years	E _{cm} (GeV)	Luminosity (10 ³⁴ cm ⁻² s ⁻¹)	lons	Polarization
EIC in US	> 2033	20–100 → 140	0.2 – 3	p → U	e, p, d, ³ He, Li
EicC in China	> 2032	16 – 34	0.1 -> 10	p → Pb	e, p, light nuclei
LHeC	> 2035	200 - 1300	1	p → Pb	е
FCC-eh	> 2070	3500	1.5	p → Pb	е



EIC in the US is at an advanced stage of approval

EicC in China: CDR in 2023 (aim at approval @ 15th 5-year plan – 2026 ->)


- Mass, spin and other emergent properties of nucleons from the dynamics of their constituents (quarks and gluons)
- Emergent properties of high-density gluon matter
- Nuclear structure


explore QCD landscape over a large range of resolution (Q²) and quark/gluon density (x⁻¹)


Advancing boundaries with innovative detectors




higher precision, faster and more intelligent














ALICE 3



FCC-hh

High-E AA Colliders: RHIC, LHC, SppC/FCC-hh



Facility	RHIC	LHC/HL-LHC	SppC / FCC-hh
Timeline	→ 2025	→ 2041 (Runs 3 to 6)	> 2035 / > 2070
Collision system	pp, d-Au, Au-Au	pp, p-Pb and A-A (Pb-Pb, ¹⁶ O, ¹²⁹ Xe, ⁸⁴ Kr, ⁴⁰ Ar,)	FCC: pp, p-A and A-A (Pb-Pb, 129Xe, 84Kr, 40Ar,)
$\sqrt{s_{NN}}$ (TeV)	0.2	5.5	~39
Int. rate (kHZ)	~15 (Au-Au)	≥50 (x 3-4 in Run5) for Pb-Pb	~2500 (FCC)
Experiments	sPHENIX, STAR	ALICE, ATLAS, CMS, LHCb phase II of ATLAS and CMS phase II-b of ALICE and LHCb	up to four experiments

An Upgrade Proposal from the PHENIX Collaboration (arXiv:1501.06197)


Physics opportunities for high-density QCD at the LHC with HI and p beams in Runs 3-4 (arXiv: 1812.06772)

ALICE 3 – A next generation HI experiment at the LHC (arXiv:2211.0249)

FCC/SppC open new opportunities (CYRM-2022-002, CEPC-SPPC CDR)

RHIC - sPHENIX






- 1.4 T superconducting solenoid
- Hermetic coverage |η|<1.1
- Excellent vertexing (CMOS pixels)
- High-precision tracking
- Large-acceptance ECal + HCal
- High data rates: 15 KHz
- Trigger capability also with streaming readout

sPHENIX: new state-of-the-art jet detector (arXiv1207.6378)


⇒ focus on jets, quarkonia and other rare processes

- installation completed and commissioning in 2023
- first physics run in 2024









LHC long-term programme



LHC is starting the (HI) high-luminosity era (x6 luminosity)

⇒ start of first (long) Pb-Pb run imminent!

Upgrades of the accelerator and the experiments planned for installation in 2026-2028


- HL-LHC (pp): x O(10) wrt to LHC design luminosity
- major upgrades of ATLAS and CMS
- small upgrades of ALICE and LHCb

Planned for 2033-2034: completely new ALICE (ALICE 3) and new LHCb (LHCb-II)



LHC programme






High-rate challenges


HL- LHC (pp): L_{int} up to $7.5 \times 10^{34} \text{cm}^{-2} \text{s}^{-1}$



Extreme interaction and particle rates: PU ≈ 200 (8x10⁹ event/s), particle rate up to 3GHz/cm²

- ⇒ Higher granularity and resolution (especially in the silicon trackers)
- ⇒ Track or hit high-precision timestamping ("4D tracking")
- \Rightarrow extreme rad-hard (@ 30 mm, after 3000 fb⁻¹): NIEL \approx 2 × 10¹⁶ n / cm² TID \approx 12 MGy
- ⇒ Extreme data throughput: unprecedented challenges for trigger and online data processing





HL-LHC ⇒ **ATLAS** and **CMS** upgrades

Run 1 Run 2 Run 3 Run 4 Run 5 Run 6


Larger tracker acceptance: from $|\eta| < 2.5$ to $|\eta| < 4$




- $2.5 < |\eta| < 5 \text{ for ATLAS}$
- $|\eta| < 4$ for CMS (TOF PID)



- HL-ZDC Muon ID up to $|\eta| < 2.8$
- Trigger and DAQ improvements





MIP Timing Detector (MTD)

- barrel: LYSO + SiPMs
- endcaps: LGADs
- $\sigma_{TOF} \approx 30 ps$

CMS BW for MB events: <u>2018</u>: 6GB/s (8.8 kHz) Run3: 17 GB/s (25 kHz) Run4: 51GB/s (> 50kHz)


LHCb Phase II Upgrade





Upgrade II

- $L_{\text{peak}} = 1.5 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$
- $L_{int} \approx 300 \text{fb-1} \text{ during Run 5 \& 6}$




LHCb-PUB-2022-012

General purpose flavour physics facility ... but also a general purpose heavy-ion experiment for pA and AA in forward rapidity

- no centrality limitations for AA
- excellent vertexing and PID

Targeting same performance as in Run 3, but with pile-up ~40!




Key ingredients: granularity, fast timing (few tens of ps), radiation hardness

ALICE Phase II Upgrade


Major ALICE upgrade in LS2 (**ALICE 2**) for Run 3 & Run 4 continuous readout (all events @50kHz) + x3 improved vertexing




Intermidiate (narrow scope) upgrades in LS3 (ALICE 2.1)



Letter of Intent for ALICE 3 (Lol Mar '22)







ALICE 3: an all-silicon detector

Run 1 Run 2 Run 3 Run 4 Run 5 Run 6





high-efficiency for reconstruction of (multi-)HF hadrons and of low-mass dielectrons


vertexing inside the beampipe with unprecedentedly low material budget

large acceptance with excellent coverage down to low p_T excellent particle ID (muons, electrons, photons, hadrons)

 \Rightarrow **Vertexing precision**: 10µm at p_T = 200 MeV

 \Rightarrow Acceptance: $|\eta| < 4$ (with particle ID)

⇒ A-A (pp) rates: up to 1 MHz (25 MHz)




⇒ novel technologies: MAPS, CMOS LGAD, combined TOF+RICH

High baryon density facilities

CERN

Systematic exploration of high μ_B region



T. Galatyuk, NPA 982 (2019), update Aug 2023 (GitHub link)

Experimental approach

 probe with highest precision different regions of the QCD matter phase diagram

Observables

- Flavour production (multi-strange, charm)
- Dileptons (emissivity of matter)
- e-by-e correlations and fluctuations
- collective effects

 $2.5 < \sqrt{s_{NN}} < 8$ Gev – key region for 1st order phase transition and Critical Point search


Facilities: BNL-RHIC, CERN-SPS, FAIR-SIS100, JINR-NICA, J-PARC, HIAF

FAIR Facility

CERN

FAIR (Facility for Antiproton and Ion Research in Europe)

- Ion beams up 11 AGeV
 ⇒ cme for Au-Au up to 4.9 AGeV
- Ion intensity up to 10⁹/s



Four Pillars

- CBM Compressed Baryonic Matter
- NUSTAR Nuclear Struc, Astroph., Reac.
- PANDA Antiproton Annihilation
- APPA Atomic, Plasma Physics and Appl.


Modularized Start Version (MSV)

FAIR 2028: will feature a large part of the programe (First Sicence +), including **CBM**



CBM Experiment










Hadrons, dielectrons and dimuons, charm Interaction rates up to 10MHz ($\sqrt{s_{NN}}$: 2.7 – 5 GeV) dead-time free continuous readout, online event selection



MVD: MIMOSIS




OF@STAR



2028: commissioning with SIS100 beam





NA60+ Experiment




Beam energy scan ($\sqrt{s_{NN}}$: 6.3 – 17.3 GeV) for precision studies of: hard processes, electromagnetic

Roadmap

- Technical proposal: 2024-2025
- Constr. & Installation: 2026-2028
- Data taking: 2029 2037


Eol in 2019 https://cds.cern.ch/record/2673280 Lol in 2022 CERN-SPSC-2022-036 ; SPSC-I-259



5-plane vertex detector based on MAPS (ALICE ITS3)

- Spatial resolution: 5μm
- X/X₀: 0.1% /plane

follows design of NA60 but with better-performing detectors




Muon Spectrometer (6 stations) on rails to adjust position depending on energy

Muon tracking stations: MPGD (GEM, MicroMeagas) or MWPC (baseline) with total active area $100m^2$, spatial resolution (radial direction) $\sim 200 \mu m$, max plarticle flux $\sim kHz/cm^2$

J-PARC-HI Project





J-PARC-HI

fixed target A+A experiment with high intensity HI beam

Phase 0: ~10¹⁰ Hz 30GeV p beam vetor meson via dielectron decay current status: commissioning

Phase1: 12 AGeV Au beam, ~108 Hz, dielectrons

Phase2


- 12 AGeV Au beam, ~10¹¹Hz(!)
- multiple probes

Pending funding approval by KEK and JAEA, Phase 1 could start in 2031/2032

The Electron Ion Collider (EIC)



Electron Ion Collider Scope



- High Luminosity: $10^{33} 10^{34}$ cm⁻² sec⁻¹, 10 100 fb⁻¹/year
- Large Center of Mass Energy Range: $E_{cm} = 29 140 \text{ GeV}$
- Highly Polarized Beams: 70%
- Large Ion Species Range: protons Uranium

Similar but more challenging than the FCC-ee (2x e⁻ current)

p: 41 GeV, 100 to 275 GeV

p/A beam
e beam
e: 5 GeV to 18 GeV

Accelerator system

Construction phase (*): 2026 – 2030 Science Phase: 2035

Detector #1 (Project Detector)

Construction phase: 2024 – 2031

Detector #2

Construction phase: 2028 – 2034


^(*) Construction: procurement, fabrication, installation, test

EPIC - EIC First Detector

CERN

- 2020 2021: EICUG Yellow Report
- Mar 2021: call for proposals

- Mar 2022: ECCE chosen <u>as reference</u> design for detector 1
- July 2022: ePIC Collaboration




- Large rapidity $(-4 < \eta < 4)$ coverage
- High precision low mass tracking
 - o new 1.7T magnet, MAPS + MPGD
- Electromagnetic and Hadronic Calorimetry
 - o e-side: PbWO₄ EMCal h-side: finely segmented
 - o barrel: imaging EMCal outer barrel HCal
- High performance PID to separate π , K, p on track level
 - o also need good e/π separation for scattered electron
 - o AC-LGAD TOF, pfRICH, hpDIRC, dRICH
- Many other ancillary detectors integrated in the beam line: low-Q² tagger, Roman Pots, Zero-Degree Calorimeter

Integration into Interaction Region (±40m) is critical

The Future Circular Collider (FCC) A new 91 km tunnel to host multiple colliders






FCC-hh reference detector



Silicon Tracker (400 m²) covering $|\eta|$ < 6



Solenoid magnets: **B = 4T**

50m long, 20m diameter


- 2. Barrel ECAL Lar
- 3. Endap and forward HCAL/ECAL Lar
- 4. Barrel HCAL Fe/Sci
- 5. Central Solenoid (>10m diameter)+ two forward solenoids
- Muon system

CMOS sensors in the realm of HI experiments







STAR HFT - 2014 ULTIMATE



ALICE ITS2 - 2021 ALPIDE



sPHENIX MVTX - 2023 **ALPIDE**




NA61 prototype **ALPIDE**




MIMOSIS




ALICE ITS3 - 2028 "Wafer-scale MOS"



NA60+ - 2028 (based on ALICE ITS3)



(based on ALICE ITS3)



ALICE3 next generation

State-of-the-art CMOS Active Pixel Sensors




ALPIDE Sensors for ALICE ITS and MFT




Based on CMOS technology 180nm

- 10 m² active silicon area
- 12.5 **G**-pixels
- 50 μm thin sensor
- Spatial resolution ~5μm
- Max particle rate ~ 100 MHz /cm²



- Detection layer: high-resistivity (> $1k\Omega$ cm) epi layer (25μm)
- Very small collection diodes (2 μm diameter) ⇒ low capacitance (~fF)
- Reverse bias voltage to substrate (contact from the top)
- CMOS circuitry within active area



Evolution of CMOS APS for HEP

CERN & Tower

full depletion of the sensitive layer combined with a low capacitance electrode



Contents lists available at ScienceDirect


Nuclear Inst. and Methods in Physics Research, A

journal homepage: www.elsevier.com/locate/nima



A process modification for CMOS monolithic active pixel sensors for enhanced depletion, timing performance and radiation tolerance

W. Snoeys ^a, *, G. Aglieri Rinella ^a, H. Hillemanns ^a, T. Kugathasan ^a, M. Mager ^a, L. Musa ^a, P. Riedler ^a, F. Reidt ^a, J. Van Hoorne ^a, A. Fenigstein ^b, T. Leitner ^b




First studied with 180nm


an even better performance with 65nm

Fully depleted sensor

- charge collection time $\ll 1ns$
- capacitance ≈ 1fF
- operational up to 10¹⁵ n_{eq} /cm²
- Time res.: 67 ps (w/o corrections)



Operated at room temperature!



doi:10.48550/arXiv.2212.08621


a CERN, CH-1211 Geneva 23, Switzerland

^b TowerJazz Semiconductor, Migdal Haemek, 23105, Israel

Wafer-size curved sensors

Nearly massless truly cylindrical detectors

TPSCo ISC 65nm CMOS Imaging 300mm wafers + stitching



from reticle-size to wafer-size





thin (<50μm CMOS can be curled)

Currently being developed for ALICE (ITS3)

Baseline option also for:

- EPIC
- HIAF
- ALICE 3 (++ improv.)








Retractable vertex detector inside beampipe




ALICE 3 vertex detector









J.D. Bjorken in a 1985 paper on Ξ_{cc} and Ω_{ccc} measurements:

My guess for the resolution requirement is (ideally) a few microns(!!) in the transverse direction and perhaps 200 microns in the longitudinal.


AIP Conference Proceedings 132, 390 (1985)

pointing resolution:~ few µm at 1 GeV/c, 30 µm at 100 MeV


CMOS Pixel Sensors for imaging calorimeters



ALICE FoCal




Shower separation in FoCal-E pixels



Pixel layers (ALPIDE) interleaved with Si PAD


Similar approach is also considered for the EPIC BECAL



Particle Identification

PID continues to be a trademark of HI facilities

- FAIR / CBM: RICH, TOF, TRD, Muon ID
- LHC / ALICE 3: RICH, TOF, Muon ID
- EIC / EPIC: DIRC, RICH, TOF, Calorimetry
- ⇒ important also for future e⁺e⁻ facilities




Novel developments & trends

Time of Flight: AC-LGAD, CMOS with gain layer, SiPM

RICH:

- "biomimetic" approach to arrange optical elements to focus light into sensors
- photon sensors: 2.5 and 3D SiPM, LAPPD


Cherenkov Angle and ToF measurement with one detector





Cherenkov light detectors

CBM RICH

CO2 radiator, spherical mirrors, MAPMT









advanced optics


ALICE 3 - proximity focused (aerogel) RICH with projective geometry



better quality image

LHCb & FCC-ee) ("biomimetic" approach) - tile the plane with separate cells, each with its own mirror, sensor array






ARC detector (one cell)

Cherenkov Angle and ToF with one detector





Cherenkov light for TOF measurement in a thin radiator


Time resolution improves

- Single SiPM σ_T improves (signal over several SPADs)
- Weighted average of signals from several SiPMs


Single SPAD dark counts can be filtered out from signal clusters

Tests at the CERN PS (prelim.)





simulation for 5 GeV/c pions



Time resolution 10-20 ps

for number of fired pixels \geq 6 (> 90% of events!)

Conclusions




- Landscape of AA and eA facilities in the short and long-term, will span a wide energy spectrum and at increasingly higher intensities
- The new facilities and detectors offer remarkable opportunities for conducting comprehensive investigations into hot and dense quark matter as well as cold QCD matter.
- These advancements call for higher precision, faster, and more sophisticated detector technologies
- Detector technology innovation will remain a driving force behind the advancement of our research
- Close collaboration with industrial partners essential to access and effectively leverage the most advanced technologies

CEE @ the High Intensity Accelerator Facility (HIAF)



New campus in Huizhou (Guangdong) under construction (2018 – 2025)




S. Ruan NIM A 892 (2018) J.C. Yang et al., NIM B 317 (2013)

High-intensity synchrotron Booster Ring (569 m)

- Extraction energy: 0.2-0.8 GeV / u
- Operation period: 3-10 s, Intensity (²³⁸U) ~10¹¹/pulse

CSR External-targe Experiment

Focus on event-by-event fluctuations and correlations hadron production and flow




Hadron spectrometer

- acceptance: 2° 90°
- interaction rates: > 100 kHz
- free- streaming DAQ

Meeting Tomorrow's Demands: Innovations Needed




Assuming $L = 30 \cdot 10^{-4} cm^{-2} s^{-1}$ and $30 ab^{-1}$



First tracker layer (R = 2.5 cm)

- Particle flux: 20 GHz cm⁻²
- Data throughput: 0.3 Tbit s⁻¹ cm⁻²
- Fluency: 5.5 x 10¹⁷ 1Mev N_{eq} cm⁻²



FCC-hh nominal average pile-up: $O(1000) = 5-7 \times HL-LHC = 33 \times LHC$

- 4D vertexing with additional track time-stamp is essential!
- Yet, very challenging beyond $|\eta| > 4$ even for $\delta t = 5 10ps$

Present technologies cannot sustain these values up to R = 40cm ⇒ novel detectors needed!

Advanced on-chip signal processing ("edge processing")





In recent years, attempts to integrate AI in imagers

Despite of a low-performance eye-lens and limited bandwidth to the brain, the human visual system generates stunning images with a low-power, sparse and asynchronous stream of digital spike events

SONY - IMX500, May 2020

Image sensor equipped with AI processing functionality 12 M pixel, 1.55μm pitch, 5.6 x 5.6 mm²





Modern **3D** hybrid stacking technology with multiple layers (Imager, DRAM, logic processor)



integrate sophisticated digital processing, including AI (the pixel sensor as first layer of AI)



several layers for measurement of space (small pixels, no time) and time coordinates (larger pixels, fast timing)

Industry's first 3-layer Stacked CMOS Image Sensor with DRAM for Smartphones (presented at ISSCC, Feb 2017)