



MQXFB: Improvements in magnet assembly

Susana Izquierdo Bermudez on behalf of MQXFB team

Acknowledgements: Jose Ferradas Troitino, Attilio Milanese, Ezio Todesco

<https://indico.cern.ch/event/1150724/>



CERN: April 29th, 2022

Outline

- Introduction to the magnet design
- MQXFS, MQXFA and MQXFB pre-load levels
- Improvements in MQXFB assembly process
- Conclusions

The focus of the presentation is on the analysis of the magnet straight section, since MQXFBP1 and MQXFBP2 were limited in middle of the magnet

Outline

- **Introduction to the magnet design**
- MQXFS, MQXFA and MQXFB pre-load levels
- Improvements in MQXFB assembly process
- Conclusions

Magnet design

- Target: 132.2 T/m; 150 mm coil aperture, **11.3 T B_{peak}**
- Q1/Q3 (by US-AUP Project), 2 magnets **MQXFA** with 4.2 m L_m
- Q2a/Q2b (by CERN), 1 magnet **MQXFB** with 7.15 m L_m
- Joint short model development program (**MQXFS**) to validate the design
- Different lengths, same design, very similar assembly procedure and loading target



MQXFS
(1.2 m)







MQXFA
(4.2 m)



MQXFB
(7.15 m)



Magnet assembly

	Bladder pressurization	Key insertion	Cool down	Powering
	Open enough clearance to insert the keys (key size + ≈ 0.3 mm clearance)	Insert the keys to set the RT pre-load level	Increase of pre-load due to the diff. of thermal contraction between aluminum and iron	Coil un-loading due to electromagnetic forces
F_{θ}/F_{em} shell	n. a.	40 %	87 %	93 %
F_{θ}/F_{em} pole	n. a.	40 %	87 %	10 %
				

Magnet assembly

		Bladder pressurization	Key insertion	Cool down	Powering (16.23/17.5 kA)
		Open enough clearance to be insert the keys (key size + 0.2-0.3 mm)	Insert the keys to set the RT pre-load level	Increase of pre-load due to the diff. of thermal contraction between aluminum and iron	Coil un-loading due to electromagnetic forces
σ_{θ} coil, Mpa	Ave Pole turn IL	-58	-52	-97	-6/-2
	Peak Pole turn IL	-72	-86	-113	-14/-8
	Peak Coil	-72	-86	-124	-109/-120
ANSYS Release 19.2 Build 19.2 NODAL SOLUTION STEP=2 SUB =1 TIME=2 SY (AVG) RSYS=1 PowerGraphics EFACET=1 AVRES=Mat DMX =.138E-03 SMN =-.857E+08 SMX =-.137E+08 .125E+09 125 MPa .110E+09 .950E+08 .800E+08 .650E+08 .500E+08 .350E+08 .200E+08 .500E+07 .100E+08 0 MPa		<p>Bladders Mid-plane</p>	<p>Keys 1</p>	<p>Cool-down</p>	<p>current 9</p>


Stress map and stress values for the new procedure, loading with auxiliary bladders in the cooling holes.
 Nominal assembly with 80 MPa pole compression at warm, 110 MPa at cold
 Uncertainty due to material properties and assembly tolerances ± 15 -20 MPa

Radial cracks and stress map

- The higher concentration of micro-cracks in the analyzed sections of coil 108 straight section is in IL the mid-plane block (see talk from S. Sgobba)

Coil 108, coil straight section

⚡ Conductor exhibiting micro-cracks (several sub-elements can be impacted for an indicated location)




Remark: In the case of BP1, with a maximum coil stress of 100 MPa at warm after loading, we expect 135 MPa in the pole block after cool down and a maximum of 110 MPa in the mid-plane at 15 kA

After cool down




Powering (16.23 kA)



Stress concentration region, 110 MPa at I_{nom} (120 MPa at I_{ult})

Mechanical instrumentation

Coils instrumented with strain gauges and of FBGs




Strain is measured in:



1. Rods
2. Aluminum shell
3. Coil Titanium pole, providing the peak stress in the coil (pole turn inner layer) during loading and cool down.

For MQXFS, one longitudinal section is measured. For MQXFB, measurements are performed in 3 longitudinal sections

Rods instrumented with strain gauges



Al-shells instrumented with strain gauges



MQXFS, one longitudinal measuring location

MQXFB, three longitudinal measuring locations


Outline

- Introduction to the magnet design
- **MQXFS, MQXFA and MQXFB pre-load levels**
- Improvements in MQXFB assembly process
- Conclusions


MQXFS

- Azimuthal pre-load level parameter space explored with the short model program, with magnets reaching > 90 % of the short sample limit, with a pole coil compression ranging from:
 - 25 MPa – 115 MPa after RT loading
 - 65 MPa – 120 MPa after cool down
- During bladder operations, 20-40 MPa overshoot needed to insert the keys, with a peak of 140 MPa in one coil in MQXFS5.
- The measured unloading of the pole during powering is consistent with the expected pre-stress lever from the RT assembly: lower pre-load at room temperature, sooner unloading during powering

Measured azimuthal stress during RT loading. Error bars represent the spread among the 4 coils in the same longitudinal location



Change of azimuthal pole pre-stress during powering, as a function of the square of the current. Average among the 4 coils in the magnet.




I_{max} (1.9 K), kA	18.5	19.2	19.1	19.1	19.6	18.5	$I_{nom} = 16.23$ kA
I_{max} (4.5 K), kA	17.9	18.0	18.2	18.1	18.1	18.2	$I_{ult} = 17.5$ kA


MQXFA

- AUP defined the pre-load targets as reference MQXFS4 (see MQXFA Series Magnet Production Specification, US-HiLumi-doc-4009)
- The target **average** measured stress on coils and shells at the end of the loading (after at least 24 h) shall be
 - **Shell** average azimuthal stress: **+58 ± 6 MPa**
 - **Coil** (winding pole) average azimuthal stress: **-80 ± 8 MPa**
- For the **maximum stress** reached during the pre-load operations, the maximum compression measured on each **coil** shall never exceed **-110 MPa**
- After cool down, the pole pre-stress is 100 – 110 MPa → coils remain in contact with the winding pole up to 80-90 % of the nominal current. Good magnet to magnet reproducibility

Training performance MQXFS4




Change of azimuthal pole pre-stress during powering, as a function of the square of the current.



MQXFB – RT loading


- MQXFB and MQXFA have identical **target** preload, i.e., **average shell stress $+58 \pm 6$ MPa**, **average coil stress** (winding pole): **-80 ± 8 MPa**
- In terms of **peak** stress during loading, the maximum measured in MQXFBP2&P3 magnets was **-140 MPa**, higher than the -110 MPa set as limit for MQXFA, but reached in MQXFS5
- The increase of coil azimuthal stress during welding is lower than the overshoot during loading



MQXFB – Cold

- At cold, only MQXFBP2 measurements in the return and middle magnet sections are available
 - In MQXFBP2, the increase of the coil stress during welding was 30 MPa (vs 8 ± 8 MPa specified at the time), so the final stress of the coil at cold is 15-20 MPa higher than the initial target
 - Un-loading of the pole turn measured with the mechanical instrumentation when approaching the nominal current, as expected from the RT pre-load levels when including the additional stress form the welding

Change of azimuthal pole pre-stress during powering, as a function of the square of the current. Average among the 4 coils in the magnet.





Outline

- Introduction to the magnet design
- MQXFS, MQXFA and MQXFB pre-load levels
- **Improvements in MQXFB assembly process**
 - **New procedure for loading**
 - **Alignment**
 - **Bladders and axial pre-load**
- Conclusions


Improved procedure: Loading

- During bladder operations, 20 - 40 MPa overshoot needed to insert the keys
- New loading procedure developed in MQXBMT3, using auxiliary bladders in the cooling holes, allows to completely remove the 20 - 40 MPa overshoot of coil stress during loading



Bladder operation

Key insertion




Bladder operation

Key insertion


MQXFBMT3: the assembly validation experiment

Pressure sensors in each bladder circuit




Heavily instrumented experiment, for a full characterization of the mechanical behavior of the magnet

Rosette SG in the pole, confirmed a biaxial longitudinal and azimuthal strain state




Large Magnet Facility


Fuji pressure sensitive film




Displacement sensors on the OD to monitor deformation during loading



Distributed FBGs measurements around Al-shells



Geometrical measurements (alignment + pre-stress estimation)




Improved procedure: Alignment (yoke-shell)



- In MQXFBP3, mis-alignment in the horizontal axis between yoke-shell subassembly modules observed, resulting on a magnet 'snaky' shape (max-min = 1.4 mm), see [EDMS 2477740](#).
 - After cold mass completion, same shape as after magnet loading
- In MQXFBMT3, the external faces of the yoke modules were machined after shell-yoke subassembly, and the procedure & measurement system for the horizontal yoke shell subassembly was optimized, keeping the alignment of the outer surface of the Al shell is within $\pm 0.3\text{mm}$



MQXFBP3



MQXFBMT3





Improved procedure: Bladders, axial pre-load and coil pack

- During the loading of MQXFBP1, 8 bladders broke. One case resulted in an unbalance stress situation for the coils (see [EDMS 2276044](#))
 - New bladder technology (**tubular bladders** instead of welded plates) implemented in MQXFBP2. No bladder failure in BP2, BP3 and MT3.
- For MQXFBP2, improved **axial loading system** (4 pistons instead of 1) for an easier force balance among rods, including in-situ measurements of rods elongation during loading → Very good balance of force among the four rods
- Coil pack bolting** process optimized in MQXFBP3, reducing the spread of the average pole key gap per quadrant from 0.5 mm to 0.1 mm

Axial system with 4 rods



Coil pack squareness



Outline

- Introduction to the magnet design
- MQXFS, MQXFA and MQXFB pre-load levels
- Improvements in MQXFB assembly process
- **Conclusions**

Conclusions

- A **new loading procedure**, with auxiliary bladders in the cooling holes, has been developed and demonstrated in MQXFBMT3. The new loading method allows to **eliminate the 20-40 MPa overshoot** of coil stress during bladder operations.
- **MQXFBMT3** was heavily instrumented, it **validated** all parameters relevant for **magnet assembly**.
- In addition to the new loading procedure, the most **relevant improvements in magnet assembly** are:
 - New bladder tubular technology (MQXFBP2), allows loading without bladder failure
 - New axial loading system (MQXFBP2), for a more balanced axial preload
 - New coil bolting procedure (MQXFBP3), for a better alignment of the coil pack
 - New yoke-shell subassembly procedure (MQXFBMT3), for a better alignment of the structure
- Coils for the assembly of the next magnet, **MQXFB02**, are available, see [here](#) (Technical meeting to review and select the coils). Timeline for the assembly:
 - Yoke-shell & coil pack subassembly: May 2022
 - Magnet assembly and loading: June-July 2022




Additional slides




Mechanical instrumentation

Coils instrumented with strain gauges and of FBGs







Al-shells instrumented with strain gauges




The strain is measured in the coil titanium pole. The peak stress in the coil during loading and cool down is in the IL pole turn, very close to the stress in the Ti pole (measuring location)

Rods instrumented with strain gauges









MQXFS, one longitudinal measuring location




MQXFB, three longitudinal measuring locations

BP3 vs MT3 loading




Welding

- Welding requirements were modified, to assure no coupling of the SS vessel to the magnet (**Same** requirements for **AUP** and **CERN**)
 - Previous target:** 8 ± 8 MPa Δ Coil stress from welding
 - New target:** $0 + 8$ MPa Δ Coil stress from welding




Coil stress




Stress during bladders operation


All quadrants, with cooling channels



Quadrant by quadrant





Assembled magnet alignment






Improved procedure: Alignment (coil pack)


- By design, 0.25 mm gap between the pole key collar at room temperature
- Coil pack bolting process optimized in MQXFBP3, reducing the spread of the average pole key gap per quadrant from 0.5 mm to 0.05 mm




- Improved methodology and measuring system in MQXFBMT3, reaching a uniformity and squareness the coil pack of ± 0.1 mm and ± 0.2 mm respectively




RT loading MQXFS



RT transfer functions




1.9 K MQXFS




MQXFA


MQXFA03




MQXFA04




MQXFA05




MQXFA06











MQXFA07










MQXFA08












MQXFBP2_MI



MQXFBP2_RE

