

Contribution ID: 242

Type: Poster

C1Po2A-02: Overview of GTL's composite cryotank development

Monday 10 July 2023 14:00 (2 hours)

Over the last twelve years, Gloyer-Taylor Laboratories (GTL) has been developing and testing a series of ultra-lightweight composite cryogenic propellant tanks in a range of sizes (16"dia to 63"dia) and form factors (cylinders and spheres). These cryotanks have been validated to deliver 75% mass reduction compared to equivalent state-of-the-art cryotanks.

For example, GTL's 48"dia x 96"long composite cryotank [83.1 cu ft, 26.6 lb (44.3 lb with skirt extensions), Weight/volume = 0.32 lb/ft3 tank only] remained leak-tight through 18 cryo-thermal pressure cycles with liquid nitrogen with 7,500 micro-strain in the cylinder section and showed no sign of degradation from testing. While GTL initially focused on launch vehicle and spacecraft applications using liquid oxygen (LOX) and liquid methane (LCH4), recently GTL expanded our efforts to include liquid hydrogen (LH2) for emerging hydrogen electric aircraft and LH2 space vehicles. GTL is now developing all-composite, vacuum-jacketed, LH2 dewar-tanks that provide hydrogen weight fractions in the 60% to 80% range including composite dewar shell, multilayer insulation, and inner tank.

In this paper, GTL will provide an overview of GTL's composite cryotank development efforts and associated testing.

Author:Mr TAYLOR, Zachary (Gloyer-Taylor Laboratories Inc.)Co-author:GLOYER, Paul (Gloyer-Taylor Laboratories Inc.)

Presenter: Mr TAYLOR, Zachary (Gloyer-Taylor Laboratories Inc.)

Session Classification: C1Po2A: Aerospace Applications I: Devices