



中国科学院大学
University of Chinese Academy of Sciences



Dynamic simulation of DALS test facility cryoplant

Zheng Sun¹, Xilong Wang¹, Liangbin Hu², Lei Xu¹, Xu Shi¹

¹Dalian Institute of Chemical Physics (DICP)

²Institute of Advanced Science Facilities (IASF)



Contents

01 Background

02 Dynamic simulation model



03 Control loops

04 Results and discussion

05 Conclusions



Dalian Institute of Chemical Physics (DICP)





- Located in Dalian, Liaoning, China
 - Dalian Coherent Light Source User Facility (Room Temperature)
 - Dalian Advanced Light Source Test Facility


- 1 HTB, 1 VTB, 1 ITB, 1 CTB
- Cryogenic system(370 W@2 K), commissioning expected in 2023.12




Cryogenic system block diagram



1 Injector test bench




1 Horizontal test bench



1 Vertical test bench 1 Cryogenic test bench 4

What dynamic simulation can do?



- **Simple process calculations, reduce calculation time:** pressure drop calculation, valve selection, safety valve selection, etc.
- **Simulation of complex dynamic processes, virtual commissioning:** Cooldown, liquefaction, load variation, fast cooldown
- **Validate new process design:** add new components, new configuration
- **Validate new control strategies:** Model based prediction, Fuzzy control, Feed forward control, etc.
- **Failure simulation and failure prediction**
- **Operation training systems**


DALS test facility cryoplant



LN2: Liquid Nitrogen
HP: High Pressure
LP: Low Pressure

T: Turbine
HEX: Heat exchanger
CD:Cooldown

WU: Warm up
TS: Thermal shield



TFCP Expected Performance Data					
Section	LN2 Pre-cooling	Refrigeration Power @2 K	Thermal Shield @ 4.5-8 K	Thermal Shield @ 40-50 K	Liquefaction Rate g/s@ 1.3 bar
Refrigeration Mode	with	370	420	2600	-
P Supply	bar	3.5	3.5	13.5	-
P Return		-	1.3	12.9	-
T Supply	K	4.6	4.6	40	-
T Return		300	8	51.7	-
Mass flow	g/s	19.9	10.5	42	-
Fast cooldown Mode	with	-	420	2600	-
P Supply	bar	3.5	3.5	13.5	-
P Return		-	1.3	12.9	-
T Supply	K	4.8	4.8	40	-
T Return		-	7.9	50.9	-
Mass flow	g/s	57.7	10.5	45	-
Liquefaction Mode	with	-	-	-	30.4
	without	-	-	-	12.8

- **Fast Cool Down Mode:** **57.7 g/s, 4.8 K @ 3.5 bar**
- Large thermal gradient through Tc in SRF cavity help magnetic flux expulsion



Contents

01 Background

02 Dynamic simulation model

03 Control loops

04 Results and discussion

05 Conclusions




Ecosimpro introduction




EcosimPro
Modelling and Simulation Software

- Developed by EI company from Spain
- Models all systems that can be described as ODE, PDE and discrete event
- **EL language** modeling and graphical programming
- **Cryogenic library CRYOLIB** developed by CERN
- Easy modeling of complex cryogenic systems




CRYOLIB library

PLC library



Software Interface

370 W @ 2 K Refrigerator model





Compressor station:
FSD575 with VFD
ESD375 * 2
Gas management panel

Cold Box:
LN2 Pre-cooling, Turbines,
Heat exchangers, Dewar

Operation modes:


- Refrigeration mode
- Liquefaction mode
- Fast cooldown mode

Control loops of Compressors



- HP control: HP1.010.U.PC
 - HP > 13.8 bar, HP1.QN030 OPEN
 - HP < 13.8 bar, HP1.QN070 OPEN
- The set value of HP Setpoint is determined by three control loops:
 - LS1.015.U.PC: Dewar liquid level control
 - CW1.050.U.SC: Compressor revolution speed
 - LP1.011.U.PC: LP overpressure control
- LP Control: PID + Cascade
 - LP1.010.U.PC: Little valve
 - →HP1.055.U.GC: Large valve
 - →CW1.051.U.GC: Revolution control

Control loops of Turbines



Turbine revolution control:
TU1.050.U.SC,
TU2.050.U.SC,
TU3.050.U.SC

TU2.065.U.TC: TU2
Temperature control
through TU3 inlet valve


TU2.067.U.TC: TU2
Temperature control
through TU3 bypass
valve

TU2.066.U.TC:
Cooldown ramp control
through TU1 inlet valve

Sequence control




1	Compressor Mode
2	Cold box connection
3	Cold Mode
3-1	LN2 precooling
3-2	TU1,2 Start
4	HTTS Mode
5	JT Turbine Mode
6	sHe Supply
7	LTTS Mode



- Sequence control through Experiment code
- Loop switch through adjusting Model EL code

Simulation target




Current target:

- Simulation of Site Acceptance (SAT)
- Verify the model accuracy with TS diagram from manufacturer

Site acceptance sequence:

- Compressor Mode → Cold Mode → JT Mode → SAT Mode
- Check Dewar level rising rate (Liquefaction Mode)
- All 4.5 K bypass through CD line, HT shield heater 2600 W, LT shield heater 400 W
- Adjust LT shield mass flow 10.5 g/s and Coriolis 30.4 g/s check Dewar level rise (Refrigeration Mode)
- Adjust LT shield mass flow 10.5 g/s and Coriolis 68.2 g/s (FCD Mode)





Contents

01 Background

02 Dynamic simulation model

03 Control loops

04 Results and discussion




05 Conclusions





Cooldown process curve



LP: Low pressure HP: High pressure



Dewar level curve



Steady state parameters comparison




Liquefaction Mode

Parameters from Manufacturer TS diagram

Parameters calculated from Ecosimpro

Liquefaction rate: 32 g/s

29.26 g/s




Steady state parameters comparison



Refrigeration Mode


2 K mass flow: 19.9 g/s
19.9 g/s



Steady state parameters comparison



FCD Mode





Contents

01 Background

02 Dynamic simulation model

03 Control loops

04 Results and discussion

05 Conclusions

Conclusions



- A refrigerator model of the DALS test facility was built, including sequence control and control loop switch logic
- Three operation modes were simulated with Ecosimpro and the parameters correspond well with the TS diagram
- The next step is to improve the model accuracy based on the future commissioning data and use it to solve real problems



Thank you

Acknowledgements

Dalian local government

Guy Gistau Baguer

J G Weisend II

IASF, Shenzhen

IHEP, CAS

SHINE

CERN

DESY

ESS