

From 32 T to the 40 T All-Superconducting Magnet



Muon Collider Collaboration Meeting

October 11 - 14, 2022

Iain R. Dixon

Dima Abraimov, Hongyu Bai, Mark Bird, Ernesto Bosque, Kwangmin Kim, Dylan Kolb-Bond, Jan Jaroszynski, Andrey Gavrilin,
Jun Lu, Denis Markiewicz, Robert Walsh, Huub Weijers...



Overview

- 32 T All-superconducting magnet
 - *Timeline and development*
- 40 T All-superconducting magnet
 - *Technical challenges*
 - *Test coils*
 - *Insulated REBCO*
 - *Resistive Insulation REBCO*
- Outlook



The 32 T magnet

Key parameters:

Center field	32 T
Clear bore	34 mm
Ramp time	1 hour
Uniformity 1 cm DSV	5×10^{-4}
Operating temperature	4.2 K
Stored energy	8.3 MJ
Expected cycles/20 years	50,000
System weight	2.6 ton



15 T / 250 mm bore LTS magnet
17 T / 34 mm bore REBCO coils
Separately powered, simultaneously ramped

REBCO: 2 double pancake coils
Nb₃Sn coils
NbTi coils




32 T Project Timeline and Development


- 2007 – 2008 IGC/SP test two test coils @NHMFL to 27 T (19 T background)
- 2008 NHMFL 33.4 T Test coil (31 T background)
- 2009 Initial funding of 32 T
- 2009 – 2012 Additional test coils




31 T + 2.4 T



High Hoop-stress coils
>760 MPa




42-62 Mark 1:
1st test coil



42-62 Mark 2:
2nd test coil


Early Heater Design





32 T Project Timeline and Development

- 2013 – 2014 Prototype test coils

2013




20 - 70:
1st Full-featured Prototype



82 - 116:
2nd Full-featured Prototype





Modern Heater Design



32 T Project Timeline and Development

- 2015 – 2017 Construction and Testing




- 2020 Open for User Operations



40 T All-Superconducting Magnet Project

- National Science Foundation Funded Design Project through 2025
- Implementation/Construction Proposal to Follow
- Specifications:
 - Central field: 40 T
 - Operating temperature: 4.2 K
 - Cold bore diameter: ≥ 34 mm
 - Ramp rate: ≥ 0.5 T/min
 - Operating lifetime: 50,000 cycles or 20 years
 - Homogeneity: ≤ 500 ppm over a 1 cm DSV
 - 10 Gauss fringe field: < 5.4 m
 - Stabilization time: < 3 minutes
- Two design options are being considered
 - Insulated REBCO (I-REBCO)
 - Resistive Insulation REBCO (RI-REBCO)





40 T Technical Challenges - Compactness

- Simple scaling of the 32 T to 40 T is not feasible
 - LTS outsert field / bore size too large
 - Most economical to design HTS coils to fit inside the commercially available 15 T LTS or 12 T LTS (with inner Nb₃Sn coil removed)
 - Need to increase current density of HTS coils, J_{eng} , J_{cu}
 - For J_{eng} we need to increase $f_{lc} = I_{op}/I_c$
 - Reduced screening currents and better quench management
 - Higher chance of finding conductor defects
 - Better knowledge of conductor properties are required ($I_c(B, \theta)$, ab-plane)
 - For J_{cu}
 - 32 T: $J_{cu} = 420 \text{ A/mm}^2$
 - I-REBCO goal: $J_{cu} = 700 \text{ A/mm}^2$
 - RI-REBCO goal: $J_{cu} = 1500 \text{ A/mm}^2$






40 T Technical Challenges - Compactness




40 T Technical Challenges – Stress Management




- It is critical to have precise knowledge of the conductor strain state
- We are working to improve accuracy of electromagnetic-screening current strain calculations
- An electromagnetic model (TA formulation) computes current & density is coupled with a structural model for strain and deformations. Iterated to recompute e-m with updated applied field angle from conductor deformations.




40 T Technical Challenges – Stress Management



Petten Test Coil



40 T Technical Challenges - Conductor



Critical Current of Conductor for the 32 T

This conductor is "TOO GOOD"


Operating margin is large:

- Exceedingly stable
- 130,000 J to protect 100 kg HTS coils
- 300 J to protect 1400 kg LTS coils

40 T Technical Challenges - Conductor

Calculated critical current (32 T) at **full field**


- Operating current is 1/10 to 1/3 of critical current



In quench at least half coil the HTS volume must be driven normal to absorb stored energy (Hot-spot temperature < 200 K)



Must be driven normal at ~ same time

Operating current






40 T Technical Challenges - Conductor

- Design approach is to maintain a constant fraction of critical current
- Example design of a 12-disk coil with maximum $f_{Ic} = 0.70$ within a pancake
- Constant f_{Ic} is achieved by varying a “standard” conductor critical current from 25 % - 90 %




40 T Technical Challenges - Conductor

- The angular tilt of the REBCO ab-plane shifts the $I_c(\theta)$ peak
- Mixing up the “left” / “right” orientation can greatly affect the critical current of a module
- We are developing techniques to determine the angle and orientation of a tape’s ab-plane
- See Lu, ASC2022 2MPo2A-04



40 T Technical Challenges - Conductor




SuperPower YBCO Fatigue Life at 77 K




NOTES:

1. Load Control Tension-Tension Fatigue, $r = 0.1$
2. Ic Failure is defined as a permanent degradation of 1% reduction in Ic or more.

- Observed 6% Ic reduction at 4.2 K, 0.4% strain after 250 k cycles.




40 T, Small Scale Test Coils



PTC1
(Apr 2019)




LBC-AR
(Apr 2019)




PTC2
(Jun 2019)




LBC-CO
(Aug 2019)



PT1R
(Oct 2019)




Mini fatigue coil
– Off centered
(Jun 2020)




PT3
(July 2020)




Mti-TC0
(Oct 2020)




PTC4
(Dec 2020)




Mini fatigue coil
– centered
(Mar 2021)




Axial pressure test coils
(Mar 2021)



PTC5
(Mar 2021)



Axial pressure test coil:
two in hand
(April 2021)



PT6
(June 2021)



40 T, Mid-Scale Test Coils




- Most Recent Test Coils
 - I-REBCO: “TC2”
 - Single insert coil operated in the 45 T Outsert
 - Two-in-hand REBCO winding “MTI”
 - RI-REBCO: “RI-NC”
 - Two nested coils – self field
 - Inner coil: 12 DP’s
 - Outer coil: 18 DP’s







I-REBCO Test Coil – TC2

- Single insert coil operated in the 45 T Outsert
- Central field: 25.4 T (11.4 T background)
- Current: 570 A
- Stored energy: 47 kJ
- Inductance: 289 mH
- Six conductor grades
- $J_{cu} = 650 \text{ A/mm}^2$
- Protected via pulsed forming network




I-REBCO Test Coil – TC2

- Fully characterized I_c of each tape used in the test coil via torque magnetometry
 - See Jaroszynski ASC2022, 2MOr2B-01
- Critical surface of each spool is unique and not scalable based from single point measurements




I-REBCO Test Coil – TC2

- The main purpose of TC2 was to study quench
- Quench modeling now includes deformation of conductors from screening currents, which affects critical current
- Very good agreement between predictions and measurements




220720 TC2 Ramp up and Deliberate Quench thru Diode (PFN protected)




RI-Nested Coils

- Two nested REBCO Coils
- Central field: 19.2 T (225 A)
- Stored energy: 0.105 MJ
- Inductance: 4.15 H
- Target $R_c = 2.7 \text{ m}\Omega$
- Mid-plane pressure = 60 MPa (coil 2)
- Self contained axial forces, designed to 245 kN
- Testing occurred late September




RI-Nested Coils

- Quench tests
 - Active protection system
 - Varied energy level of quench heaters to study discharge time and quench propagation
 - Quench initiated
 - Coil 2, module 12




RI-Nested Coil

- Quench moment
 - Module starts to transition
 - $t \sim 57$ s
 - Voltage rises until exceeding threshold of 0.5 V for 5 ms
 - $t = 57.045$ s
 - Protection fires
 - $t = 57.046$ s
 - Other modules start to normalize within 10 ms
 - $t = 57.057$ s
- Comparisons with modeling are proceeding




RI-Nested Coils

- Contact resistance
 - Target $R_c = 2.7 \text{ m}\Omega$
 - Measured: $0.74 \text{ m}\Omega$
 - Using fast discharge method
 - Contact resistance remained constant through the testing



First discharge test



Final discharge test
(after quench tests)

Outlook

- Technical risks are being retired because of the results produced by the test coils and conductor characterizations – but there is still more to do
- Additional thermometry is being added to TC2, which will be retested in November
- RI-NC results are still being reviewed
- Within 1-year we will select the technology for the 40 T final design
- Final demonstration large scale coil testing to be performed based on final design