

Introduction to the LHC DCCT System

P.Odier

Plan


1. LHC parameters
2. General Layout
3. Distribution of the acquisition ranges
4. Mechanical Layout
5. Pictures
6. Electronics
7. Acquisition system
8. Quick check & calibration
9. Uncertainty-Resolution-Accuracy
10. Specifications
11. Results

LHC parameters relevant for the beam intensity measurement

Ring circumference [m]		26659	
Revolution period [μs]		88.9	
Revolution frequency [kHz]		11.245	
RF frequency [MHz]		400.8	
Harmonic number		35640	
Number of bunches		1 to 2808	
bunch spacing [ns]		24.95 to 88925	
Protons	Bunch charge	Probe [q]	2 E9
		Nominal [q]	1.15 E11
		Ultimate [q]	1.7 E11
	Circulating beam current	Probe [μA]	3.6
		Nominal [mA]	582
		Ultimate [mA]	860
Ions	Bunch charge	Early [q]	5.6 E8
		Nominal [q]	5.6 E9
	Circulating beam current	Early [mA]	6.4
		Nominal [mA]	0.64

} Large dynamic !


General layout




LHC DCCT Mechanical layout

caution: sketch not to scale!

for further details, see drawing LHCDGBT_0028




Picture (1)



General view of DCCTs A et B on beam 1


Picture (2)



Installation in SX4 (surface building)

Electronics

Simplified schematics




Acquisition system

Acquisition

- 50Hz ADC sampling rate, 8 channels/DCCT
- (4 ranges, temperature probes, etc.)

Real Time Program

- 10Hz interrupt
- ADC reading, autoranging
- 3 sets of scaling factors (precise, quick, theoretical)
- Status acquisition
- 10Hz and 1 Hz publishing results
- Interlock (Safe Beam Flag) based on Beam intensity and energy
- Logging (TIMBER) very convenient to analyze data afterwards



Quick check & calibration

- Quick check
 - A burst of 4 calibration pulses is systematically generated before each first injection (4E11, 4E12, 4E13 and 4E14 charges; 100ms per pulse; home made current generator)
 - Result evaluated by the CCC-sequencer agent
- Choice between 3 calibration modes, i.e. 3 different sets of scaling factors applied to the acquisitions:
 - Precise (used at the moment)
 - Scaling factors determined after averaging of the acquisition performed during a few minutes with a known current (commercial current generator, accuracy better than 0.1%) applied to the calibration winding
 - Theoretical (used in case...)
 - Quick (used as a check)
 - See above

Uncertainty-Resolution-Accuracy

Expected values based on measurements made in laboratory

calibrator accuracy	0.1%	Expected quality for the precise calibration
ADC #bit:	12	VME ADC used at the moment
noise (rms, 1s int.) [A]	2.0E-06	Conservative value (best case obtained is 1.3E-6)
lb = N *	1.8E-15	Relationship: beam current vs Nb of circulating charges
temp. coef [A/°C]	5.0E-06	Typical temperature dependance (sensor + FEE); equ. to: 2.8E+09 [charges/°C]
HR ADC #bit	24	Future improvement

Range	SF [charges/V]	FS [charges]	1 bit equivalent [charges]	Noise (rms, 1s int.) [charges]	Dominant absolute uncertainty	Resolution (rms, 1s int.) [charges]	Accuracy at stable temperature ±(% of reading + charges)	Accuracy at variable temperature ±(% of reading + charges +charges/°C)
1	1.00E+14	5.00E+14	2.44E+11	1.1E+09	± 1 bit	2.44E+11	0.1 + 2.44E11	0.1 + 2.5E11 +2.8E9
2	1.00E+13	5.00E+13	2.44E+10	1.1E+09	± 1 bit	2.44E+10	0.1 + 2.44E10	0.1 + 2.5E10 +2.8E9
3	1.00E+12	5.00E+12	2.44E+09	1.1E+09	± 1 bit	2.44E+09	0.1 + 2.44E9	0.1 + 2.5E9 +2.8E9
4	1.00E+11	5.00E+11	2.44E+08	1.1E+09	noise	1.1E+09	0.1 + 1.1E9	0.1 + 1.1E9 +2.8E9
HR	1.00E+14	5.00E+14	5.96E+07	1.1E+09	noise	1.1E+09	0.1 + 1.1E9	0.1 + 1.1E9 +2.8E9


Note: the offset is considered suppressed

DCCT main specifications

DCCT size including the magnetic shielding	
· Internal diameter	114mm
· External diameter	265mm
· Length	350mm
Vacuum pipe	
· External diameter	64mm
· Distance between beam 1 and beam 2 axes	192mm
Magnetic core	
Material	Nanocrystalline
Size (box)	168mm / 142mm / 23mm
μ_i	>100000
Dynamic range	1 μ A to 0.9A
Modulation frequency	212Hz
Acquisition sampling rate	50S/s
Noise	
measured during 1 hour with no beam	
(rms, 1s int. time)	
min.	1.3 μ A
typ.	2.1 μ A
max.	3.0 μ A

Results (1)


First beam observed (December 2008)




Results (2)

BCT signals during the first collision @ 3.5 TeV, March 30 2010 12h58 to 16h31

BEAM 1
2E10 charges




BEAM 2
2E10 charges



Results (3)

Multi injection (13), total: 5E12 (9mA)



Results (4)

Long term noise (December 2010, C.Barschel)

