

# Future Circular Colliders

CERN Accelerator School, 13 May 2022

Xavier Buffat, CERN  
on behalf of the FCC collaboration  
Slides by Michael Benedikt

LHC

PS

SPS

FCC



FUTURE  
CIRCULAR  
COLLIDER  
Innovation Study



<http://cern.ch/fcc>



Work supported by the **European Commission** under the **HORIZON 2020** projects **EuroCirCol**, grant agreement 654305; **EASITrain**, grant agreement no. 764879; **ARIES**, grant agreement 730871, **FCCIS**, grant agreement 951754, and **E-JADE**, contract no. 645479



European  
Commission

Horizon 2020  
European Union funding  
for Research & Innovation

photo: J. Wenninger


## **Copyright statement and speaker's release for video publishing**

The author consents to the photographic, audio and video recording of this lecture at the CERN Accelerator School. The term “lecture” includes any material incorporated therein including but not limited to text, images and references.

The author hereby grants CERN a royalty-free license to use his image and name as well as the recordings mentioned above, in order to post them on the CAS website.

The material is used for the sole purpose of illustration for teaching or scientific research. The author hereby confirms that to his best knowledge the content of the lecture does not infringe the copyright, intellectual property or privacy rights of any third party. The author has cited and credited any third-party contribution in accordance with applicable professional standards and legislation in matters of attribution.

# CERN Future Circular Collider Study







International FCC collaboration (CERN as host lab) to study:

- ~100 km tunnel infrastructure in Geneva area, linked to CERN
- $e^+e^-$  collider (*FCC-ee*), as potential first step
- $pp$ -collider (*FCC-hh*) → long-term goal, defining infrastructure requirements

**~16 T  $\Rightarrow$  100 TeV  $pp$  in 100 km**

- lepton-hadron collisions as options to FCC-hh





# FCC study: physics and performance targets

## FCC-ee:

- Exploration of 10 to 100 TeV energy scale via couplings with precision measurements
- ~20-50 fold improved precision on many EW quantities (equiv. to factor 5-7 in mass)  
( $m_Z$ ,  $m_W$ ,  $m_{\text{top}}$ ,  $\sin^2 \theta_w^{\text{eff}}$ ,  $R_b$ ,  $\alpha_{\text{QED}}(m_Z)$ ,  $\alpha_s(m_Z)$ , Higgs and top quark couplings)
- Machine design for highest possible luminosities at Z, WW, ZH and ttbar working points

## FCC-hh:

- Highest center of mass energy for direct production up to 20 - 30 TeV
- Huge production rates for single and multiple production of SM bosons (H,W,Z) and quarks
- Machine design for ~100 TeV c.m. energy & integrated luminosity  $\sim 20\text{ab}^{-1}$  within 25 years

# FCC-ee basic design choices

**double ring  $e^+e^-$  collider**  $\sim 100$  km

**follows footprint of FCC-hh**, except around IPs

**asymmetric IR layout & optics** to limit synchrotron radiation towards the detector

**large** horizontal crossing angle **30 mrad**


**crab-waist optics**

**presently 2 IPs** (alternative layouts with 3 or 4 IPs under study),

**synchrotron radiation power 50 MW/beam** at all beam energies; tapering of arc magnet strengths to match local energy

**common RF** for  $t\bar{t}$  running

**top-up injection** requires **booster synchrotron** in collider tunnel




K. Oide et al.



# FCC-ee design concept

based on lessons and techniques from past colliders (last 40 years)



**B-factories: KEKB & PEP-II:**

**double-ring lepton colliders,  
high beam currents,  
top-up injection**

**KEKB:  $e^+$  source**

**DAFNE: crab waist, double ring**

**S-KEKB: low  $\beta_y^*$ , crab waist**

**LEP: high energy, SR effects**


**VEPP-4M, LEP: precision E calibration**

**HERA, LEP, RHIC: spin gymnastics**

combining successful ingredients of several recent colliders → highest luminosities & energies



# FCC-ee: efficient Higgs/electroweak factory



luminosity  $L$  per  
supplied  
electrical wall-  
plug power  $P_{WP}$   
is shown as a  
function of  
centre-of-mass  
energy for  
several  
proposed future  
lepton colliders

## Luminosity vs. capital cost


- for the H running, with  $5 \text{ ab}^{-1}$  accumulated over 3 years and  $10^6$  H produced, the total investment cost ( $\sim 10$  BCHF) corresponds to **10 kCHF per produced Higgs boson**
- for the Z running with  $150 \text{ ab}^{-1}$  accumulated over 4 years and  $5 \times 10^{12}$  Z produced, the total investment cost corresponds to **10 kCHF per  $5 \times 10^6$  Z bosons**

This is the number of Z bosons collected by each experiment during the entire LEP programme !

**Capital cost per luminosity dramatically decreased compared with LEP !**



# FCC-ee asymmetric crab-waist IR optics



yellow boxes:  
dipole magnets

**Novel asymmetric IR optics**  
to suppress synchrotron  
radiation toward the IP,  $E_{\text{critical}}$   
**<100 keV from 450 m from IP**  
**(e) – lesson from LEP**

H. Burkhardt, A. Blondel, M. Koratzinos, K. Oide, et al.

**4 sextupoles (a–d) for local vertical  
chromaticity correction combined w.  
crab waist, optimized for each working  
point – novel “virtual crab waist”,  
standard crab waist demonstrated at  
DAFNE**

K. Oide et al., Phys. Rev. Accel. Beams 19, 111005 (2016)

# FCC-ee RF staging


“Ampere-class” machine

WP	$V_{rf}$ [GV]	#bunches	$I_{beam}$ [mA]
Z	0.1	16640	1390
W	0.44	2000	147
H	2.0	393	29
ttbar	10.9	48	5.4

three sets of RF cavities to cover all options for FCC-ee & booster:

- high intensity (Z, FCC-hh): 400 MHz mono-cell cavities (4/cryom.)
- higher energy (W, H, t): 400 MHz four-cell cavities (4/cryomodule)
- ttbar machine complement: 800 MHz five-cell cavities (4/cryom.)
- installation sequence comparable to LEP ( $\approx 30$  CM/shutdown)

“high-gradient” machine



R&D aimed at improving performance & efficiency and reducing cost:

- improved Nb/Cu coating/sputtering, partner STFC (e.g. ECR fibre growth, HiPIMS)
- new cavity fabrication techniques, partner STFC (e.g. EHF, improved polishing, seamless)
- coating of A15 superconductors (e.g. Nb<sub>3</sub>Sn), · cryo-module design optimisation
- bulk Nb cavity R&D at FNAL, Cornell, JLAB, also KEK and CEPC/IHEP
- MW-class fundamental power couplers for 400 MHz; · novel high-efficiency klystrons

## Seamless 400 MHz single-cell cavity formed by spinning at INFN-LNL




Legnaro, Feb 2018

V. Palmieri  
C. Pira

Tooling fabricated and successfully tested with an Aluminium cavity.

## high-efficiency klystron at CERN



novel klystron  
bunching methods:  
**LHC klystron**  
**retrofit** as proof of  
principle for FCC

Parameter	present TH2167	CSM upgrade
Frequency [MHz]	400	
Beam voltage [kV]	54	
Saturated RF power [kW]	300	350
Efficiency [%]	60	70




# SRF R&D program, FCC-eh option and ERL



5-cell 800 MHz cavity, JLAB prototype for FCC-ee (top mode) & FCC-eh; also single-cell cavities for all FCC's


optimized for high energy operation



**FCC-eh: 60 GeV  $e^-$  from  
Energy Recovery Linac (ERL)  
PERLE@Orsay ERL test facility**

BINP, CERN, Daresbury/Liverpool, Jlab, Orsay +..

400 MeV, 3 turns,  
20 mA, 802 MHz



CDR

J Phys G [arXiv:1705. 08783]



Intensity 100 x ELI: technology, beam dynamics, physics







# Prototypes of FCC-ee low-power magnets

**Twin-dipole design with 2× power saving  
16 MW (at 175 GeV), with Al busbars**




prototype

**Twin F/D arc quad  
design with  
2× power saving  
25 MW (at 175 GeV),  
with Cu conductor**



prototype

# FCC-ee injector complex (baseline)



SLC/SuperKEKB-like 6 GeV S-band linac accelerating 1 or 2 bunches ( $2E10/b$ ), with repetition rate **100-200 Hz**


**Same linac** used for e<sup>+</sup> production @ **4.46 GeV**  
 e<sup>+</sup> beam emittances reduced in DR @ **1.54 GeV**

Injection @ **6 GeV** into pre-booster Ring (SPS or new ring) & accel. to 20 GeV, or 20 GeV linac

injection to main Booster @ **20 GeV** and interleaved filling of e<sup>+</sup>/e<sup>-</sup> (**<20 min for full filling**) and continuous top-up, typical rate 1/minute (Z) to 1/10s (tt)




# FCC-hh: highest collision energies




- **order of magnitude performance increase** in both **energy & luminosity**
- **100 TeV cm collision energy** (vs 14 TeV for LHC)
- **20 ab<sup>-1</sup> per experiment collected over 25 years** of operation (vs 3 ab<sup>-1</sup> for LHC)
- similar performance increase as from Tevatron to LHC
- **key technology: high-field magnets**

from  
LHC technology  
8.3 T NbTi dipole



via  
HL-LHC technology  
12 T Nb<sub>3</sub>Sn quadrupole





FNAL dipole  
demonstrator  
14.5 T Nb<sub>3</sub>Sn

# Worldwide FCC Nb<sub>3</sub>Sn program

Main development goal is wire performance increase:

- $J_c$  (16T, 4.2K) > 1500 A/mm<sup>2</sup> → 50% increase wrt HL-LHC wire
- Reduction of coil & magnet cross-section

After 1-2 years development, prototype Nb<sub>3</sub>Sn wires from several new industrial FCC partners already achieve HL-LHC  $J_c$  performance



## FCC conductor development collaboration:

- Bochvar Institute (production at TVEL), **Russia**
- KEK (Jastec and Furukawa), **Japan**
- KAT, **Korea**, Columbus, **Italy**
- University of Geneva, **Switzerland**
- Technical University of Vienna, **Austria**
- SPIN, **Italy**, University of Freiberg, **Germany**
- Bruker, **Germany**, Luvata Pori, **Finland**


## 2019/20 results from US, meeting FCC $J_c$ specs:

- Florida State University: high- $J_c$  Nb<sub>3</sub>Sn via Hf addition
- Hyper Tech /Ohio SU/FNAL: high- $J_c$  Nb<sub>3</sub>Sn via artificial pinning centres based on Zr oxide.



# 16 T dipole design activities and options


Cos-theta



INFN


H2020  
EuroCirCol  
A key to New Physics

Common coils




CIEMAT

Swiss contribution




Canted Cos-theta




PSI

Blocks



CEA

The U.S. Magnet Development Program Plan



S. A. Gourlay, S. O. Prestemon  
Lawrence Berkeley National Laboratory  
Berkeley, CA 94720

A. V. Zlobin, L. Cooley  
Fermi National Accelerator Laboratory  
Batavia, IL 60510

D. Larbalestier  
Florida State University and the  
National High Magnetic Field Laboratory  
Tallahassee, FL 32310

Intercepting ribs  
Conductor  
Spar  
Shrinking Al tube





LBNL

FNAL


Short model magnets (1.5 m lengths) will be built until 2025



- synchrotron radiation** ( $\sim 30 \text{ W/m/beam}$  (@16 T field) (cf. LHC  $< 0.2 \text{ W/m}$ )  $\sim 5 \text{ MW}$  total load in arcs
- absorption of synchrotron radiation at higher temperature ( $> 1.8 \text{ K}$ )** for cryogenic efficiency
  - provision of beam vacuum, suppression of photo-electrons, electron cloud effect, impedance, etc.



# FCC-hh operation phases and luminosity



Phase 1: Controlled transvers blow-up

Phase 2: High beam-beam tune shift

**phase 1:**

$\beta^* = 1.1 \text{ m}$ ,  $\Delta Q_{\text{tot}} = 0.01$ ,  $t_{\text{ta}} = 5 \text{ h}$   
**250 fb<sup>-1</sup> / year**

**phase 2:**

$\beta^* = 0.3 \text{ m}$ ,  $\Delta Q_{\text{tot}} = 0.03$ ,  $t_{\text{ta}} = 4 \text{ h}$   
**1 ab<sup>-1</sup> / year**


**Transition via operation experience,  
 no HW modification**

**Total integrated luminosity over  
 25 years operation:  
 O(20) ab<sup>-1</sup>/experiment  
 consistent with physics goals**




# FCC-hh injector options and transfer lines

Baseline:  
LHC @ 3.3 TeV



Alternative:  
scSPS @ 1.3 TeV





Current baseline:

- **Injection energy 3.3 TeV LHC**  
→ Field-swing FCC-hh like LHC

Alternative option:


- **Injection from SPS<sub>upgrade</sub> around 1.3 TeV**
- **SPS<sub>upgrade</sub> could be based on fast-cycling SC magnets, 6-7T, ~ 1T/s ramp, cf. SIS 300 design**





## present baseline position was established considering:

- lowest risk for construction, fastest and cheapest construction
- feasible positions for large span caverns (most challenging structures)
- 90 – 100 km circumference
- 12 surface sites with few ha area each




# collider placement optimisation



layout & placement optimisation across both host states (Switzerland and France) ;  
following "avoid-reduce-compensate" directive of European & French regulatory frameworks ;

- permitting **world-leading** diverse requirements and constraints:
- **scientific research**
- **technical feasibility of civil engineering** and subsurface constraints
- **territorial constraints on surface** and subsurface
- **nature, accessibility**, technical infrastructure, resource needs & constraints
- economic factors including benefits for, and synergies, with the **regional developments**
- ...

collaborative effort: CERN technical experts, consulting companies, government-notified bodies









- Total construction duration 7 years
- First sectors ready after 4.5 years

# FCC-tunnel integration in the arcs

**FCC-ee**      **FCC-hh**  
 5.5 m inner diameter






# FCC-hh reference detector

- 4T, 10m solenoid, unshielded
- **Forward solenoids, unshielded**
- Silicon tracker
- Barrel ECAL LAr
- Barrel HCAL Fe/Sci
- Endcap HCAL/ECAL LAr
- Forward HCAL/ECAL LAr

Subdetector performance (tracker, calorimeter etc.) was simulated and parametrized for fast physics simulation (DELPHES).




- Challenges:
- Pileup of 1000
- Radiation levels up to  $10^{18} \text{ cm}^{-2}$  1MeV neutron equivalent vs.  $10^{16} \text{ cm}^{-2}$  at HL-LHC
- Integration, opening and maintenance scenarios

**50m length, 20m diameter  
similar to size of ATLAS**

# Common experimental points (A, G)

Distance between detector cavern and service cavern 50 m.  
Strayfield of unshielded detector solenoid  $< 5\text{mT}$ .




Preliminary design of access and cable paths






# FCC integrated project technical schedule



# FCC-integrated project cost estimate

Domain	Cost in MCHF
Stage 1 - Civil Engineering	5,400
Stage 1 - Technical Infrastructure	2,200
Stage 1 - FCC-ee Machine and Injector Complex	4,000
Stage 2 - Civil Engineering complement	600
Stage 2 - Technical Infrastructure adaptation	2,800
Stage 2 - FCC-hh Machine and Injector complex	13,600
<b>TOTAL construction cost for integral FCC project</b>	<b>28,600</b>



**total construction cost FCC-ee (Z, W, H) : ~10,500 MCHF & 1,100 MCHF (tt)**

**total construction cost for subsequent FCC-hh: 17,000 MCHF.**

(FCC-hh stand alone cost ~25 BCHF)



# FCC CDR and Study Documentation



- **FCC-Conceptual Design Reports:**

- Vol 1 Physics, Vol 2 FCC-ee, Vol 3 FCC-hh, Vol 4 HE-LHC
- CDRs published in **European Physical Journal C (Vol 1) and ST (Vol 2 – 4)**

EPJ C 79, 6 (2019) 474 , EPJ ST 228, 2 (2019) 261-623 ,

EPJ ST 228, 4 (2019) 755-1107 , EPJ ST 228, 5 (2019) 1109-1382

- **Summary documents provided to EPPSU SG**

- FCC-integral, FCC-ee, FCC-hh, HE-LHC
- Accessible on <http://fcc-cdr.web.cern.ch/>



# Status and Outlook

- **1st phase** of FCC design study **completed** → **baseline machine designs**, performance matching physics requirements, in **4 CDRs**.
- **Integrated FCC programme** submitted to European Strategy Update 2019/20 → **Request for feasibility study as basis for project decision by 2026/27**
- **Next steps: concrete local/regional implementation scenario** in collaboration **with host state authorities**, accompanied by **machine optimization, physics studies and technology R&D**, performed **via global collaboration** and supported by **EC H2020 Design Study FCCIS**, to **prove feasibility by 2025/26**
- Long term goal: **world-leading HEP infrastructure for 21<sup>st</sup> century** to push the particle-physics **precision and energy frontiers** far beyond present limits.
- **Success of FCC relies on strong global participation !**

*Core sentence and main request “order of the further FCC study”:*

“Europe, together with its international partners, should investigate the **technical and financial feasibility of a future hadron collider at CERN with a centre-of-mass energy of at least 100 TeV and with an electron-positron Higgs and electroweak factory as a possible first stage.** Such a feasibility study of the colliders and related infrastructure should be established as a global endeavour and be completed on the timescale of the next Strategy update.”





# FCC integrated program

## inspired by successful LEP – LHC programs at CERN

comprehensive cost-effective program maximizing physics opportunities

- **stage 1: FCC-ee (Z, W, H,  $t\bar{t}$ ) as Higgs factory, electroweak & and top factory at highest luminosities**
- **stage 2: FCC-hh (~100 TeV) as natural continuation at energy frontier, with ion and eh options**
- complementary physics
- common civil engineering and technical infrastructures
- building on and reusing CERN's existing infrastructure
- FCC integrated project allows seamless continuation of HEP after HL-LHC







# FCC-ee Collider Parameters (stage 1)


parameter	Z	WW	H (ZH)	ttbar
beam energy [GeV]	45	80	120	182.5
beam current [mA]	1390	147	29	5.4
no. bunches/beam	16640	2000	393	48
bunch intensity [10 <sup>11</sup> ]	1.7	1.5	1.5	2.3
SR energy loss / turn [GeV]	0.036	0.34	1.72	9.21
total RF voltage [GV]	0.1	0.44	2.0	10.9
long. damping time [turns]	1281	235	70	20
horizontal beta* [m]	0.15	0.2	0.3	1
vertical beta* [mm]	0.8	1	1	1.6
horiz. geometric emittance [nm]	0.27	0.28	0.63	1.46
vert. geom. emittance [pm]	1.0	1.7	1.3	2.9
bunch length with SR / BS [mm]	3.5 / 12.1	3.0 / 6.0	3.3 / 5.3	2.0 / 2.5
luminosity per IP [10 <sup>34</sup> cm <sup>-2</sup> s <sup>-1</sup> ]	230	28	8.5	1.55
beam lifetime rad Bhabha / BS [min]	68 / >200	49 / >1000	38 / 18	40 / 18



# FCC-hh (pp) collider parameters (stage 2)

parameter	FCC-hh		HL-LHC	LHC
collision energy cms [TeV]	100		14	14
dipole field [T]	16		8.33	8.33
circumference [km]	97.75		26.7	26.7
beam current [A]	0.5		1.1	0.58
bunch intensity [ $10^{11}$ ]	1	1	2.2	1.15
bunch spacing [ns]	25	25	25	25
synchr. rad. power / ring [kW]	2400		7.3	3.6
SR power / length [W/m/ap.]	28.4		0.33	0.17
long. emit. damping time [h]	0.54		12.9	12.9
beta* [m]	1.1	0.3	0.15 (min.)	0.55
normalized emittance [ $\mu\text{m}$ ]	2.2		2.5	3.75
peak luminosity [ $10^{34} \text{ cm}^{-2}\text{s}^{-1}$ ]	5	30	5 (lev.)	1
events/bunch crossing	170	1000	132	27
stored energy/beam [GJ]	8.4		0.7	0.36

# Cryoplants – energy efficiency



BS temperature choice is overall optimisation of:

- Cryoplane power consumption
- Vacuum system performance
- Impedance and beam stability


- Optimum beam screen operation temperature 40 - 60 K
- Electrical power for beam screen cooling ~100 MW .






# supply & distribution of electrical energy


additional 200 MW available for FCC at each of the three 400 kV sources





per-point power requirements as input for infrastructure-optimized conceptual design (peak FCC-ee: 260-340 MW, total FCC-hh: 550 MW)



If one power source goes down fall back to “degraded mode”: FCC remains cold, vacuum preserved, controls on, RF off, no beam (“standby”); all FCC points supplied from 2 other 400 kV points, through the power transmission line



3 x 400 kV connections  
+ 135 kV underground power distribution (NC)





# FCC-ee physics program staging


working point	luminosity/IP [ $10^{34} \text{ cm}^{-2}\text{s}^{-1}$ ]	total luminosity (2 IPs)/ yr	physics goal	run time [years]
<b>Z first 2 years</b>	100 (50% nominal)	26 $\text{ab}^{-1}/\text{year}$	<b>150 <math>\text{ab}^{-1}</math></b>	<b>4</b>
<b>Z later</b>	200	48 $\text{ab}^{-1}/\text{year}$		
<b>W</b>	25	6 $\text{ab}^{-1}/\text{year}$	<b>10 <math>\text{ab}^{-1}</math></b>	<b>2</b>
<b>H</b>	7.0	1.7 $\text{ab}^{-1}/\text{year}$	<b>5 <math>\text{ab}^{-1}</math></b>	<b>3</b>
machine modification for RF installation & rearrangement: <b>1 year</b>				
<b>top 1st year (350 GeV)</b>	0.8 (50% nominal)	0.2 $\text{ab}^{-1}/\text{year}$	<b>0.2 <math>\text{ab}^{-1}</math></b>	<b>1</b>
<b>top later (365 GeV)</b>	1.4	0.34 $\text{ab}^{-1}/\text{year}$	<b>1.5 <math>\text{ab}^{-1}</math></b>	<b>4</b>

**total program duration: 15 years** - *including machine modifications*

**phase 1 (Z, W, H): 9 years,**    **phase 2 (top): 6 years**



# FCC roadmap towards stage 1






# FCC key deliverables: prototypes by 2025

## FCC-ee complete arc half-cell mock up


including girder, vacuum system with antechamber + pumps, dipole, quadrupole + sext. magnets, BPMs, cooling + alignment systems, technical infrastructure interfaces.



## key beam diagnostics elements

bunch-by-bunch turn-by-turn **longitudinal charge density profiles** based on electro-optical spectral decoding (beam tests at KIT/KARA) ;

**ultra-low emittance measurement** (X-ray interferometer tests at SuperKEKB, ALBA) ;  
**beam-loss monitors** (IJCLab/KEK?) ;  
**beamstrahlung monitor** (KEK);  
**polarimeter ; luminometer**



# FCC key deliverables: prototypes by 2025




400 MHz SRF cryomodule,  
+ prototype multi-cell cavities  
for FCC ZH operation  
High-efficiency RF power sources

positron capture linac  
large aperture S-band linac


- Freq : 2.856 GHz
- 90 cells per structure
- Length: 3.254 m
- Distance between two TWs: 45 cm
- Gradient: 20 MV/m
- Aperture: 30 mm



high-yield positron source  
target with DC SC solenoid or flux  
concentrator





beam test of  $e^+$  source & capture linac  
at SwissFEL – yield measurement



strong support from Switzerland via CHART II program 2019 – 2024 for  
FCC-ee injector, HFM, beam optics developments, geology and geodesy activities.



# US – MDP: 14.5 T magnet tested at FNAL





- 15 T dipole demonstrator
- Staged approach: In first step pre-stressed for 14 T
- Second test in June 2019 with additional pre-stress reached 14.5 T



# Implementation studies with host states

- Classification of zones along/around the perimeter of FCC according to „realisation risk levels“ defined with host states.
- Study of variants following the approach „Avoid – Reduce – Compensate“

## Territorial constraints – Canton Geneva





# Feasibility Study of FCC integrated project

**Feasibility study to be delivered end 2025** as input for next ESPP Update expected by 2026/2027, to enable a project decision:

- *feasibility study of the 100 km tunnel (infrastructure aspects, administrative aspects, local authorities, environment, energy, etc.)*
- *high-risk areas site investigations included, to confirm principle feasibility*
- *host-state related processes, to allow start of construction early 2030ies.*
- *CDR+ for colliders and injectors, including key technology proofs.*
- *HFM program intermediate milestones, in line with long-term R&D plan.*
- *physics and experiments CDR + for FCC integrated project.*
- *financing concept & organization model for project and operation phases.*
- *for all these activities sequential nature of implementation and overall timeline need to be taken into account !*