



CompactLight Prototype Structures

I.Fast 2nd annual meeting

Pedro Morales Sanchez - CERN

Contents


- CompactLight + iFAST
- iFAST prototype on going
 - Design
 - Mock-Up
 - Prototype
- Conclusion



Contents

- CompactLight + iFAST
- iFAST prototype on going
 - Design
 - Mock-Up
 - Prototype
- Conclusion

CompactLight + iFAST




Objective of CompactLight: “The project aims at making X-ray FELs small and inexpensive enough to be within national and even university scale, yet with uncompromised scientific potential”.

Focus on Cost, Power consumption and Footprint.

EU Founded H2020 collaboration among 26 institutions


CompactLight + iFAST




10 MW, 1.5 μ s, @1 KHz

50 MW, 1.5 μ s, @100 Hz

CompactLight + iFAST



Parameter	Unit	Dual mode		Dual source	
Operating Mode		B		U1, U2	
Repetition rate	kHz	0.1	0.25	0.1	1
Linac active length	m			94	
Number of structures				104	
Number of modules				26	
Number of klystrons			26	26 + 26	
Peak acc. gradient	MV/m	65	32	65	30.4
Energy gain per module	MeV	234	115	234	109
Max. energy gain	MeV	6084	2990	6084	2834






10 MW, 1.5 μ s, @1 KHz

50 MW, 1.5 μ s, @100 Hz

CompactLight + iFAST

Parameter	Units	Value		
Frequency	GHz	11.994		
Peak klystron power (100 - 250 Hz)	MW	50		
Peak klystron power (1000 Hz)	MW	10		
RF pulse length (250 Hz)	μ s	1.5 (0.15)		
Waveguide power attenuation	%	≈ 10		
Average iris radius a	mm	3.5		
Iris radius a	mm	4.3-2.7		
Iris thickness t	mm	2.0-2.24		
Structure length L_s	m	0.9		
Unloaded SLED Q-factor Q_0		180000		
External SLED Q-factor Q_E		23300		
Shunt impedance R	M Ω /m	85-111		
Peak modified Poynting vector	W/ μ m ²	3.4		
Group velocity v_g/c	%	4.7-0.9		
Filling time t_f	ns	146		
Repetition rate	Hz	100	250	1000
SLED		ON	OFF	ON
Required klystron power	MW	44	44	9
Average accelerating gradient	MV/m	65	30	30



Courtesy M. Diomedè

CompactLight + iFAST

Objectives: “iFAST aims to enhance innovation in the particle accelerator community,[...]These include, among others, new accelerator designs and concepts, advanced superconducting technologies for magnets and cavities, techniques to increase brightness of synchrotron light sources, strategies and technology to improve energy efficiency, and new societal applications of accelerators”.

Quick links

- WP1: Management
- WP2: Communication
- WP3: Industry engagement
- WP4: Innovation, materials
- WP5: R&D strategies
- WP6: Novel concepts
- WP7: Light sources**
- WP8: Magnets
- WP9: Cavities
- WP10: Technologies
- WP11: Sustainability
- WP12: Applications
- WP13: Technology infrastructure
- WP14: Ethics requirements

WP7: High brightness accelerators for light sources

Objectives

- Organise workshops on the technology enabling the design and construction of future ultra-low emittance rings
- Specify and design magnetically and mechanically a longitudinal variable field dipole magnet with transverse gradient, adapted to the ELETTRA storage ring upgrade, for reducing further the horizontal emittance
- Design of two different C-band (5.712 GHz) RF electron guns operating at very high gradient cathode peak field
- Build and test, at low and high RF power, two prototypes at different TRL of the X-band (12 GHz) accelerating structure designed for the CompactLight (XLS) project

Tasks

Task	Name	Task Leader
7.1	Coordination and communication	R. Bartolini (DESY)
7.2	Enabling technologies for ultra-low emittance rings	A. Mochihashi (KIT)
7.3	Variable Dipole for the upgrade of the ELETTRA storage ring	Y. Papaphilippou (CERN)
7.4	Very high gradient RF Guns operating in the C-band RF technology	D. Alesini (INFN)
7.5	CompactLight Prototype Accelerating Structures	G. D'Auria (Elettra)

CompactLight + iFAST

Task 7.5: CompactLight accelerating structure prototype

Objective: Build and test, at low and high RF power, two prototypes of the X-band (12 GHz) accelerating structure designed for the CompactLight project.

Two deliverables:

- **D7.5: Construction of the XLS accelerating structure pre-prototype.**







Development of production process and RF tests of the pre-prototype (@TRL 6/7)_ Dec23

- **D7.6: Construction of the XLS accelerating structure full prototype.**

Production process analysis and validation, RF tests of the full prototype (@TRL 7)_Apr25

CompactLight + iFAST

Task 7.5 Partners

ELETTRA-ST	CERN	INFN	VDL-ETG	COMEB	TMD
 Elettra Sincrotrone Trieste		 Istituto Nazionale di Fisica Nucleare			
<ul style="list-style-type: none">- General coordination	<ul style="list-style-type: none">- Consultancy- Metrology verification- RF measurements at low and high power	<ul style="list-style-type: none">- Electro- magnetic design of the structure- RF measurements at low and high power	<ul style="list-style-type: none">- Fabrication of cells and couplers	<ul style="list-style-type: none">- Fabrication of cells and couplers	<ul style="list-style-type: none">- Brazing

Contents


- CompactLight + iFAST
- iFAST prototype on going
 - Design
 - Mock-Up
 - Prototype
- Conclusion



iFAST prototype on going - Design

Thermo-mechanical simulations

- Optimization of the cooling geometry
- Iteration with RF on the deformation
- Choice for 4 cooling channels with a diameter of 6 mm (similar to CLIC)
- Cooling channels slightly asymmetrical to match the RF couplers





Courtesy M. van den Berg

iFAST prototype on going - Design



RF accelerating structure



RF Structure
Input – Output RF couplers

Contents

- CompactLight + iFAST
- iFAST prototype on going
 - Design
 - Mock-Up
 - Prototype
- Conclusion



iFAST prototype on going – Mock-up




Courtesy COMEB

Test:

- Machinability
- Interlocking alignment
- Brazing material
- Leak tightness






3 cells tall mock-up




10 cells tall mock-up

iFAST prototype on going – Mock-up




iFAST prototype on going – Mock-up


- 35um



Nice metrology



iFAST prototype on going – Mock-up



Courtesy TMD

Aiming to test the procedure feasibility to do the interlocking shrink fit.


New issue found using the designed jigs and now this is being corrected.

Next try for assembly 21st April for 3 cell tall and second trail for next 3rd May.


Contents

- CompactLight + iFAST
- iFAST prototype on going
 - Design
 - Mock-Up
 - Prototype
- Conclusion

iFAST prototype on going – Prototype



Machining progressing for the first prototype at VDL



Contents

- CompactLight + iFAST
- iFAST prototype on going
 - Design
 - Mock-Up
 - Prototype
- Conclusion



Conclusions

- The work from CompactLight to develop cost-efficient and versatile X-Band linac has been a success story. We have been able to benefit from this in iFAST project.
- There is a good trend into the institutions and industry to further develop the works in X-Band.
- Despite the delay we have faced on the Mock-up we are catching up doing parallel working thanks to the effort of the whole team with an special mention to VDL.

iFAST

Thank you for your attention

References:

<http://www.compactlight.eu/Main/Publications>

[Home](http://www.compactlight.eu) | [IFAST \(ifast-project.eu\)](http://ifast-project.eu)

Thanks Gerardo for the opportunity giving and building this presentation



This project has received funding from the European Union's Horizon 2020 Research and Innovation programme under GA No 101004730.