

PAUL SCHERRER INSTITUT



FUTURE
CIRCULAR
COLLIDER



Paolo Craievich (PSI) on behalf of the CHART/FCCee Injector design collaboration

The FCCee (Pre-)Injector Complex


(Diagnostic requirements based on the SwissFEL linac)

1st FCCee Beam Instrumentation Workshop FCC Week, CERN, 21 and 22 November 2022


- **Injector specification**
- **Injector layout**
 - ❖ Electron source, Common linac, Positron source, Damping ring
- **General requirements (for diagnostics)**
 - ❖ Specifications for diagnostic components
 - ❖ Machine protection system
- **Diagnostics for the PSI Positron Source (P³) project**
- **Conclusion**

Where are we in FCC-ee?


Electron-Positron collider
~91 km



Option 1 (with SPS/PBR)



Option 2 (HE Linac)



Injector parameters (Z-mode)

FCC Accelerator Pillar meeting #07, 01.11.22

	CDRO	HE Linac	Unit
Ring for injection	SPS/PBR	BR	
Injection energy	6	20	GeV
Bunch charge (max)	4 (5)		nC
Repetition rate	200		Hz
Number of bunches	2		
Bunch spacing	17.5-25		ns
Normalized emittance (x, y) (rms)	10, 10		mm.mrad
Bunch length (rms)	~1		mm
Energy spread (rms)	<0.1		%
Bunches/beam	~10000		


Other important requests:

- The bunch by bunch intensity will **randomly vary 0 (?) to 100%**, depending on the intensity balance between the collider rings
- **Bunch-by-bunch injection intensity fluctuation: 3%**

Filling pattern for the Z-mode (an attempt)


Sketch based on the proposal by K. Oide (FCC Accelerator Pillar meeting #07, 01.11.22)

Option 2 (with high-energy linac)



- Total filling time from scratch for the Z-mode 245.7 s for each species
- Collider filling time for top-up 27.3 s
- Luminosity lifetime 479 s (4 IP)
- Collider top-up interval (between e+ and e-)(4 IP) 24 s


In this phase changing bunches/train can meet the specifications



— Injector is split in WPs:


- WP1: Electron source, e-linac (2.8 GHz, 200 Hz), common linac (2.8 GHz, 400 Hz), e+Linac (2.0 GHz, 200 Hz), High Energy Linac (2.8 or 5.6 GHz, 200 Hz)
- WP3: Positron generation and capture (2-bunches, 25 ns, 200 Hz)
- WP4: DR and transfer lines (Energy Compressor, DR, Transfer line, Bunch Compressor)

— Outstanding question for the layout: is the DR also necessary for electron bunches?




- **Electron source:** an injector based on a photocathode RF gun can provide electrons for both ring injection and positron production
- **First conceptual design of a photo-injector exists, very good emittance can be achieved even at higher charge**
 - ❖ DR for electron bunches can be avoided
- **Electron source, preliminary:** shorter bunch length is possible 1.3 mm → 0.65mm
- **The 100% amplitude modulation of the electron and positron charge required for injection into the collider ring could be provided from an optical modulator in the laser system – under investigation**

Electron source




Common linac: repetition rate 1



Common linac: repetition rate 2

2+2 pulses in the same rf bucket




- Baseline: Common linac at 400 Hz, 200 Hz (electrons) + 200 Hz (positrons) when positron are generated
 - Challenging for the RF systems (HV mods and klystrons). Klystron at 400 Hz from CETD could be feasible. HV modulators under development for other projects.
- DR has to provide a delay of 2.5 ms (more complicate timing) to allocate the positron bunches on the on the right rf bucket

Positron source


Positron yield up to 7 (Y. Zhao FCC week 2022)

Conventional scheme (baseline for FCCee)





Schematic of FCC-ee Injector Complex


- Target
- Adiabatic Matching Device
- 10 RF Cavities surrounded by solenoids



Hybrid scheme




FC used as AMD



HTS solenoid used as MD

Damping ring

Parameters from the WP4 - Damping ring and transfer lines meeting on 11.11.22



Required Parameters	
Energy [GeV]	1.54
Circumference [m]	\sim 250 m
Stored time [ms]	40
Damping time (hor.) [ms]	\approx 10
Extraction geo. emittance (hor.) [nm.rad]	\approx 5
Number of bunches	16
Energy spread @ extraction [%] (rms.)	-
Injection type	on axis
Number of straight sections	3
Injected Parameters	
Injected emittance (h) (e-/e+) [nm.rad/ μ m.rad]	5.5/1.29
Injected emittance (v) (e-/e+) [nm.rad/ μ m.rad]	6/1.22
Injected momentum spread [%] (e-/e+) (rms.)	0.2/5
Injected bunch length (e-/e+) (mm)	1/3.4

\sim 5 ms

\sim 1.7 nm.rad

more

Parameters	CDR	After CDR	New
Bending magnet quantity*	232	232	72
Dipole magnet length [m]	0.21	0.21	0.28
Bending angle [degree]	1.55	1.55	5
Dipole magnetic field [T]	0.66	0.66	1.8
Filling factor	0.2	0.2	0.07
Damping wiggler magnet	26.5 m / 1.8 T	68 m / 1.8 T	18 m / 2 T
Robinson wiggler magnet	-	-	3.8 m / 1.2 T
Circumference	242 m	240 m	257.31 m
Emittance	2 nm.rad	1.25 nm.rad	4.89 nm.rad
Damping time	10.5 ms	5.9 ms	6 ms
Energy loss per turn	0.253 MeV	0.47 MeV	0.253 MeV

- The concepts for the DR and the return transfer line are still working in progress (specification are still changing...)
- RF systems to be decided (most likely 400 MHz)
- Positron bunch has higher emittance and energy spread \rightarrow DR acceptance has to be verified

General requirements (for diagnostics)

Based on the experiences in SwissFEL at PSI

– Role for FCCee Pre-Injector Diagnostics:


- Allows for successful commissioning of the electron source, linacs, positron source and DR
- Fast and reliable set-up of the machine for operation (filling pattern and top-up for different collider operational modes)
- Monitor possible drifts (non-invasive) for feedback systems

– How much diagnostics?

- Avoid operating the different injector sections blindly
- Decoupling of machine sections (in accordance with piece-wise commissioning of the injector)
- Reducing the impact of model-derived assumptions (beam parameters derived from simulation)

Balance between Instrumentation and Costs

Injector Layout & Diagnostic locations



For commissioning and daily operation a beam diagnostics for the following parameters are required (16 bunches, 4 nC per bucket, 80 mA):


- transverse emittance and energy spread (emittance and energy spread monitors)
- charge and charge loss (beam loss monitor)
- beam size and position (BPM)
- beam current and filling pattern
- bunch length (streak camera)

Transfer line Diagnostics:

- BPMs and optical screens


→ To be defined the requirements in term of minimum beam size, resolutions, field of view

- Resolution of 5 μm (?)
- 200 Hz Readout of the 2 bunches
- Charge range 0(?) - 5 nC per bunch
- Valid Range +/- 1 mm (just a number here, to be defined from the trajectory jitter studies)
- It has to resolve both bunches




SwissFEL Cavity BPM, low Q, bunch spacing 28 ns, 100 Hz (Ref. F. Marcellini and B. Keil)

- Transverse Profile Screens (Destructive, assume 100% losses):
 - Typical beam sizes
 - β : 5-100m, ε_n : 1-5 mm mrad, E: 0.2 – 6 – 20 GeV \rightarrow σ : 25-1100 μm
 - Avoid unnecessary losses \rightarrow beam synchronous acquisition
 - Long term insertion of screen with low rep rate



Test of different cameras, different scintillators and imaging geometries




- Compression & de-compression (energy compression) monitors
 - Compression: from ~ 20 ps to ~ 3 ps
 - De-compression (energy compression): to be studied
 - Dynamic range:
 - Expected range of bunch lengths for commissioning/tuning
- Bunch Compression Monitor
 - Relative measurement with CSR at some bending magnets
 - Locked (Calibrated) with Bunch Profile Measurements?
 - Needed for Feedback, it has to resolve both bunches in main linac

— Bunch Profile Measurements:


- Streaking Bunch Profile with TDS
- Location:
 - After electron linac and after Common linac
 - After positron linac?
- Resolution: ~ 200 fs at 6 GeV – challenging 20 GeV

— Arrival time

- Needed for feedbacks
 - Non-destructive
 - Resolves both bunches
 - Resolution: 50-200 fs (to be studied)
- Injector: Measurement of electron beam and gun laser (LAM) to separate laser drift and phase drifts in the injector



- Energy Measurement
 - BPMs in dispersive dominated location (e.g. bunch compressors, transfer lines)
 - Resolution: to be defined (i.e. $<1e-4$ for dispersion of 0.1 m and higher)
 - Needed for Feedback, measurement of both bunches
 - Cross-check with Spectrometer dumps (Gun, Injector, BC, Common linac etc..)
- Energy Spread Measurement
 - Incoherent SR port in dispersive section
 - Needed for Feedback 200 Hz, resolving 2 bunches



- Most of the time the machine will run in user operation with the needs to monitor important beam parameters and apply feedback to it:
 - Orbit, Compression, Energy, Energy spread, Charge, Transmission, Emittance, Matching, Arrival Time
- DR: fast orbit feedback system, transverse and longitudinal multi-bunch and fill pattern feedback

Beam power levels

Location	Beam parameters	Beam power
Injector/e-linac/e+linac	200 Hz, 5 nC, 1.54 GeV	2 x 1.54 kW = 3.08 kW
Common linac/positron source	200 Hz, 5nC, 6 GeV	2 x 6 kW = 12 kW
HE linac/trasfer lines	200 Hz, 5 nC, 20 GeV	2 x 20 kW = 40 kW



The following systems will be used to detect an improper state of the machine:

- Beam modes
- Differential charge monitoring
- Beam loss monitoring
- Monitoring of average beam current
- Radiation dose monitoring

Beam loss monitor


- Redundant Cherenkov fibers along the entire machine
- Scintillating fibers

→ Protection of the machine from radiation!
This is NOT a personal safety system




What we want to validate with the experiment

- ✓ Positron Yield (simulation showed > 5) with conventional scheme (simulation vs measurement)
- ✓ AMD: SC Solenoid with HTS technology including mech. and thermal (cryostat) concept
- ✓ RF structures: large iris aperture
- ✓ Diagnostics for positron bunches (cloud)
- ✓ Phase 2: hydride scheme with crystal




- Very broadband pickups (bandwidth > 40 GHz) can measure the time structure of the beam
- e+ and e- buckets are separated by 167 ps
- Based on SuperKEKB diagnostic


Development of fast BPM (summer student project), based on T. Suwada et al., Sci Rep 11, 12751 (2021)





Time structure of the beam



Simulated signal at BBPs (E. Ismaili)




- Measurement of e^+ and e^- charge separately
- 2 parallel 25 Ohm connectors each
- Negligible backscattering




Optimized dimensions of diagnostics chamber.

- Dipole strength scanned to measure e^+ energy profile
- e^+ at different p_z detected by narrow screen
- Technology of the detector under investigation (we are planning to test a scintillating fiber).



Schematic of energy spectrum measurement



- The pre-injector is still in the design phase and there are still some outstanding questions to be addressed
- Some specifications of the pre-injector were frozen in view of the next year mid-term cost review (second half 2023)
- As deliverable for the review, we must provide a cost estimate for the injector. So, after the design phase we must start with a cost model for the different part of the injector (including diagnostics)!
- The type and technology for diagnostics fairly defined based on the experiences of SwissFEL (2-bunches, smaller charge), BUT the number of components and their specifications still to be defined
- PSI Positron production (P³) project
 - ❖ Some key diagnostics for the positron source will be tested, broadband pickups, energy spread and charge measurements

PSI: R. Zennaro, M. Schaer, N. Vallis, B. Auchmann, I. Besana, S. Bettoni, H. Braun, M. Duda, D. Hauenstein, E. Hohmann R. Ischebeck, P. Juranic, J. Kosse, G. L. Orlandi, M. Pedrozzi, J.-Y. Raguin, S. Reiche, S. Sanfilippo, all the technical groups involved in the P³ experiment

IJCLab: I. Chaikovska, F. Alharthi, V. Mytrochenko, R. Chehab

CERN: A. Grudiev, W. Bartmann, M. Benedikt, T. Brezina, M. Calviani, S. Doebert, Y. Duthell, O. Etisken, J.L. Grenard, B. Humann, A. Latina, A. Lechner, A. Marcone, H. Pommerenke R. Ramjiawan, Y. Zhao,, R. Mena Andrade, Z. Vostrel, F. Zimmermann

SLAC T. Rauberheimen

INFN-LNF: C. Milardi, A. De Santis, O. Etisken

KEK: K. Oide, Y. Enomoto, K. Furukawa




This work was done under the auspices of CHART (Swiss Accelerator Research and Technology) Collaboration, <https://chart.ch> - **CHART Scientific Report 2021**: <https://chart.ch/reports/>


Backup slides

What we want to validate with the experiment

- ✓ Positron Yield > 3 (simulation showed > 5) with conventional scheme (simulation vs measurement)
- ✓ AMD: SC Solenoid with HTS technology including mech. and thermal (cryostat) concept
- ✓ RF structures: large iris aperture
- ✓ NC versus SC solenoids around the rf structures
- ✓ Phase 2: hydride scheme with crystal




...but repetition rate only 200pC at 1 Hz (due to radiation losses) and the dissipated power on the target less than in the FCC target (~W against few kW)




*HTS demonstrator at PSI
(M. Duda et al.)*

- HTS demonstrator developed at PSI (left)
 - 4 ReBCO tape coils at 2kA
 - Operation at 18.2 T, on-axis peak
 - Temperature 20 – 30 K, no need of He cooling
 - Quench self-protected
- Technical design of cryostat for P³ in development at PSI (right)
- CW operation, ramp-up time of magnetic field ~ 2 days




*Preliminary model of the AMD for P³
(H. Garcia Rodriguez)*

Energy (capt. LINAC)	197.8 MeV
e+ capture (capt. LINAC)	75 %
emittance (capt. LINAC)	≈ 15000 pi mm mrad
Energy spread (c. LINAC)	≈ 50 MeV
AMD max field	12.54 T
Solenoid strength	1.5 T
Decelerating mode	Yes
Yield	7.86



Collaboration between PSI and CERN with external partners:

CNRS-IJCLab (Orsay), INFN-LNF (Frascati), SuperKEKB as observer (also interested in the P³ project), INFN-Ferrara – radiation from crystal





- **CHART (Swiss Accelerator Research and Technology): umbrella collaboration for accelerator research and technology activities in Switzerland**
- **The mission is to support the future oriented accelerator project FCC at CERN and development of accelerator concepts beyond the existing technology**

- **The activities are focused on the support of the FCC project. I.e. High-field magnet R&D complemented by beam dynamics studies for FCC-ee, FCC-hh and FCC-ee Injector and positron production test facility**

→ CHART is contributing to the FCC Feasibility Study to be delivered in 2025