

The CONUS+ experiment

On behalf of the CONUS+ Collaboration





Edgar Sánchez García
(MPIK)



Magnificent CEvNS (Munich), March 2023

The CONUS experiment

- CONUS detector operated in Brokdorf nuclear power plant (Germany) from 2018 to 2022.
- It provides best CEvNS limit at reactor up to date:
Factor 2 over SM prediction with $k=0.162\pm 0.004$.
- W. Maneschg talk on Wednesday for more details.
- However, the Brokdorf nuclear power plant stopped its operation at the end of 2021 ...



The CONUS+ experiment

CONUS+ is going to be installed in the Leibstadt nuclear power plant (KKL) in Switzerland during summer 2023.



Experimental conditions:

- 20.7 m from 3.6 GWth reactor core → high antineutrino flux expected $1.45 \times 10^{13} \bar{\nu}_e \text{ s}^{-1} \text{ cm}^{-2}$.
- High duty-cycle: 1 month/year of reactor-off.
- Shallow-depth site (7-8 m w.e.).

CONUS+ Collaboration



Max Planck Institut für Kernphysik (MPIK)



N. Ackermann, S. Armbruster, H. Bonet, A. Bonhomme, C. Buck, J. Hakenmüller, J. Hempfling, G. Heusser, M. Lindner, W. Maneschg, K. Ni, T. Rink, E. Sanchez Garcia and H. Strecker

Preussen Elektra GmbH, Kernkraftwerk Brokdorf (KBR)

K. Fülber and R. Wink






Leibstadt AG , Kernkraftwerk Leibstadt (KKL)

J. Woenckhaus


CONUS+ background: γ 's

- Ultra-low background p-type coaxial HPGe detector CONRAD (m =2.2 kg). Electrical cryocooling system.
- Scan over different positions with measurement from few hours to one day.
- High energy gamma contribution (>2.7 MeV) factor 25 smaller than at Brokdorf power plant. Stronger contribution of ^{60}Co lines.



CONUS+ background: Cosmic muons



- Liquid scintillator cell filled with 120 ml of “Ultima Gold”. PMT for light detection.
- Measurements at MPIK and KKL for comparison.
- Quality cuts applied: saturation, pile-up.
- Pulse shape discrimination cut to remove neutrons.



- Energy cut at 10 MeV to avoid environmental radioactivity and high energy gamma contribution.
- Muon rate outside: 0.121 Hz.
- Muon rate in KKL: 0.058 Hz.
- Reduction factor of 2.1 in KKL compare to surface → overburden ~7-8 m.w.e.
- Muon rate factor 2.2 larger than at KBR.

CONUS+ background: Radon



- Monitoring of the radon level in the room during one month.
- Radon concentration value of $194 \pm 2 \text{ Bq/m}^3$.
- It is needed to reduce the concentration to at least 1 Bq/m^3 inside the detector chamber.



- Detector chamber flushed with radon free air from a radon filtering system.
- Five 7 kg activated charcoal columns for radon reduction factor > 300.
- Pressurized dry air (<1 %) line from outside containment area with lower radon content.
- Stand-alone system. Robust and simple to reduce maintenance operations.



CONUS+ background: Neutrons

- Neutron spectrometry with Bonner Sphere detectors in scientific cooperation with PSI.
- Monitoring of thermal and fast neutrons during whole measurement campaign. Neutron flux stable within 3%.
- Same configuration of spheres as in KBR for direct comparison giving a sensitivity from 10^{-9} to 10^3 MeV
- Neutron flux ~ 30 times larger than in KBR. However, it is still a subdominant contribution of the background in the region of interest.



Neutron correlation with thermal power


- Reactor-correlated backgrounds are critical for CONUS since they can mimic a CEvNS signal.
- Monitoring of neutron rate with 5" PE sphere to study correlation with thermal power.



- Good agreement with devices placed close to the fuel elements.
- As expected, the signal is dominated by the neutrons coming from the reactor. Small contribution from cosmic neutrons.

CONUS+ detector


- 4 p-type point contact HPGe with total crystal/active mass: 4 kg /3.74kg as target.
- Active + passive shielding: low ^{210}Pb lead, borated and pure PE and 2 active μ -vetos (plastic scintillator).
- Apply muon veto offline. New DAQ for veto system. Energy deposited stored for each PMT.
- Radon filtering system will provide radon free-air for inner volume flushing.
- Specific space dedicated for CONUS+ with AC for temperature control.
- Network connection to outside containment area. Real-time monitoring and slow control of the experiment.



Upgraded germanium detectors

CONUS Ge detectors refurbished for CONUS+



- Point-contact size reduced and new ASIC electronics.
- Water instead of fans for cryocooler cooling → reduce vibrations and environmental dependence.
- Pulser resolution (FWHM) < 55eVee.
- Improved trigger efficiency. Preliminary tests at MPIK show that a threshold lower than 200 eV is achievable.



New veto system

- The high energetic gamma flux is expected to be lower in KKL. However, amount of overburden will be smaller and consequently the muon rate will be larger.
- For this reason, the CONUS shield will be modified for CONUS+. One of the inner lead layers of will be replaced by a second plastic scintillator muon veto.
- 9 plates of EJ-200 plastic scintillator + 20 low background PMTs to minimize material contamination.
- Coincidences of different scintillator plates will reduce the impact of high energy gammas for the veto rejection efficiency.
- Goal: muon rejection efficiency over 99%.



Lead




New veto system

- The high energetic gamma flux is expected to be lower in KKL. However, amount of overburden will be smaller and consequently the muon rate will be larger.
- For this reason, the CONUS shield will be modified for CONUS+. One of the inner lead layers will be replaced by a second plastic scintillator muon veto.
- 9 plates of EJ-200 plastic scintillator + 20 low background PMTs to minimize material contamination.
- Coincidences of different scintillator plates will reduce the impact of high energy gammas for the veto rejection efficiency.
- Goal: muon rejection efficiency over 99%.

Plastic scintillator



Physics potential



- The energy threshold is a crucial parameter for CEvNS detection. Assuming a trigger efficiency of 50% at 100 eV, improving the threshold from 230 to 140 eV, the number of signal events will increase roughly by a factor ~ 7 .

Summary



- CONUS+ is a follow-up experiment which aims to detect CEvNS for the first time from a reactor.
- It will be installed in Leibstadt power plant (Switzerland) in summer 2023 at 20 m from the reactor core.
- For this purpose, the 4 Ge detectors of CONUS were upgraded, reducing the threshold under 200 eV.
- Additional plastic scintillator layer to increase muon rejection efficiency.
- The new experimental location background was fully characterized with a HPGe detector, a Bonner Sphere array and a liquid scintillator cell.

Thank you for your attention



TSLSD detector

- Technical Scale Liquid scintillator Detector (TSLSD) for muon and neutron and background characterization.
- Different option for filling adapted to safety specifications. Possibility to fill with silicon oil as scintillator base: no hazard symbol, low vapor pressure and flash point very high (300°C). Volume 17 L.
- Certified safety box for transport and operation.
- Muon energy deposition 50-120 MeV.



Comparison KKL vs KBR for gammas

Time exposure: 24.0 h

