

The Effects of a Passive Bi-Polar Grid on Ion Back Flow & Resolution

Friday 16 December 2022 10:20 (20 minutes)

Time Projection Chamber (TPC) tracking detectors measure 3D space points of charged particles to give position, dE/dx & Particle Identification (PID). The gain stages create large amounts of Ion Back Flow (IBF), which is the dominant source of space charge & distorts the drift E -field, and thus resolution. IBF can be reduced by manipulating field ratios above and below the gain structure to absorb the ions. However, higher ratios towards the bottom cause gain fluctuations, lowering resolution. A passive structure can be considered as an alternative. A Bi-Polar Grid (BPG) can block practically all ions by simply absorbing them on the negative wires. Avoiding electron loss on the positive wires can be done either with an active grid, losing luminosity, or passively with a B -field exploiting that $F = qv \times B$ will provide a "kick" to the electrons while the heavier ions aren't affected. Our DOI: 10.1109/TNS.2020.3042311 IEEE paper shows that as voltage between the BPG increases, all ion transparency goes zero while electrons maintain 30%-80% transparency depending on the gas, source strength, etc. The sPhenix TPC for BNL, with a quad-GEM stack, uses unique zig-zag shaped radial pads, with DNL corrections. The BPG's effect on resolution was studied with linear & equidistant wires, regardless of the pad position, & with radial wires aligned with each pad. A prototype TPC, with ≈ 40 cm drift length and ≈ 43 cm diameter, will have been studied at ANL using their 4T MRI magnet. I'll present both BPG experiments with IBF results from our paper, and resolution results.

Presenter: ZAKHAROV, Vladislav

Session Classification: Session 12