Contribution ID: 64

Type: Oral

## Longevity studies for the CMS Resiste Plate Chambers for HL-LHC phase

Wednesday 8 November 2023 11:50 (25 minutes)

The present Compact Muon Solenoid (CMS) Resistive Plate Chambers (RPC) system has been certified for 10 years of Large Hadron Collider (LHC) operation at a maximum background rate of 300 Hz/cm<sup>2</sup> and integrated charge of 50 mC/cm<sup>2</sup>. In the next years, during the Phase 2 of the LHC physics program, called High Luminosity LHC (HL-LHC), the accelerator will increase the instantaneous luminosity up to factor five more than the nominal LHC luminosity, providing to experiments an additional integrated luminosity of about 3000 fb<sup>-1</sup> over 10 years of operation. At the HL-LHC phase, the expected rate and integrated charge are about 600 Hz/cm<sup>2</sup> and 840 mC/cm<sup>2</sup>, respectively (including a safety factor of three) based on Run 2 data and assuming a linear dependence of the background rates as a function of the instantaneous luminosity. A longevity test is then needed to estimate the impact of HL-LHC conditions on the RPC detector performance in order to confirm that the RPC system will survive the harsher background conditions expected at HL-LHC. A dedicated long term irradiation program has been started at CERN Gamma Irradiation Facility (GIF++) since 2016, where few RPC detectors are exposed to intense gamma radiation for long term to mimic the HL-LHC operational conditions. The main detector parameters (currents, rate, resistivity) are continuously under monitoring as a function of the collected integrated charge and the detector performance has been studied with muon beams. The latest results of the irradiation test will be presented.

Author: BARROSO FERREIRA FILHO, Mapse (Universidade do Estado do Rio de Janeiro (BR))
Presenter: BARROSO FERREIRA FILHO, Mapse (Universidade do Estado do Rio de Janeiro (BR))
Session Classification: Longevity studies