



HIGHLIGHTS FROM 6TH FCC PHYSICS WORKSHOP -- MDI PERSPECTIVE --

Manuela Boscolo (INFN-LNF)

MDI meeting #43 zoom, 6 February 2023






NFN

6th FCC Physics Workshop Program

23-27 January, Krakow, Poland

https://indico.cern.ch/event/1176398/

Scientific Programme Committee Patrizia Azzi (INFN Padua) Alain Blondel (Paris-Sorbonne, co-chair) Gregorio Bernardi (APC Paris) Manuela Boscolo (INFN Frascati) Mogens Dam (NBI Copenhagen) Gerardo Ganis (CERN) Christophe Grojean (DESY/Berlin) Clement Helsens (CERN) Patrick Janot (CERN) Jacqueline Keintzel (CERN) Michelangelo Mangano (CERN) Matthew Mccullough (CERN) Emmanuel Perez (CERN) Philipp Roloff (CERN) Felix Sefkow (DESY) Frank Simon (KIT) Mike Sullivan (SLAC) Jörg Wenninger (CERN) Guy Wilkinson (Oxford)



○ FCC

Agenda MDI sessions

Tuesday 24/1 (MDI/Detector Joint)					
Mechanical model of the FCC-ee MDI	Francesco Fransesini (INFN-LNF)				
Detectors integration in the MDI area	Franco Bedeschi (INFN-Pisa)				
Status and Perspectives for FCC-ee Detector Backgrounds Studies	Andrea Ciarma (CERN)				
FCC-hh detector concept	Anna Zaborowska (CERN)				

Wednesday 25/1					
Summary of review for FCC Experimental sites	Mogens Dam (NBI)				
Lesson learnt from CMS IR mock-ups	Andrea Gaddi (CERN)				
IR beam losses	Andrey Abramov (CERN)				
FCC-ee synchrotron radiation collimators and masks	Kevin Andre (CERN)				
Detector Stray Magnetic Fields	Nikkie Deelen (CERN)				





Goals of the Workshop

- **Get together in person for the 1st time in three years**
 - 3rd FCC physics workshop: <u>13-17 Jan 2020</u>
 - In person at CERN
 - ♦ 4th FCC physics workshop : <u>10-13 Nov 2020</u>
 - Remote only
 - ♦ 5th FCC physics workshop : <u>7-11 Feb 2022</u>
 - Foreseen to be in person (Liverpool), became remote only
 - ♦ 6th FCC physics workshop: <u>23-27 Jan 2023</u>
 - In person in Krakow
 - ➔ First in-person physics workshop in the FCC FS era
 - 190 participants of which 75-80 in person
- Strengthen the Physics/Experiments/Detector community
 - Share experience with newcomers
 - Synergy with Snowmass and ECFA Workshops





5




5



Goals of the Workshop

- Monitor the PED progress since the beginning of the FCC Feasibility Study
 - Physics Programme: Electroweak, Higgs, Top, Flavours, QCD, BSM
 - Detector requirements, Detector concepts and Machine-Detector Interface
 - Centre-of-mass energy calibration, polarisation, monochromatisation
 - Physics software and computing
- Plan and prepare our contribution to the FCC FS mid-term review report
 - Main mid-term review PED deliverables, with current focus on FCC-ee
 - FCC-INT physics case consolidated (w/ specificities and complementarities of both colliders)
 - Theoretical calculation improvement strategically planned
 - Main detector requirements documented
 - Cost drivers for detector construction and operation evaluated
 - → See https://www.overleaf.com/read/tqshqcrkknmh for more details
 - A lot more to explore and document beyond these compulsory deliverables





Goals of the Workshop

- A lot more to <u>explore :</u> preliminary to-do list to be amended and completed
 - Document the (physics) arguments for having 2 or 4 interaction regions
 - Includes carbon footprint, plus all arguments we developed a couple years ago
 - Requirements from detectors on experimental sites
 - e.g, position of the booster, need of a secondary cavern, services, etc.
 - Cost drivers and estimates for detectors
 - Required detector R&D
 - Common software framework and computing infrastructure
 - E.g., plug-and-play, analysis framework, etc.
 - International community building
 - With, in particular, the Informal Forum of National Contacts (IFNC)
 - FCC-<u>hh</u> detector concept
 - Etc.

D To be amended and completed during this and the next workshops

P. Janot, C	. Grojean
-------------	-----------

optimized placement and layout

FUTURE CIRCULAR

COLLIDER

M. Benedikt, FCC FS Status

8-site baseline "PA31-	-3.0″	Sergy 5 PA: Experiment Campes Vielance	Gy Jussy Saint Cerg
Number of surface sites	8	Satisfy Stranger Colorest Scionest Scio	
LSS@IP (PA, PD, PG, PJ)	1400 m	Pueringe Pe	la-Grand
LSS@TECH (PB, PF, PH, PL)	2032 m	Peron Cartigge Cartige Car	Aerodrome Marcel Bruchon Heraz-Monthoux
Arc length	9.6 km	Aulty Sezence Luly Plan-les-Ouales Veyner Homes Homes	Arthar-Pont- Notre-Dame Nangy
Sum of arc lengths	76.9 m	Changy Notify Seegnn Sont Saint-Julian- Dugry Seegnn Sont Saint-Julian- Dugry Michange Seegnn Sont Saint-Julian- Dugry Michange South Seegnn Filter Stable P	PD: experiment
Total length	90.6 km	A 40 Vr7 regers	Scientifier
 8 sites – less use of land, <40 ha instead 62 ha Possibility for 4 experiment sites in FCC-ee All sites close to road infrastructures (< 5 km of new road constructions for all sites) Vicinity of several sites to 400 kV grid lines Good road connection of PD, PF, PG, PH suggest 		Very very very very very very very very v	errs juny d d technical
 operation pole around Annecy/LAPP Exchanges with ~40 local communes in preparation 		the selectors and the selector	t J. Gutleber

CIRCULAR reviews of surface site requirements, 3-4 October 2022

Review of CE and TI requirements for FCC experimental sites

Reviewers: Austin Ball (STFC), Alain Chabert (SFTRF), Peter Krizan (Jozef Stefan Institute), Rolf Lindner (CERN), Andrew Parker (University of Cambridge – Chairperson), Roberto Tenchini (INFN Sezione di Pisa), Frank Zimmermann (CERN – Secretary)

- endorses the baseline concept for the FCC experiment site underground structures of an experimental cavern with a single experimental shaft for the main detector, linked via a transfer tunnel to the service cavern, with a second shaft (cf. CMS),
- suggests detailed study of implications of the stray field from unshielded FCChh detector magnets and to consider alternatives with shielded magnet systems.

FUTURE CIRCULAR Mid-Term Review & Cost Review, autumn '23

M. Benedikt, FCC FS Status

Mid-term review report, supported by additional documentation on each deliverable, will be submitted to review committees and to Council and its subordinate bodies, as input for the review.

Results of both general mid-term review and the cost review should indicate the main directions and areas of attention for the second part of the Feasibility Study

Infrastructure & placement

- Preferred placement and progress with host states (territorial matters, initial states, dialogue, etc.)
- Updated civil engineering design (layout, cost, excavation)
- Preparations for site investigations

Technical Infrastructure

- Requirements on large technical infrastructure systems
- System designs, layouts, resource needs, cost estimates

Accelerator design FCC-ee and FCC-hh

- FCC-ee overall layout with injector
- Impact of operation sequence: Z, W, ZH, $t\bar{t}$ vs start at ZH
- Comparison of the SPS as pre-booster with a 10-20 GeV linac
- Key technologies and status of technology R&D program
- FCC-hh overall layout & injection lines from LHC and SC-SPS

Physics, experiments, detectors:

- Documentation of FCC-ee and FCC-hh physics cases
- Plans for improved theoretical calculations to reduce theoretical uncertainties towards matching FCC-ee statistical precision for the most important measurements.
- First documentation of main detector requirements to fully exploit the FCC-ee physics opportunities

Organisation and financing:

- Overall cost estimate & spending profile for stage 1 project

Environmental impact, socio-economic impact:


- Initial state analysis, carbon footprint, management of excavated materials, etc.
- Socio-economic impact and sustainability studies

10

Next Steps - Mechanical model of the FCC-ee MDI

- Integration of the support tube with the detector Anchoring points with the detector Required space for services
- Support and alignment of the LumiCal
- Cryostat-Support tube interface
- Refine FEA calculation with weights and thermal loads
- Refine the assembly procedure while the MDI design progresses

Design of the Bellows• RefinWakefields calculationsdesignEngineered design of endcap-bellows & flange-bellows interface



11

IDEA vertex detector in full simulation

Talk: Armin Ilg (Univ. Zurich)

First full sim implementation in DD4hep

Use this layout as basis for full simulation implementation

 \rightarrow Needed for performance estimation



End-cap with three disks per side

Working together to update the software with the evolving design



12

Future plans: mechanical model of the MDI

The very central region ± 1.5 m from the IP is being studied including the integration of the vertex and outer trackers, we will progress outside the very central region and with the overall design, assembly strategy, supports

Also the following topics relevant/critical for the design of the IR

- Remote flange design based on shape-memory-alloy (SMA) will start in the next months
- IR magnets design, key component for the MDI dedicated slide later
- > IP diagnostics, especially for the constraint to the available space, BPMs need discussion with BI group
- Supports & vibration control
- Alignment system

IR magnet system


- Progress on the overall IR magnets design including solenoids and correctors is essential to progress with the overall mechanical design, integration and assembly of the MDI.
- Review April 2022 on IR magnets design with cryostat, challenges identified tapering, corrector design, accessibility and serviceability- we need to move to the next level of the design. There are pending details on the mechanical support, cryogenics, thermal heat loads, alignment, services which need resourcing to move forward.
- TE Magnet group identified two main work packages as potential collaboration to be discussed with FCC.
 - IR final focus magnets with solenoids, interest of BNL to collaborate, collaboration CERN-BNL under discussion.
 - Crab high field sextupole on FCC-ee are under evaluation for conduction cooled options, optics sensitivity requested and magnetic design. Resourcing subject to pending collaboration with TE.

14

Interaction Region magnet design

BNL's Superconducting Magnet Division involved in areas of Interaction Region magnet design and Machine Detector Interface

- BNL Direct Wind magnet production technology suitable for producing the main IR quadrupoles
 - only practical way to introduce FCC-ee IR corrector magnets
 - significant design challenges to resolve for implementing the required anti-solenoid coils for detector field compensation while maintaining the desired experimental acceptance
- Enhance collaboration with the FCC-ee IR design team




BNL Direct Wind in Action Closeup View

Starring: Brett Parker



Conclusion

- BNL has excellent synergies in physics, accelerators and detectors in support of high energy physics
- Excited to deepen BNL's contribution to FCC-ee
- Building FCC-ee community in the US



Marc-André Pleier, BNL contributions to the FCC-ee



NFN

FCC-ee IR mock-up at Frascati

Very useful to learn from other experiences of similar R&D activity, e.g. CMS, CLIC.


We propose to add to the CAD model of the MDI a complementary R&D activity consisting in a full-scale IR mock-up to be realised at Frascati.

A project proposal is under evaluation by INFN and details of **scope, cost and timeline** under discussion with CERN. We need to conclude with FCC addendum.

Lessons learnt:


FCC


- Start with a simple, cheap design get a general feeling of the possible problems, then upgrade. Don't go for the too sophisticated mockup to early.
- Iterate with CAD models in parallel, don't wait for the final beautiful CAD models to be finished to find out that they don't work, Check your 3D design on the physical objects as soon as possible and iterate.
- 3. Don't hesitate to make the assumptions – getting all the solid inputs in R&D projects is a rare thing. Assumptions even if wrong can trigger useful discussions.
- Try to predict other possible functions for the mockup and leave as much flexibility for the coming modifications as possible.
- 5. If possible, locate your mockup in the proximity of the workshop.



Lessons Learnt from CMS Mock-ups link talk Andrea Gaddi(CERN)

with considerations on a mock-up for FCC-ee IR





(a)

courtesy F. Duarte Ramos

17

Conclusions

- First and most important: define the scope of the mock-up, then make a deep evaluation of its design, the manufacturing methods, the installation, the different functionality tests, etc.
- Define the different mock-up materials, as function of their scope (<u>e.g.</u> if it is just to represent a volume, make it in plastic or wood, if it is needed to evaluate vibration modes, mass and stiffness are important).
- A physical mockup changes with time, as the needs of physicists and engineers -> it shall be designed for its evolution in time.
- Evaluate the need for general utilities (<u>e.g.</u> crane, cooling, power, sensors, dry air, gas) and the proximity of a workshop.
- Draft a timeline and a resources estimate for the muck-up preparation and exploitation.

A side issue for the experimental sites review: Position of the booster ring


Booster position may have consequences on the tunnel layout around the IP

The booster ring passes through cavern outside detector volume at [x, y] = [8.0, 1.3]m

Request: At the booster position, the magnetic field should not exceed 10 mT

Study performed by Nikkie Deelen (see next slide)

CAVEAT: Compensation solenoids in the interaction region are not included yet, design of those magnets is ongoing by M. Koratzinos.



Detector stray magnetic fields

FCC-ee booster line will pass close to detectors

Nikkie Deelen


IDEA Stray field (x,y) = [8.0,1.3]mLCalo OUT Stray field (x,y) = [8.0,1.3]mCLD Stray field (x,y) = [8.0,1.3]m10 30 □ Br ♦ Bz ○ IBI 100 Magnetic flux density [mT □ Br◊ Bz○ IBI Magnetic flux density [mT Im 🗆 Br O Bz Magnetic flux density o IBI 20 5 50 10 mT 10 10 m -10 mT -10 -10 mT -5 -50 -20 -50 -20 50 13 z [m] 17 z [m] 8 z [m]

Will be followed-up:

we need to have the tolerable limit value from the booster dipole during injection, and understand if we need shielding or if correctors in the booster can easily recover this value


Detector Backgrounds

- CLD detector and MDI model in Geant4 adapted to 10 mm beampipe
- Solenoid field map imported in key4hep
- Collision products, beam, and photon losses are now studied
- Occupancy from incoherent pair production tolerable
- Occupancy from beam halo losses only concerning at ttbar, for beam loss scenarios considered until now




Beam losses & photon tracks from A. Abramov & K. André

- Preliminary studies show little quench risk for the FF quads due to halo losses.
- Preliminary studies show photon losses absorbed or deflected by mask



	z	ww	ZH	Тор
Pairs/BX	1300	1800	2700	3300
Max occup. VXDB	70e-6	280e-6	410e-6	1150e-6
Max occup. VXDE	22.5e-6	95e-6	140e-6	220e-6
Max occup. TRKB	9e-6	20e-6	38e-6	40e-6
Max occup. TRKE	110e-6	150e-6	230e-6	290e-6



Next Steps on Backgrounds studies

more details at next MDI meeting 20 February https://indico.cern.ch/event/1251507/

Beam losses

FCC

- Study other beam loss scenarios
- Obtain input for the equipment loss tolerances superconducting magnets, collimators, other
 - Energy deposition studies required for magnets, collimators, and masks
 - Detailed evaluation of detector backgrounds required shielding, muon backgrounds
- Study all beam modes
- Synchrotron Radiation

Iteration on the positions and apertures of the synchrotron radiation collimators within the collimation hierarchy Study the SR collimation performance with the X-Y tail distribution modeling (charge and width) Continue the study of the synchrotron radiation background due to off-axis top-up injection

• Backgrounds in CLD (& IDEA?) detector

Tracking the primary beam particles and the photons hitting the pipe performed in Key4HEP Photons at the tip of the SR mask upstream the IP

• Radiation studies in the experimental area and in the BS dump area will start with FLUKA in March

Detector Software

The community agreed on using a common software framework for all future collider studies: Key4hep Detector description with DD4hep, geometry description ongoing:

CLD


FCC

- All CLD sub-detectors implements in DD4hep
- Reconstruction well advanced, inherited from ILD/CLICdet

IDEA

MDI:

- IDEA full sim: standalone (plain Geant4) detector simulatio
- Full reconstruction non available yet
- ongoing effort towards Key4hep integration **Noble Liquid Based**
- Detector concept in its infancy



- Improve beam background overlay workflow
- produce field maps with the interplay between magnets and detector magnet fields
 - impact on the tracking performance

Francois Brieuc

23

Outlook

FCC

The FCC Physics workshop was a good occasion:

- to get together in person
- strengthen the FCC PED community
- prepare Mid-term report
- sharpen FCC physics case

About MDI:

- We have a FCCIS deliverable on the IR and MDI design, that will be also used as part of the mid-term review report.
- We need a rough cost estimate for the cost review.

Plans for the Mid-Term Review

- Interaction Region and machine detector interface design: 3D CAD proof-of-principle engineered mechanical design of the interface between the accelerator and detector components in the interaction region.
- **Detector backgrounds** evaluation, including a first collimation setting and shieldings for various beam loss scenario.
- **Radiation in the IR**: assessment from all sources and handling strategy.
- Heat load assessment from beam losses, synchrotron radiation and wake-fields on the beam pipe, magnets and components.
- List of **functional and conceptual specification for all the various magnetic fields** including the SC correctors and the cryostat.
- Definition of the **IR magnet system**, studied as an integrated group: **field quality**, **mechanical constraints**, **e.m. forces**, supports, accessibility, services.
- Definition of the IR mock-up project