

Towards the CLIC Readiness Report

Meeting in March

- Process to understand better specs, status and measurement results for wake-field monitors
- Prototyping DR RF cavity (essential for power reductions in this area)
- First indications of embedded carbon due to accelerator construction

https://indico.cern.ch/event/ 1260607/

| 🧮 Tuesday | Dwards Readiness Report 2025-26 7 Mar 2023, 11:00 \rightarrow 13:00 Europe/Zurich 18 (CERN) | 2 - |
|----------------------|---|-----------|
| 11:00 → 11:05 | CLIC readiness report 2025-26 | () 5m 🕑 👻 |
| | Brief intro | |
| | Speaker: Steinar Stapnes (CERN) | |
| | intro-march23.pdf | |
| 11:05 → 11:50 | Wakefield monitor measurements and issues - including discussion | 𝔅 45m 🕑 ▾ |
| | Speakers: Kyrre Ness Sjobaek (University of Oslo (NO)), Kyrre Ness Sjøbæk (University of Oslo) | |
| | 2023-03-07_CASC | |
| 11:50 → 12:00 | Brief update on DR RF demonstration | ©10m ┏ - |
| | Speaker: Alexej Grudiev (CERN) | |
| | BriefUpdateDRRFd BriefUpdateDRRFd | |
| 12:05 → 12:30 | Update on sustainability studies | © 25m 🕑 👻 |
| | Speakers: Dr Benno List (Deutsches Elektronen-Synchrotron (DE)), Carlo Rossi (CERN), Steffen Doebert (CERN) | |
| | CLIC_Main_Linac | |
| 12:40 → 12:45 | Next meeting - close | () 5m 🕑 👻 |
| | Project meeting Thursday 27.4 | |

Sustainability during operation

- Operation costs dominated by energy (and personnel, not discussed in the following)
- Reducing power use, and costs of power, will be crucial. Other consumables (gas, liquids, travels ...) during operation need to be well
 justified. Align to future energy markets, green and more renewables, make sure we can be flexible customer and deal with grid
 stability/quality.
- Carbon footprint related to energy source, relatively low already for CERN (helped by nuclear power), expected to become significantly lower towards 2050 when future accelerators are foreseen to become operational (in Europe, US and Japan). Provided we can run on green mixtures (PPA example at CERN, also built fully into the green ILC concept) we can also contractually chose green options. LCs are very suited for this (variable power load).




Figure 6.14 \triangleright Average CO₂ intensity of electricity generation for selected

regions by scenario, 2020-2050

CO₂ intensity of electricity generation varies widely today, but all regions see a decline in future years and many have declared net zero emissions ambitions by around 2050



For ILC: renewable energy available (Tohoku Electric Power) in local grid at ~23% level, need 0.5-1 % for ILC. Additionally considers increased CO2 absorption to be fully neutral. A rough estimate, assuming ~50% nuclear and ~50% renewables (as wind/sun/hydro):


1 TWh annually equals ~12.5 ktons CO2 equiv. annually

(note: this is factor four below the current French summer month average)


Energy costs

Typical power numbers for Higgs factories on the right – table also shown earlier

The CERN "standard" running scenario is shown below, used to convert to annual energy needs.



Extrapolating out to 2032 assuming: No ARENH and "high" future electricity prices



Very uncertain but MTP assumes 140 MCHF/TWh beyond 2026.

With "standard" running scenario (on the right) every 100 MW corresponds to ~0.6 TWh annually, corresponding to ~85 MCHF annually.

Annual shutdown
 Commissioning
 Technical stops
 Machine development
 Fault induced stops
 Data taking

120

30

139




Sustainable Construction – Life Cycle Assessment

For carbon emission the construction impact will be much earlier and might be more significant (also rare earths and many other issues etc):

- Construction: CE, materials, processing and assembly not easy to calculate
- Markets will push for reduced carbon, responsible purchasing crucial (see right) construction costs likely to increase

Decommissioning – how do we estimate impacts ?



Assume a small tunnel (~5.6m diameter) **and** that the equipment in the tunnel has the same carbon footprint as the tunnel itself, a 20km accelerator (tunnel plus components) corresponds to 240 kton CO2 equiv.

Many caveats, this is only a very first indication of the scale:

- + many more components in tunnel (also infrastructure), injectors, shafts, detectors, construction work, spoils, etc etc
- + upgrades and decommissioning, this is not only an initial important contribution
- improvement and optimisations (e.g. less and/or better concrete mixes, support structures, less steel in tunnels, responsible purchasing, etc etc)

Responsible purchasing – and understanding the impact on our supply chain, costs and potential for changes – will be essentials for future projects (CERN implementation information from E.Cennini)

ARUP

Carbon Cost/Life Cycle Assessment LCA study 2023

Goal and Scope


- Goal: Reduce embodied and construction environmental impacts
- LCA for 3 tunnel options (tunnels, caverns & access shafts)
- System boundaries: Embodied and construction. Excluding operation, use and end of life.

1. CLIC Drive Beam tunnel, 5.6m internal diameter 2. CLIC Klystron tunnel, 10m internal diameter


 ILC Japan tunne arched 9.5m span







Material (incl. Scrap) GWP [kg CO2-eq]



Copper
Stainless Steel
Mild Steel
Titanium
Aluminium



Readiness Report ~2025

Update wrt PiP 2018, format to be determined


Key updates:

- Luminosity numbers, covering beam-dynamics, nanobeam studies and hardware, and positron production - at all energies
 - Risk reduction (wrt performance), bumps, redundancies
- Energy/power/sustainability: 380 well underway, 3 TeV to be done, L-band klystrons
- Sustainability issues, more work on running/energy models, carbon (construction/operation/disassembly)
- X-band progress for CLIC, smaller machines, industry availability, including RF network
- RF design optimization/development including injectors, R&D for higher energies, gradient (cool/HTS/etc.), power, beam parameters links to plasma (if it can be made)
- Cost update. Changes wrt to 2018, plus impact of going green. CHANGED
- Physics "update", use for "diversity" types of physics, LDM etc. CHANGED
- Low cost/power klystron version, with fewer klystrons, 250 GeV

On-going CLIC studies towards next ESPP update

Project Readiness Report as a step toward a TDR


Assuming ESPP in ~ 2026, Project Approval ~ 2028, Project (tunnel) construction can start in ~ 2030.



Optimizing the luminosity at 380 GeV – already implemented for Snowmass paper, further work to provide margins will continue.

Luminosity margins and increases:

- Initial estimates of static and dynamic degradations from damping ring to IP gave: 1.5 x 10³⁴ cm⁻² s⁻¹
- Simulations taking into accord static and dynamic effects with corrective algorithms give 2.8 on average, and 90% of the machines above 2.3 x 10^{34} cm⁻² s⁻¹ (this is the value currently used)



Various other updates:

Budget planning CERN, no significant changes wrt to last year for the LC studies.

ATF3 kick off 8-9.3: <u>https://indico.cern.ch/event/1259176/</u> EAJADE kick off 29-30.3: <u>https://indico.desy.de/event/36774/</u> CompactLight follow up Eindhoven 3-4.4: <u>https://indico.cern.ch/event/1250754/</u> (SmartLight on the table top right)

Snowmass and P5: Snowmass input completed, P5 session at SLAC next week with talk given by E.Nanni and about C3 and CLIC (dominated by C3 resources "bid")


LCWS 15-19.5: <u>https://indico.slac.stanford.edu/event/7467/overview</u>

- Plenary talks about CLIC and CLIC inspired Applications
- High Eff. Klystrons, Sustainability and ATF with common LC approach
- Parallel talks (several) not yet posted

2-3 day meeting in Oct-Nov, including nano beam WS ? Also CB

| | | | | | | 1 - | | | |
|------------------------|---|---------------------|----------------------|-------------------|-------------|---------------------|-----|--|--|
| Status of | CERN's futu | re collider pro | ojects | | | | | | |
| | | | | | | | | | |
| by Daniel Sc (CERN) | hulte (CERN), Fra | nk Zimmermann (| (CERN), Michelan | gelo Mangano (C | CERN), Stei | nar Stapnes | | | |
| Tuesday 14 | Mar 2023, 11:00 → 1 | 13:00 Europe/Zurich | | | | | | | |
| ♀ 500/1-001 - | Main Auditorium (CEF | | | | | | | | |
| Description | scription Opening event of a new seminar series dedicated to future collider projects. This first seminar will present the status and goals of ongoing studies related to the Future Circular Collider (Zimmermann), the Muon Collider (Schulte) and Linear ee Colliders (Stapnes). Refreshments will be served at 10:30. | | | | | | | | |
| | | | | | | | | | |
| Ø | PrankZimmermann | FrankZimmermann | MCC_Schulte_CER | Mangano_Intro.pdf | S Recording | 🔁 Stapnes-linear-co | III | | |
| | Stapnes-linear-colli | & Video preview | | | | | | | |
| Videoconference | Stuture Colliders Ser | ► J | ► Join ■ 500/1-001 ↓ | | | | | | |
| Webcast | There is a live webc | | | | | | | | |
| Contact | contact 🖾 ep-seminars.colloquia@cern.ch | | | | | | | | |
| | -h | | | | | | | | |

https://indico.cern.ch/event/1260648/





16–20 Oct 2023 INFN Frascati National Laboratori Europe/Rome timezone

Enter your search term Q

https://agenda.infn.it/event/34253/

CLIC in accelerating news

https://acceleratingnews.eu/topic /compact-linear-collider-clic The Compact Linear Collider (CLIC) is a proposed accelerator, designed as an addition to CERN's accelerator complex. Its objective is to collide electrons and positrons (antielectrons) head-on at energies of up to several teraelectronvolts (TeV). For an optimal exploitation of its physics potential, CLIC is intended to be built and operated in three stages, at collision energies of 380 GeV, 1.5 TeV and 3 TeV respectively, for a site length ranging from 11 to 50 km. The design and technology development for CLIC being is pursued by an international collaboration of more than 70 institutes in more than 30 countries.



Japan's Accelerator Test Facility 2 opens again for overseas collaborators experiments

Located in KEK Japan, this experimental facility will pursue the necessary R&D to maximize the luminosity potential of linear colliders.

Issue 43 | Compact Linear Collider (CLIC) | 15 March, 2023

CLIC looks towards 2025

The CLIC collaboration is moving towards its technical design report.

Issue 42 | Compact Linear Collider (CLIC) | 15 December, 2022



Optimising CLIC for reducing the electricity consumption at machine and laboratory level

Optimised system designs for power efficiency, high efficiency klystrons, permanent magnets, renewable power... The linear collider projects are working to address power efficiency and reduce the environmental impact of the facilities.

Issue 41 | Compact Linear Collider (CLIC) | 19 September, 2022



Permanent magnets, a new design paradigm for ultralow emittance rings

In order to reduce the beam emittance by a large factor, the CLIC Collaboration has developed an innovative dipole magnet prototype and built a permanent magnet demonstrator

Issue 40 | Compact Linear Collider (CLIC) | 23 June, 2022

CompactLight completes the Conceptual Design Report for an advanced and compact hard X-ray facility

The EU-funded project held the promise of designing more compact and cost-effective linac-based photon sources.

Issue 39 | Compact Linear Collider (CLIC) | 04 March, 2022