



Electron cloud: potential mitigation strategies and plans for interventions during LS3

EDMS 2954143

V. Baglin – CERN – TE/VSC on behalf of

G. Rosaz, P. Chiggiato, V. Petit, M. Taborelli, J.-P. Tock, M. Barberan Marin, S. Atieh, S. Le Naour

<https://indico.cern.ch/event/1293138/timetable/#20230926>

Outline

1. Electron cloud in the LHC

- Run 1 and Run 2
- Surface analysis of LHC-extracted beam screens during LS2
- Run 3 and beyond
- HL-LHC heat load forecast

2. Proposed mitigation project


- Phase 1 – Process selection and optimization
- Phase 2 – Mock-up demonstration / Personnel training
- Phase 3 – Implementation

3. Summary


1. Electron cloud in the LHC

Electron cloud in the LHC – Run 1 and Run 2

- After LS1, we observed a **wide beam-induced heat load spread** between low and high heat load arcs and between consecutive cells within an arc
- Heat loads are in **good agreement with electron cloud effects** assuming a **deterioration of the Secondary Electron Yield (SEY)** (multiplication factor of the electrons in the beam pipe) of some beam screens






G. Iadarola




Surface analysis of LHC-extracted beam screen during LS2

- **Surface analysis at RT of low and high heat load beam screens extracted from the LHC during LS2 suggest CuO (Cu II oxide or cupric oxide) and low carbon amount as responsible for high heat loads**



Run 3 and beyond

- Although additional precautions were implemented for LS2 (dry air venting, limited air exposure time...), further heat load degradation are observed during Run 3.
- Since we currently do not control the process of the **surface ageing** in the different sectors, **further degradation cannot be excluded** for Run 4 and beyond.
 - keep investigating this aspect with laboratory experiments
 - **need for mitigation solutions** e.g. hybrid beams for LHC




B. Bradu

HL-LHC heat load forecast

Example of Sector 12:

- Heat load simulation for high intensity beams based on recent heat load measurements
- Heat load estimate **overcomes the cryogenic capacity**
 - a beam screen **treatment** is required to bring **heat loads 10% below cooling capacity**



2. Proposed mitigation: Beam Screen Treatment Project

BST Project overview

Objective

- **Remove CuO** and/or **increase surface carbon concentration** on selected beam screens
- Beam screen **surface passivation** (robustness against re-oxidation)

Strategy

- Limit the number of magnet interconnection opening
 - treatment of full half-cells (3 dipoles + 1 quadrupole, 53 m) in a single step
- Treatment campaign during LS3

Project phasing


- **Phase 1** – Process selection / optimization (2 technological choices) (up to Q2-2024)
- **Phase 2** – Mock-up demonstration / Personnel training (Q2-2024 → Q1-2026)
- **Phase 3** – Implementation in the machine (Q2-2026 → Q2-2028) – LS3

	2023				2024				2025				2026				2027				2028			
	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
Phase-1																								
Phase-2																								
Phase-3																								

Phase 1: Process selection / optimization

Quality assessment

- **Secondary Electron Yield:** « as produced » and after electron conditioning at 15 K
- **Photo-Electron Yield** quantification on samples
- Ageing (multiple 15K conditioning + thermal & air exposure cycles)
 - robustness against re-oxidation
- Adhesion
- **Electron Stimulated Desorption**




Option 1: Plasma-assisted CuO reduction and carbon recovery (PE-CVD)

- + Efficient CuO reduction and carbon deposition obtained in 10^{-1} mbar of C_3H_8 (propane)
- + Several cm/min \rightarrow \approx 1 day/53m/beam line
- + No significant warm-up (\leq 50 W)
- "as-produced" SEY is high (\approx 1.5 - 2) due to presence of hydrogen in C_xH_y gas

To be further investigated:

\rightarrow Optimize gas type, pressure, time...




PE-CVD : Plasma Enhanced Chemical Vapor Deposition

Option 2: Very thin amorphous carbon coating by sputtering (PVD)

- + CERN has expertise (SPS campaign, HL-LHC: in-situ a-C coating of IT2&8 + new IP1&5 beam screens)
- + Compatibility with LHC beam pipe environment already assessed (Q5L8 a-C coated during LS2)
- + Lower “as-produced” SEY achieved than with PE-CVD
- “as-produced” SEY is still high (≈ 1.3) due to the absence of H_2 pumping during the process (performed without Ti sputtering) and due to lower coating thickness as compared to HL-LHC base line (<10 nm vs 50-100 nm)
- ≈ 4 days/53m/beam line

To be further investigated:


→ Evaluate effect of degraded vacuum quality during coating onto SEY



PVD : Physical Vapor Deposition

Assessment of conditioning at 15 K

- Validated behaviour during conditioning at 15 K for both techniques
- Ageing study on going



➔ Decision on technological choice by mid-2024

Phase 2: Mock-up demonstration / Personnel training

Mock-up demonstration and personnel training

- Demonstrate on a **1:1 scale** the **treatment process** over a full 53m long half-cell
- Mock-up = cold bore + beam screen + plug-in modules (PIMs) + beam position monitors (BPMs) with **arc curvature**
- **PIMs and BPM passage** by the coating train
- **Vacuum interface** qualification
- **Process fine tuning**
- **Personnel training** in view of in-situ deployment
- Ongoing discussion to identify location




HL-LHC in-situ a-C coating test bench

Phase 3 – Implementation in the machine during LS3


Activities and structure identification

- Interconnections opening / closure (TE-MSC)
- PIMs cutting / re-installation (EN-MME) (component availability ensured by TE-VSC)
- Beam screen treatment + QA (witness sample) (TE-VSC)
- Post treatment QA (cf. LS2 procedures) (TE-VSC)
- Temperature sensors inspection (TE-CRG)
- Beam Loss Monitor removal / re-installation (SY-BI)




Preliminary working sequence

- Assuming effective treatment time ~ **4 days / hc / beamline** (process dependant)
- **2 days** for coating system assembly + **1 day** for disassembly per beam line
- **3 coating setups** used in parallel managed by **2 teams**
- Available time for in-situ treatment: **400 working days**
 → estimate: **100 full half-cells (i.e. 2x5.3 km of beam pipes)**
- Arc sequence determined by LS3 coordination (including synergies with other consolidation activities)



...

...



3. Summary

Summary

- Beam-induced heat loads are of **critical importance** for HL-LHC operation
- **Surface-induced effects** are identified as root cause
- **Mitigation project** submitted to CERN ATS management: BST Project
 - Phase 1: process selection + optimization
 - Cryo-conditioning of as-processed films validated
 - Ageing study ongoing
 - Phase 2: mock-up demonstration and personnel training
 - Location in discussion
 - Phase 3: Implementation
 - Ongoing definition
- Ongoing identification of selected half-cells by the CERN Beam-Induced Heat Loads Task Force

Thank you for your attention!