


Low Emittance Rings workshop 2024

13-16 February 2024 CERN, Geneva



Sustainability and energy efficiency at ESRF 15 February 2023 Jean-Luc Revol





The European Synchrotron

OUTLINE



- Context
- EBS contribution
- Overall sustainability
- ESSRI workshops
- Conclusion and outlooks



ESRF, Grenoble, 29-30 September 2022


ESSRI: Energy for Sustainable Science at Research Infrastructures



CONTEXT



- Practical experience of climate change with record temperatures, long drought periods, forest fires, floods
- General inflation of energy cost: Covid19, Ukraine invasion, Unpredictable fluctuations on the energy trading exchange,..



But sustainability in our institutes is mostly limited to energy (and largely electricity) management driven by operational cost reduction!!!

→ High energy prices and crisis often help and not hinder decarbonisation !!

Some light sources were obliged to reduce user operation due to energy cost (Soleil, Elettra, Solaris...).

ESRF was able to maintain the operation schedule for users and development but the energy has a large impact on the budget.



REGULATIONS

02

03

04

05



Periodic report (every 4 years) Action plan required.

Energy saving plan

French initiative : 10% reduction of energy consumption in 2024 (base : 2019).

EU climate law : FIT 55

European regulation. 47% reduction on Green House gas emissions in 2030 (base 2005)

Decret Tertiaire

40% Energy consumption reduction for tertiary buildings in 2030. Reference year to be defined

Loi Climat et Resilience

Car parks solar panels

Minimum 50% of parking places covered by solar panels.



THE ESRF: FACT AND FIGURES

Light source in operation since 1994, Grenoble, France 22 partner nations


Budget: 115 million euros, Staff: 700 people 5500 hours of beam delivery 1500 experimental sessions 49 beamlines

Upgrade programme 2009-2023 (2 phases):

- New beamlines
- Renew infrastructures and support facilities
- New storage ring source (EBS)


The Extremely Brilliant Source (EBS) 2015-2020:

- Decrease the horizontal emittance
- Increase the source brilliance
- Increase the source coherence
- Keep as much as possible of the infrastructure
- Minimize operation costs, particularly wall-plug power




133 pm.rad

4000 pm.rad





EBS UPGRADE LATTICE



MAGNETS OPTIMIZATION

Space limitation, Wall plug power, Performance, Procurement, Installation, Operation

Resistive magnets

Copper cross section adapted for reasonable current density

• ~ 3 A/ mm² @ nominal working point



Permanent magnets

Primarily for fixed field magnets

→ Dipoles

Wall plug power=0 Affordable technology (and cost) Experience with insertion device construction





➔ Also for septa

(Some) tunability and flexibility should be maintained for the lattice.



POWER AND ENERGY CONSUMPTIONFOR THE MAGNETS

ESRF :	2018	EBS
Dipoles (D)	720 kW	0
Correctors and Steerers	10 kW	11 kW
Other magnets	1625 kW	1059 kW
Dipole-quadrupoles (DQ)		16%
High gradient quadrupoles (HGQ)		29%
Moderate gradient quadrupoles (MGQ)		44 %
Sextupoles (S)		10%
Octupoles (O)		1%
Total	2355 kW	1070 kW
Energy for one year operation (7200 H: USM+MDT)	16.9 GWh	7.7 GWh

Very positive experience with Permanent Accelerator Magnet for EBS:

- · Works as expected, passive devices in the storage ring, no maintenance
- ... and no cabling, no power supply, no cooling, no vibration, easier installation and better operational reliability
- · Very good stability vs temperature, based on passive compensation
- Electrical power required for the EBS magnets → half that of the previous lattice
- DQs and HGQs could be permanent magnets (no tuning required), 476 kW additional saving

Permanent magnet is convincing for operation,...but the overall sustainability is less obvious considering the extraction and production issues Storage Ring Total electrical power: 6350 kW [2018] 4100 kW [EBS]



RADIO-FREQUENCY CONSUMPTION

Storage Ring Total power:

1300 kW RF [2018],

900 kW RF [EBS].

Radiation loss 4.88 MeV/turn+ 0.5 (ID) 5 Five 5-cell, 2 single-cell cavities 9 MV total voltage


Radiation loss 2.5 MeV/turn + 0.5 (ID) 13 single-cell cavities 5.5 MV total voltage

ECO mode (applied since October 2022): Reduction of total accelerating voltage from 6.0 to 5.5 MV

• And Increase AC to RF conversion efficiency:

150 kW SSA operated way below nominal power, at 90 ...100 kW, where the efficiency was low.

- ⇒ Increase the Klystron power by increasing Cav 1 to 10 voltage from 4.5 to 5.0 MV
- \Rightarrow Operate with only 1 SSA at 0.5 MV



Efficiency AC → RF:	
Klystron:	53%
Present SSA:	47%
New SSA (to replace Klystron):	59%

EBS_RF configuration


RESULT:

- 200 kW AC power savings at 200 mA
- Same beam lifetime for typical ID losses
- 500 kW total savings possible if operation at 100 mA

Storage Ring Total electrical power: 6350 kW [2018] 4100 kW [EBS]



LIFETIME, INJECTION EFFICIENCY AND INJECTOR USAGE




EBS parameters:

Beam lifetime larger than 20 hours Injection efficiency in the order of 70% Top-up every 1 hour

Typical injection in 2022:

725 kW for the injector during 2 mn. every 1 hour

(45s for preparation, 70s for injection with only 32s beam on)



The European Synchrotron


During machine development time, optimisation of the programme and guidelines is imposed for the usage of the injector.

TYPICAL POWER CONSUMPTION

- 854 kW Base with cooling and auxiliaries ON Base Power in shutdown: 330 kW
- 360 kW HQPS consumption mode ECO: (with transient up to 800 kW when SYRF switched ON) In normal mode 510 kW (transient 731 kW).
- 2149 kW Power consumption of the storage ring without beam: (Magnets: 1084 kW RF: Klystron: 941 kW SSA: 124 kW)
- 522 kW Beam power at 200 mA
- 150 kW ID power (90 kW average)
- 4035 kW Total for the storage ring
- +725 kW Injector consumption (RF : 176 kW ; Magnets: 560 kW)

Total electricity consumption of the institute:

- 4100 kW for the SR at 200 mA
- + 725 *kW* every hour for 2 *mn* for injection (1100 max with transient)
- + 2300 *kW* base facility consumption for labs, office, Experiments,...
- + 700 kW facility fluctuation for staff activity



The European Synchrotron ESRF

ENERGY MANAGEMENT FOR THE WHOLE INSTITUTE


<u>Today:</u>

Electricity consumption:50 GWh / yearHeating consumption:7.1 GWh / year

(District heating network)

Cooling: DRAC River

(free cooling)




Total energy savings :

25 GWh done 6.1 GWh in project

> Buildings: LED lightning, insulation,... Cooling: Pumping system, regulations, refrigerators, heating pump.. Accelerators: EBS, RF



Heat recovery from cooling which should provide 93 % of the experimental-hall heating



- Installation of solar panels
- Guest house wall insulation
- Data centers consumption (3.5% today) will increase in the years to come (heat recovery)



THE ESRF : SUSTAINABILITY WITH A REDUCTION OF TRAVELS

• Full remote access possibilities for users to reduce travel

	Number of experiments				
Year	Total	Onsite	Hybrid	Remote	
2018	2831	2285	91 (3%)	455 (16%)	Prior EBS
2019					Shutdown
2020					COVID
2021					COVID
2022	2295	1276	245 (11%)	774 (34%)	EBS

- ✓ Well adapted to repetitive experiments and automated beamlines (macromolecular crystallography, commercial clients..)
- ✓ <u>Hybrid access is favoured</u> with the presence of experts on site to support the local scientists
- Full remote access possibilities to the accelerators to support machine studies and for interventions *(expended since COVID pandemic but will be re-discussed due to cybersecurity)*



• Incitation to a reduction of the staff professional trips and the use of remote meetings




CONCLUSION FOR THE ESRF

- The use of permanent magnets for accelerator design proved to be efficient and reliable
- The EBS upgrade allowed a drastic reduction of the electricity consumption and this associated to an increase of performance
- Significant effort have been done on the reduction of energy consumption on the infrastructure
- All the efforts vanished by the drastic increase of the energy cost, nevertheless it allowed the continuation of a normal operation program
- Sustainability should not be limited to energy management, significant efforts have also been done on the user side and an action plan have been initiated for a more sustainable procurement
- Life cycle is an important issue for facility upgrades (ESRF old machine was "only" treated as waste with some income)



OVERVIEW OF SUSTAINABILITY FOR LIGHT SOURCES



economical and societal aspects are today key concern for us

GENERAL CONCLUSION

The analysis of the situation is clear

Means and tools are there

What should be next ?

- Act on the climate change
- Think sustainable
- React to the increased energy cost
- Reduce and adapt the energy consumption
- Have a broader vision
 of the situation

- Technology (or almost there)
- Methodology and tools (or almost there)
- Investment is often associated to an increase of performance
- Funding from national or international agencies for efficiency and sustainability (or emerging)

- Conduct new projects and new designs with efficiency and sustainability as primary specifications
- Enhance flexibility in the technical, operational, experimental and human behaviour and actions
- Measure the "scientific productivity" as a function of the energy consumption and the sustainability
- Define sustainability metrics for field
 <u>of activity</u>



ESSRI WORKSHOP SERIES

The 6th ESSRI workshop in a series and was held at ESRF in Grenoble in September 2022 at the ESRF.

Main themes:

Energy management at research infrastructures and * resulting experience

2011: ESS

Lund - Sweden

- Sustainability of equipment, materials and resources *
- * *Energy-efficient technologies*





29/30 OCTOBER 20



6th Workshop **Energy for Sustainable** Science at Research Infrastructures



September 25th to 27th, 2024

https://agenda.ciemat.es/e/ESSRI2024

