





## 1. Motivation

**Detailed simulation** of the interaction between the traversing particles and the LHCb active volumes is the major consumer of CPU resources. During the LHC Run2, the LHCb experiment has spent **more than 90% of the pledged CPU time** to simulate events of interest. Matching the upcoming and future demand for simulated samples means that the development of **faster simulation options** is critical.


## 2. Fast simulation VS. flash simulation



**Detailed simulation** relies on Geant4 to reproduce the radiation-matter interactions that are computed within Gauss\*, the LHCb simulation software.




**Fast simulation** techniques aim to speed up the Geant4-based simulation production by parameterizing the energy deposits instead of relying on physics models.



**Flash (or Ultra-Fast) simulation** strategies aim to directly transform generator-level particles into analysis-level reconstructed objects.

## 3. What is Lamarr?

**Lamarr** is the novel flash-simulation framework of LHCb, able to offer the fastest option to produce simulated samples. Lamarr consists of a **pipeline of (ML-based) modular parameterizations** designed to replace both the simulation and reconstruction steps.



The Lamarr pipeline can be split in two chains:

1. a branch treating **charged particles** relying on tracking and particle identification models;
2. a branch facing the **particle-to-particle correlation** problem innate in the **neutral objects** reconstruction.

## 4. Models under the $k$ -to- $k$ hypothesis


Assuming the existence of an **unambiguous ( $k$ -to- $k$ ) relation** between generated particles and reconstructed objects, the high-level detector response can be modeled in terms of **efficiency** and **"resolution"** (i.e., analysis-level quantities):

- **Efficiency:** *Deep Neural Networks* (DNN) trained to perform classification tasks so that they can be used to parameterize the fraction of "good" candidates (e.g., accepted, reconstructed, or selected).
- **Resolution:** Conditional *Generative Adversarial Networks* (GAN) trained on detailed simulated samples to parameterize the high-level response of LHCb detector (e.g., reconstruction errors, differential log-likelihoods, or multivariate classifier output).

## 5. Charged particles pipeline: the tracking system

Lamarr parameterizes the high-level response of the **LHCb tracking system** relying on the following models:

- **propagation:** approximates the trajectory of charged particles through the dipole magnetic field  $\rightarrow$  *parametric model*;
- **geometrical acceptance:** predicts which of the generated tracks lay within a sensitive area of the detector  $\rightarrow$  *DNN model*;
- **tracking efficiency:** predicts which of the generated tracks in the acceptance are properly reconstructed by the detector  $\rightarrow$  *DNN model*;
- **tracking resolution:** parameterizes the errors introduced by the reconstruction algorithms to the track parameters  $\rightarrow$  *GAN model*;
- **covariance matrix:** parameterizes the uncertainties assessed by the Kalman filter procedure  $\rightarrow$  *GAN model*.




Validation plots for the DNN-based model of the tracking efficiency (left) and the GAN-based model of the spatial tracking resolution (right).

## 6. Charged particles pipeline: the PID system

Lamarr parameterizes the high-level response of the **LHCb PID system** relying on the following models:

- **RICH PID:** parameterizes DLLs resulting from the RICH detectors  $\rightarrow$  *GAN model*;
- **MUON PID:** parameterizes likelihoods resulting from the MUON system  $\rightarrow$  *GAN model*;
- **isMuon:** parameterizes the response of a FPGA-based criterion for muon loose boolean selection  $\rightarrow$  *DNN model*;
- **Global PID:** parameterizes the global high-level response of the PID system, consisting of CombDLLs and ProbNNs  $\rightarrow$  *GAN model*.

Lamarr provides separated models for **muons, pions, kaons, and protons** for each PID set of variables.



Validation plots for the proton-kaon separation parameterized with the GAN-based models of the Global PID response in terms of distributions (left) and proton selection efficiency (right).


## 7. Neutral particles pipeline: the ECAL detector

The flash simulation of the LHCb ECAL detector is not trivial task:

- bremsstrahlung radiation, converted photons, or merged  $\pi^0$  may lead to have  $n$  **generated particles** responsible for  $m$  **reconstructed objects** (in general, with  $n \neq m$ );
- the **particle-to-particle correlation problem** limits the validity of strategies used for modeling the unambiguous  $k$ -to- $k$  detector response.

To parameterize a generic  $n$ -to- $m$  response of the ECAL detector, solutions inspired by the natural language **translation problem** are currently under investigation:

- the aim is to define an **event-level description** of the ECAL response;
- assuming ordered sequences of photons/clusters, the problem can be modeled with a **Transformer** model;
- complying with the problem topology, the ECAL response can be modeled with a **Grapha Neural Network** (GNN) model



Validation plots for the  $(x, y)$ -position of the ECAL clusters as reconstructed by detailed simulation (left) and a Transformer-based model (right). Each bin entry is properly weighted to include also the energy signature.


## 8. Validation campaign

Lamarr provides the high-level response of the LHCb detector by relying on a **pipeline of (subsequent) ML-based modules**. To validate the charged particles chain, the distributions of a set of **analysis-level** reconstructed quantities resulting from Lamarr have been compared with that obtained from detailed simulation for  $\Lambda_b^0 \rightarrow \Lambda_c^+ \mu^- X$  decays with  $\Lambda_c^+ \rightarrow p K^- \pi^+$ .

The deployment of the ML-based models follows a **transcompilation approach** based on **scikitnC**. The models are translated to C files, compiled as **shared objects**, and then dynamically linked in the LHCb simulation software (Gauss).

The integration of Lamarr with Gauss enables:

- interface with all the **LHCb-tuned physics generators** (e.g., Pythia8, EvtGen);
- compatibility with the **distributed computing middleware** and production environment;
- providing **ready-to-use datasets** for centralized analysis.



Validation plots for the  $\Lambda_c^+$  mass obtained from Pythia8 (left) and particle-gun (right) generators by Lamarr VS. detailed simulation. Reproduced from **LHCb-FIGURE-2022-014**.

## 9. Preliminary timing studies

Overall time needed for producing simulated samples has been analyzed for detailed simulation (Geant4-based) and Lamarr. When Lamarr is employed, the generation of particles from collisions (e.g., with Pythia8) becomes the new **major CPU consumer**.

Lamarr allows to reduce the CPU cost for the simulation phase of (at least) **two-order-of-magnitude**. Further timing will require speeding up the generators.

**Detailed simulation:** Pythia8 + Geant4  
1M events @ 2.5 kHS06.s/event = 80 HS06.y

**Ultra-fast simulation:** Pythia8 + Lamarr  
1M events @ 0.5 kHS06.s/event = 15 HS06.y

**Ultra-fast simulation:** Particle Gun + Lamarr  
100M events @ 1 HS06.s/event = 4 HS06.y

## 10. Conclusions and outlook

Great effort is ongoing to put a **fully parametric simulation** of the LHCb experiment into production, aiming to reduce the pressure on computing resources.

DNN-based and GAN-based models succeed in describing the high-level response of the LHCb tracking and PID detectors for **charged particles**. Work is still required to parameterize the response of the ECAL detector due to the **particle-to-particle correlation problem**.

Future development Lamarr aims to support both integration within the LHCb software stack and its use as a **stand-alone** package.

## References

1. V. Chekalina et al., *Generative Models for Fast Calorimeter Simulation: the LHCb case*, *EPL Web Conf.* **214** (2019) 02034, arXiv:1812.01319
2. A. Maevskiy et al., *Fast Data-Driven Simulation of Cherenkov Detectors Using Generative Adversarial Networks*, *J. Phys. Conf. Ser.* **1525** (2020) 012097, arXiv:1905.11825
3. L. Anderlini and M. Barbetti, *scikinC: a tool for deploying machine learning as binaries*, *PoS CompTools2021* (2022) 034
4. A. Rogachev and F. Ratnikov, *GAN with an Auxiliary Regressor for the Fast Simulation of the Electromagnetic Calorimeter Response*, *J. Phys. Conf. Ser.* **2438** (2023) 012086, arXiv:2207.06329
5. L. Anderlini et al., *Lamarr: the ultra-fast simulation option for the LHCb experiment*, *PoS ICHEP2022* (2023) 233
6. M. Barbetti, *Lamarr: LHCb ultra-fast simulation based on machine learning models deployed within Gauss*, arXiv:2303.11428
7. F. Vaselli et al., *FlashSim prototype: an end-to-end fast simulation using Normalizing Flow*, *CERN-CMS-NOTE-2023-003*
8. L. Anderlini et al., *The LHCb ultra-fast simulation option, Lamarr: design and validation*, arXiv:2309.13213
9. M. Barbetti, *The flash-simulation paradigm and its implementation based on Deep Generative Models for the LHCb experiment at CERN*, PhD thesis, University of Firenze, 2024

