**ACAT 2024** 



Contribution ID: 163

Type: Oral

## Tracking and vertexing downstream the LHCb magnet at the first stage of the trigger.

Monday 11 March 2024 15:50 (20 minutes)

A new algorithm, called "Downstream", has been developed at LHCb which is able to reconstruct and select very displaced vertices in real time at the first level of the trigger (HLT1). It makes use of the Upstream Tracker (UT) and the Scintillator Fiber detector (SciFi) of LHCb and it is executed on GPUs inside the Allen framework. In addition to an optimized strategy, it utilizes a Neural Network (NN) implementation to increase the track efficiency and reduce the ghost rates, with very high throughput and limited time budget. Besides serving to reconstruct Ks and Lambda vertices to calibrate and align the detectors, the Downstream algorithm and the associated two-track vertexing will largely increase the LHCb physics potential for detecting long-lived particles during the Run3.

## Significance

The algorithms developed under this work hugely increases the LHCb potential to discover new physics.

## References

https://arxiv.org/abs/2312.14016

## Experiment context, if any

LHCb

**Primary authors:** DE OYANGUREN CAMPOS, Arantza (Univ. of Valencia and CSIC (ES)); Dr JASHAL, Brij Kishor (IFIC, Univ. of Valencia, CSIC (ES) and Tata Institute of Fundamental Research (TIFR)); ZHUO, Jiahui (Univ. of Valencia and CSIC (ES)); KHOLOIMOV, Valerii (IFIC - Valencia); SVINTOZELSKYI, Volodymyr (IFIC -Valencia)

Presenter: SVINTOZELSKYI, Volodymyr (IFIC - Valencia)

Session Classification: Track 2: Data Analysis - Algorithms and Tools

Track Classification: Track 2: Data Analysis - Algorithms and Tools