

BGC monitor Phase II: vacuum studies for LHC integration and operation

Cristina Castro Sequeiro TE-VSC-VSM



BGC collaboration meeting - 12.12.2023

Index

- 1. Off-line test campaign
- 2. Simulations
 - H₂O throughput from unbaked chambers and NEG coating saturation
 - N₂ operation: pressure profile, gas exit ratios and NEG coating saturation
 - Ne operation & distributed injections: pressure profile (sim. & measurements), gas exit ratios and deposition on cryogenic surfaces



Off-line test campaign









LHC simulations



LHC simulations – N₂



LHC simulations – N₂



L-LHC PROJEC













Conclusions

- **Pump down and injections characterized** during off-line tests, allowing to obtain **inputs** for the LHC simulations.
- Acceptable compromise between BGC pump down time and estimated saturated length of the beamline with H₂O from unbaked chambers, avoiding the bake-out.
- Significant NEG saturation simulation results due to N₂ injections: 3.7 m both sides in 1 day (smooth surface model -worst case-).
- Good agreement between Ne pressure simulations and measurements without beam or at lower beam intensities.
- Negligible contribution to SEY of Ne monolayers after 100 h of operation in RF cavities (0.07 monolayers, SEY 1E-3) while it is not in the cold bore (19.6 monolayers, SEY 0.28)



Thank you for your attention

