

# Designing a synchrotron - A real life example

**Yannis PAPAPHILIPPOU**

**Accelerator and Beam Physics**

**Beams Department**


**CERN**

**CERN Accelerator School**

**Introduction to Accelerator Physics**

**Santa Susanna, Spain**

**September 22<sup>nd</sup> – October 5<sup>th</sup>, 2024**




The CERN Accelerator School  
in collaboration with ALBA is organising a course on



## INTRODUCTION TO ACCELERATOR PHYSICS

**SANTA SUSANNA, SPAIN**  
22 September - 5 October 2024

The two-week residential course represents the core teaching of all CAS courses, offering the ideal opportunity to delve into the fascinating world of particle accelerators. This course is designed for laboratory and university staff and students, as well as manufacturers of accelerator equipment. It also provides a comprehensive introduction to the fundamental concepts of beam dynamics and underlying accelerator systems. Through engaging lectures, illuminating tutorials, and insightful discussion sessions, participants will deepen their knowledge of crucial topics in the accelerator universe. In addition to the comprehensive curriculum, networking is crucial, as attendees forge connections with fellow students and lecturers working in the field. This opportunity to connect and collaborate is a key aspect of the program, further enhancing its value as an indispensable resource for anyone seeking to expand their understanding of particle accelerators.

Location: Hotel Indalo Park

ALBA  Contact: CERN Accelerator School  
CH - 1211 Geneva 23  
cas@cern.ch  
AcceleratorSchool@cern.ch

- The author consents to the photographic, audio and video recording of this lecture at the CERN Accelerator School. The term “lecture” includes any material incorporated therein including but not limited to text, images and references.
- The author hereby grants CERN a royalty-free license to use his image and name as well as the recordings mentioned above, in order to post them on the CAS website.
- The material is used for the sole purpose of illustration for teaching or scientific research. The author hereby confirms that to his best knowledge the content of the lecture does not infringe the copyright, intellectual property or privacy rights of any third party. The author has cited and credited any third-party contribution in accordance with applicable professional standards and legislation in matters of attribution.

- Review several **aspects of beam dynamics** (mostly) presented in the introductory CAS lectures, applied to the **design and operation of a real synchrotron**


- Review several **aspects of beam dynamics** (mostly) presented in the introductory CAS lectures, applied to the **design and operation of a real synchrotron**
  - Choice of **basic parameters**
    - Energy, bending field and circumference
  - **Optics design**
    - Cell optics, insertions, transition energy
  - **Collective effects**
    - **Instabilities, Space-charge, e-cloud**
  - **Electron/Positron beam dynamics**
    - Equilibrium beam properties, energy loss/turn, damping time

- Our choice is the **CERN Super Proton Synchrotron (SPS)**
- From its design and operation, it has shown enormous **versatility** used for several purposes and serving various applications

- Our choice is the **CERN Super Proton Synchrotron (SPS)**
- From its design and operation, it has shown enormous **versatility** used for several purposes and serving various applications
  - High energy **synchrotron** serving **fixed target** experiments (West Area, North Area, CNGS, HIRADMAT)
  - **Collider** of protons and anti-protons (W and Z bosons discovery in 1983)
  - Accelerating **electrons** and **positrons** and injecting them to the Large Electron-Positron (**LEP**) Collider
  - Accelerating **protons** for the Large Hadron Collider (**LHC**)
  - Accelerating **ions** for **fixed target** physics and the **LHC**
  - Extracting protons for exciting plasma for a **plasma wakefield acceleration** experiment (**AWAKE**)

# Basic parameters: energy, bending field and circumference

- Consider **accelerator ring** for particles with **energy**  $E$  with  $N$  dipoles of **length**  $L$  or **effective length**  $l$ , i.e. measured on beam path





- Consider **accelerator ring** for particles with **energy**  $E$  with  $N$  dipoles of **length**  $L$  or **effective length**  $l$ , i.e. measured on beam path


- **Bending angle**  $\theta = \frac{2\pi}{N}$

- **Bending radius**  $\rho = \frac{l}{\theta}$

- The **magnetic rigidity** is  $B\rho = \frac{\beta E}{q}$

- The **integrated dipole strength** is

$$Bl = \frac{2\pi}{N} \frac{\beta E}{q}$$



- Consider **accelerator ring** for particles with **energy**  $E$  with  $N$  dipoles of **length**  $L$  or **effective length**  $l$ , i.e. measured on beam path

- **Bending angle**  $\theta = \frac{2\pi}{N}$

- **Bending radius**  $\rho = \frac{l}{\theta}$


- The **magnetic rigidity** is  $B\rho = \frac{\beta E}{q}$

- The **integrated dipole strength** is

$$Bl = \frac{2\pi}{N} \frac{\beta E}{q}$$

- By imposing a **dipole field**, the **dipole length** is **fixed** and vice versa

- The **higher** the **field**, the **shorter** or **less dipoles** can be used



- The **filling factor**, is defined as the ratio of the total length of the bending path, with respect to the circumference

$$k_f = \frac{Nl}{C}$$

- The **filling factor**, is defined as the ratio of the total length of the bending path, with respect to the circumference

$$k_f = \frac{Nl}{C}$$


- The ring **circumference** becomes

$$C = \frac{2\pi}{k_f B} \frac{\beta E}{q}$$

- The ring **circumference (cost)** is driven by the bending **field** choice (**technology**), the **energy** reach (**physics** case, applications) and the design of the **lattice cells** (optics)

- The **maximum** possible **circumference** between the CERN I (Meyrin) and CERN II (Prevessin) site was



$$C_{SPS} = 11C_{PS} = 2\pi \times 1100 \text{ m} \approx 6912 \text{ m}$$



- Combined function magnets with **1.2 T** field (PS-like) would give an energy of no more than **~260 GeV** for a highly packed lattice

- The **maximum** possible **circumference** between the CERN I (Meyrin) and CERN II (Prevessin) site was



$$C_{SPS} = 11C_{PS} = 2\pi \times 1100 \text{ m} \approx 6912 \text{ m}$$



- Staged approach with **1.8 T dipoles** could reach from 200 to 400 GeV

- The maximum possible circumference between the CERN I (Meyrin) and CERN II (Prevessin) site was



$$C_{SPS} = 11C_{PS} = 2\pi \times 1100 \text{ m} \approx 6912 \text{ m}$$



- SPS dipoles have been pushed to beyond **2 T** to reach **450 GeV**

- The maximum possible circumference between the CERN I (Meyrin) and CERN II (Prevessin) site was

$$C_{SPS} = 11C_{PS} = 2\pi \times 1100 \text{ m} \approx 6912 \text{ m}$$



- SPS dipoles have been pushed to beyond **2 T** to reach **450 GeV**



- Super-conducting** option could raise the energy to **1 TeV**




# Optics design and Magnet system

- **FODO cell** of around **65 m** long with phase advances of  $\pi/2$
- **Beta function maxima** slightly above **100 m**


The 300 GeV Program, CERN/1050, 14/01/1972




- Magnet apertures follow beta function and dispersion evolution





**Dipole B1**



**Dipole B2**



**Quadrupole F**



**Quadrupole D**

- **744 dipoles** (MBAs and MBBs) with 6.26 m length and different gaps

Number of magnets	744
Year of 1 <sup>st</sup> operation	1976
Maximum field on beam axis [T]	2.02
Physical vertical aperture [mm] MBA/MBB	38.5/51.5
Yoke assembly [Solid,Laminated,Welded,Glued]	L,W
Coil technology [Copper,Aluminium,Glass-epoxy,Mica,Other]	C,G
Maximum voltage to ground [V] (worst case 2 spare converters)	4150
Operation	Cycled
Maximum cooling water velocity [m/s]	9
Operational temperature [C°]	40



## D. Tommasini CERN/TE-Note-2010-003

- Maximum field of **2.02 T**, for reaching 450 GeV
- High mechanical stress on coils

- **216 quadrupoles** (102 QF, 100 QD, 6 QFA and 8 QDA)
- Maximum **gradient** of **22 T/m**, corresponding to a pole-tip field of around **1 T**
- Normal operation necessitates almost the **full gradient @ 450 GeV**

D. Tommasini CERN/TE-Note-2010-003

Number of magnets	216
Year of 1 <sup>st</sup> operation	1976
Maximum gradient [T/m]	22
Physical vertical aperture [mm]	88
Yoke assembly [Solid,Laminated,Welded,Glued]	L,W
Coil technology [Copper,Aluminium,Glass-epoxy,Mica,Other]	C,G
Maximum voltage to ground [V]	3450
Operation	Cycled
Maximum cooling water velocity [m/s]	3.6
Operational temperature [C°]	40




M. Giesch, CERN/SPS/80-3/AMS, 1980

MAIN PARAMETERS OF SEXTUPOL		LSFN	LSDN
Basic	: Nominal rms current [A]	350	350
	Peak Current [A]	500	450
* Strength at peak current			
	1) Sextup. $\int a_3 dl$ ( $a_3 = B''/r_2 = B''/2$ ) [T/m]	85.8	176.6
		$n^2$	
	* Magnetic length [m]	0.435	0.426
	Aperture, radius of inscr.circle [mm]	60.7	44.0
Core	: Length [m]	0.4	0.4



- **54 “focusing”** and **54 “defocusing”** sextupoles in two (three for F) families (24 and 30), with different apertures
- Maximum pole-tip field of around **0.8 T**
- Around 80% and 60% in operational conditions




- **Dispersion** has to be **eliminated** in **special areas** like injection, extraction or interaction points (orbit independent to momentum spread)
- Use **dispersion suppressors**
- Methods for suppressing dispersion
  - **Eliminate two dipoles** in a FODO cell (missing dipole)
  - Set last dipoles with **different bending angles**


$$\theta_1 = \theta \left( 1 - \frac{1}{4 \sin^2 \mu_{\text{HFODO}}} \right)$$

$$\theta_2 = \frac{\theta}{4 \sin^2 \mu_{\text{HFODO}}}$$

- For **equal bending angle** dipoles, the FODO phase advance should be equal to  **$\pi/2$**










- In the SPS, all **dipoles** are powered in **series**, i.e. dispersion suppressor cells looks like a missing dipole, but they are not!

- Dispersion suppression is achieved by tuning the **phase advance** of the arc, to a **multiple of  $2\pi$**

- **Dispersion oscillates** through the arc and vanishes at the edges




- Ring is composed by **6 identical sectors** (“sextants”) with **16 arc cells** and **2 cells** in the **straight sections**
- The cell phase advance of  $\pi/2$  brings the tunes between 26-27 (**Q26**)



- Replace two straight section quadrupoles with **2 doublets** (4 quadrupoles)
- Equip adjacent **left/right quadrupoles** with individual bipolar **power convertors**
- Achieved **low  $\beta^*$**  of 1.3/0.65 m

P. Faugeras et al., CERN-SPS-80/11, CERN-SPS-83/29




- Repla with :
- Equip with :
- Achie



Photo from the Nobel Foundation archive.  
**Carlo Rubbia**  
 Prize share: 1/2




Photo from the Nobel Foundation archive.  
**Simon van der Meer**  
 Prize share: 1/2



rupoles

**poles**  
**vertors**



The Nobel Prize in Physics 1984 was awarded jointly to Carlo Rubbia and Simon van der Meer "for their decisive contributions to the large project, which led to the discovery of the field particles W and Z, communicators of weak interaction"

# Transition energy and slippage factor

- Transition “energy” (or momentum compaction factor) is defined as

$$\frac{1}{\gamma_t^2} = \alpha_p = \frac{1}{C} \oint \frac{D(s)}{\rho(s)} ds$$

- The **higher** the **dispersion oscillation** in the bends, the **lower** the **transition energy**



**Quadrupoles**

- Transition “energy” (or momentum compaction factor) is defined as

$$\frac{1}{\gamma_t^2} = \alpha_p = \frac{1}{C} \oint \frac{D(s)}{\rho(s)} ds$$


- The **higher** the **dispersion oscillation** in the bends, the **lower** the **transition energy**



## Quadrupoles


- Note also that, for FODO cells (SPS lattice),  $\gamma_t \approx Q_x$ , meaning that lowering the transition energy implies **lowering** the **horizontal tune**
- High intensity beams can be injected in the SPS **above transition** avoiding losses and operational complexity of transition jump scheme

$\gamma_t$  in the SPS



- Resonant oscillation of dispersion function close to the “Resonant integer tunes” (multiples of **super-periodicity 6**) → asymptotic behavior of  $\gamma_t$ , (difficult for routine operation)
- $\gamma_t$  is a linear function of horizontal tune  $Q_x$  elsewhere







- Resonant oscillation of dispersion function close to the “Resonant integer tunes” (multiples of **super-periodicity 6**) → asymptotic behavior of  $\gamma_t$ , (difficult for routine operation)
- $\gamma_t$  is a linear function of horizontal tune  $Q_x$  elsewhere

- Nominal SPS working point for LHC proton beams ( $\gamma_t \sim 23$ )
- D. Boussard et al., SPS improvement note No 147, 1978; Injection above transition as TT10 was not ready for 26 GeV/c ( $\gamma_t \sim 14$ )
- G. Arduini et al., CERN/SL-Note 98-001, 1998; “Resonant tune” ( $\gamma_t \sim 20$ )
- YP, H. Bartosik et al., Low  $\gamma_t$ , 2010 - “Resonant arc” with small dispersion in long straight sections ( $\gamma_t \sim 18$ )

- Injection beam line **TT10** has not been upgraded to 26 GeV in 1978 and limited to **16 GeV**
- **Injection above transition** is possible if SPS integer part of the tune is lowered to 15 ( $\gamma_t \sim 14$ )

D. Boussard et al., SPS improvement note No 147, 1978



# Manipulating optics for curing instabilities

## □ **Transverse** instabilities

- **TMCI** at injection - single bunch instability in vertical plane
  - Threshold at  $1.6 \times 10^{11}$  p/b ( $\epsilon_l = 0.35$  eVs,  $\tau = 3.8$  ns) with low vertical chromaticity

$$N_{th} \propto \frac{\epsilon_l}{\beta_y} \eta$$

- **E-cloud** vertical instability for 25 ns beam
  - Threshold higher than  $1.2 \times 10^{11}$  p/b

$$N_{th} \propto Q_s \propto \sqrt{\eta}$$

## □ **Longitudinal** instabilities




- Single bunch and coupled bunch
  - Threshold at  $2 \times 10^{10}$  p/b for single harmonic RF (800 MHz cavity use is mandatory)

$$N_{th} \propto \epsilon_l^{5/2} \eta$$



Moving FODO phase advance from  $4/16 \cdot 2\pi$  ( $\pi/2$ ) to  $3/16 \cdot 2\pi$  ( $3\pi/8$ )

$$\eta = \frac{1}{\gamma_t^2} - \frac{1}{\gamma^2} \quad \longleftrightarrow \quad \gamma_{tFODO} \approx Q_x$$

Slippage factor increased by a factor of **2.8** at **injection** and **1.6** at **flat top**




Slip factor relative to nominal SPS optics <sup>57</sup>




## Measurement of the optics functions of the new lattice

- Beta beating** around 20% in horizontal and 10% in vertical plane
- Normalized **dispersion** in striking agreement with the model

- ❑ Measured synchrotron frequency from “quadrupole” oscillations at injection
  - ❑ Same RF-voltage for both optics
- ❑ Ratio of Synchrotron frequencies  $\sim$  **1.63** corresponds to an **increase in slippage factor  $\eta$  by factor 2.65** (MADX prediction: 2.86)







Q26:  $F_s = 458/2 = 229\text{Hz}$ ,  
 $Q_s = 0.0106/2 = 0.0053$



Q20:  $F_s = 746/2 = 373\text{Hz}$ ,  
 $Q_s = 0.0172/2 = 0.0086$



- ❑ In **nominal optics**, measured/simulated threshold at  **$1.6 \times 10^{11} \text{ p/b}$**  for low chromaticity
  - ❑ High-chromaticity helps increasing threshold, but also losses along the cycle become excessive
- ❑ Measured/simulated threshold in **Q20** >  **$4 \times 10^{11} \text{ p/b}!!!$**

$$N_{th} \propto \frac{\epsilon_l}{\beta_y} \eta$$



H. Bartosik et al,  
IPAC 2014






$$N_{th} \propto Q_s \propto \sqrt{\eta}$$

- ❑ Simulations with HEADTAIL code
  - ❑ Injection energy, uniform cloud distribution, located in dipole regions
- ❑ Linear scaling with Synchrotron tune demonstrated
  - ❑ Clearly higher thresholds predicted for **Q20**



**More margin with Q20 if e-cloud becomes issue for high intensity**

H. Bartosik et al, IPAC2011


T. Argyropoulos et al.




SPS-Q20 ( $1.6 \times 10^{11}$  p/b)  
double harmonic RF




SPS-Q26 ( $1.6 \times 10^{11}$  p/b)  
double harmonic RF



- Operational deployment of Q20 optics for LHC beams since 2012 allowing around **20% brighter beams on LHC flat bottom**
- Opened way for **ultra-high brightness beams** of HL-LHC era



# Non-linear dynamics



● proton working point

● ion working point

resonances:

red: systematic

blue: non-systematic


– upright

- - skew


H. Bartosik et al. HB2018

## ■ Dynamic tune scan for identification of resonances

- Losses around 3<sup>rd</sup> order (normal) resonances and the diagonal clearly observed
- Faint traces of 4<sup>th</sup> order resonances
- Operational working point for protons 20.13/20.18 (moved up for high brightness beams)



M. Carla' et al. IPAC2018





Sextupoles

$$Q = \underbrace{Q_0}_{\text{Quadrupoles}} + \underbrace{Q' \left(\frac{\delta p}{p}\right)}_{\text{Octupoles}} + \underbrace{Q'' \left(\frac{\delta p}{p}\right)^2}_{\text{Decapoles}} + Q''' \left(\frac{\delta p}{p}\right)^3 + \dots$$

- Estimate “effective” magnet multi-poles that reproduce non-linear chromaticity measurement for three different optics

# Space-charge

emittance at end of flat bottom





## Vertical tune scan with high brightness beam for 10 s storage time

- $N = 1.95 \times 10^{11}$  p/b (at injection)
- $\epsilon \sim 1.1 \mu\text{m}$  (at injection)
- Transmission to flat top around 94% (very small losses on flat bottom)

$$\Delta Q_x / \Delta Q_y \sim 0.10 / 0.20$$



## emittance at end of flat bottom



## Vertical tune scan with high brightness beam for 10 s storage time


- $N = 1.95 \times 10^{11}$  p/b (at injection)
- $\epsilon \sim 1.1 \mu\text{m}$  (at injection)
- Transmission to flat top around 94% (very small losses on flat bottom)

$$\Delta Q_x / \Delta Q_y \sim 0.10 / 0.20$$


- Tune scan with high brightness single bunch beam for **3 s storage time**
  - Blow-up at integer resonances as expected (tune spread  $\Delta Q_x, \Delta Q_y \sim 0.10, 0.19$ )
  - **Margin for higher brightness for working points in white box** (enhanced losses only close to  $Q_x + 2Q_y = 61$  normal 3<sup>rd</sup> order resonance and around  $4Q_x = 81$  normal 4<sup>th</sup> order resonance)

H. Bartosik et al. 2018

measurements




measurements




# Electron-positron dynamics


## P. Collier – Academic Training 2005




- LEP filling interleaved with proton operation
- 4 cycles with 4 bunches ( $2e^+$ ,  $2e^-$ ) evolved to 2 cycles with 8 bunches ( $\sim 2.5 \times 10^{10}$  p/b)
- Energy to LEP: 18  $\rightarrow$  20  $\rightarrow$  22 GeV
- Lots of RF for leptons (200MHz SWC, 100MHz SWC, 352MHz SC),
- 2 Extractions in Point 6 towards LEP



LEP design report 1983





- Energy loss/turn necessitate **large RF voltage** (30 MV) at high energy
- Impact of a 2-m **3.5T damping wiggler** is mild at high energies



- Damping time at injection (3.5 GeV) very large (9 s)
- A 2-m 3.5T **damping wiggler** could enhance damping for low energies to below 1 s (good for instabilities)

- Move horizontal phase advance to 135 deg. i.e.  $3\pi/4$  (**Q40 optics**) which is optimal for low emittance in a FODO cell
- **Emittance with nominal optics @ 3.5 GeV of 3.4 nm drops to 1.3nm**
- Further reduction can be achieved with damping wiggler



- Using the **~50 years experience** since the design and operation of the Super Proton Synchrotron (SPS), reviewed **several beam dynamics concepts**
  - Choice of basic parameters
    - Energy, bending field and circumference
  - Optics design
    - Cell optics, insertions, transition energy
  - Collective effects
    - Instabilities, Space-charge, e-cloud
  - Electron/Positron beam dynamics
    - Equilibrium beam properties, energy loss/turn, damping time