
# HalfShell Clamping, Cycling and testing in Liverpool (all Layers)

Helen Hayward, Tim Jones


# Liverpool LSDC

- Liverpool LSDC has several rooms, which will be used for different activities.
- We are limited on space, with no room to expand.




# Map of clean room

- Space inside cleanroom is limited
- Assume we have 4 cradles to maintain schedule
  - i.e. if L2 rings are late we can proceed installing L3 services..
- The ring insertion area is close to climate chamber for easy access.
- Exact placement of the central integration support tool is needed to ensure space to transfer cradles from "service-area" to "ring-insertion area"
- The full blue-base and central station can not move until its conversion into the transport box.





# Clamping layers together

12 connectors per Layer L2/L3 connectors on outside L4 connectors on inside




### Zooming in....





#### Detail....




#### Can cut-out in cylinder only required for L4 A bespoke tool is needed for L4 where connector is on the inside

Could cut-out be used with endoscope to help spot issues during alignment?

01/02/2024

# Mating of half-shells

- Testing of mating of bare shells already occurred
- Move both LH and RH trolleys to central assembly
- Check alignment with laser tracker.
- Services transferred separately to services trolley
- Connectivity warm-test with LP
  - 1 module per SP
  - To be demonstrated LP + convective cooling works on closed layer
  - Option: to test whilst layers are a few cm apart? (but after services transferred).
    - Does this teach us anything?
  - Does the service cradle move (rotate) independently to half cylinder cradle?



## Can we cold test each mated layer?


- If we wanted to cool with CO<sub>2</sub> at  $T_{ev}$ ~+15C
  - Check distance from Lukasc
    - ~7m
  - Or auxillary chiller?
    - Only possible to chill environment inside enclosure
  - Possibility of secondary "tent" enclosure with dry air.?
  - The enclosure has to be within footprint of blue base
- Need to incorporate time into schedule to construct enclosure per layer




# Complete layer ready

Orbital welder: Swagelock M200


Q: how exactly to leak test?




- Move trolley in the mating area
- Weld the manifolds of the individual HS here
- Leak test
- Pressure test 162 bar
  - Compressed Dry Air/Argon (TBD)
- Leak test



# Completed Endcap




- All mainfolds are welded →CO2 flux reduced by 2
- Final reference warm test to be compareted with reception test at SR1:
  - Low power mode: To be demonostrated that LP + convective cooling works on closed layer






# Dispatch



- Transport box to be built around EC and blue-base (blue base is floor of transport box?)
  - LxWxH=4250mmx 2200mmx 2000mm
  - Dispatch doors 3000x3000
- Slide transport box into LSDC via airskates
  - Jack end cap up
  - Design for blue base must incorporate recess and/or fixings and qualified for toe-jack lifting
- Slide transport box base under EC
- Blue base coupled to transport box via coupling springs
- Construct shipping box around EC
- Use air-skates to transport to loading bay
- Forklift (from shipping company) loads into truck.
  - Alternative workshop crane (check ceiling height).

# Dispatch



- Transport box to be built around EC and blue-base (blue base is floor of transport box?)
  - LxWxH=4250mmx 2200mmx 2000mm
  - Dispatch doors 3000x3000
- Slide transport box into LSDC via airskates
  - Jack end cap up
  - Design for blue base must incorporate recess and/or fixings and qualified for toe-jack lifting
- Slide transport box base under EC
- Blue base coupled to transport box via coupling springs
- Construct shipping box around EC
- Use air-skates to transport to loading bay
- Forklift (from shipping company) loads into truck.
  - Alternative workshop crane (check ceiling height).