

The Diamond Beam Monitor for Luminosity Upgrade of ATLAS

Monday 3 September 2012 14:40 (20 minutes)

Luminosity monitors, beam monitors and tracking detectors of the experiments at the Large Hadron Collider and their upgrades must be able to operate in radiation environments several orders of magnitude harsher than those of any current detector. We have observed in ATLAS that as the environment becomes harsher, detectors not segmented, either spatially or in time, have difficulty handling the separation of signal from background. Once the charged particle multiplicity reaches the point where all segments of these detectors have a high probability of having a hit in every bunch crossing their sensitivity quickly vanishes. This is already happening in ATLAS to the MBTS luminosity counters that will be removed in the 2011 year-end shutdown and LUCID luminosity counters. Chemical Vapor Deposition (CVD) diamond has a number of properties that make it an attractive alternative for high energy physics detector applications. Its large band-gap (5.5 eV) and large displacement energy (42 eV/atom) make it a material that is inherently radiation tolerant with very low leakage currents and high thermal conductivity. CVD diamond is being investigated by the RD42 Collaboration for use very close to LHC interaction regions, where the most extreme radiation conditions are found. The ATLAS Diamond Beam Monitor project (DBM) is a highly spatially segmented diamond-based luminosity monitor to measure bunch-by-bunch luminosity in ATLAS. The DBM will complement the highly time-segmented ATLAS BCM so that when the other ATLAS luminosity monitors (MTBS and LUCID) have difficulty functioning the ATLAS luminosity measurement which is a key to most precision measurement is not compromised. The DBM will provide three orders of magnitude higher spatial segmentation (relative to the single BCM pads) at the expense of lower (25 ns vs sub-2 ns) time resolution. However these two systems will complement one and each other in our characterization of the beam backgrounds. The BCM will still use its exquisite timing resolution to localize beam background sources up (or down) stream of ATLAS, while the DBM will provide additional spatial information about the source(s) of background. To accomplish these goals, the DBM architecture is four 3-layer telescopes on each side of the interaction point with each layer having the size of one FE-I4 module, namely 20mm x 16.8mm active area. The first and last layers of the telescope are offset so that particles from both the ATLAS interaction point and beam halo background can be tracked. It is foreseen to install the DBM during the long shutdown of LHC in 2013/14 together with the ATLAS Insertable B-Layer (IBL) upgrade of the pixel detector. DBM shares a lot of parts with the IBL project mainly in off detector area. The development of the DBM components are well advanced and the project enters now the production phase to be ready for integration in 2013. Several DBM modules made of a FE-I4 readout chip bump bonded to a CVD diamond have been built and tested in laboratory and test beams. The results from these prototype detectors and status of other project components like mechanics and readout will be presented.

Author: KAGAN, Harris (O)

Presenter: KAGAN, Harris (O)

Session Classification: Session2

Track Classification: Particle physics applications - High Energy Physics