

## Planar pixel detector module development for the HL-LHC ATLAS pixel system

*Friday, 7 September 2012 11:10 (20 minutes)*

The ATLAS pixel detector for the HL-LHC will require the development of large area pixel modules that can withstand doses up to  $2 \times 10^{16}$  neq  $\text{cm}^{-2}$ . The area of the pixel system will be over  $5 \text{m}^2$  and as such low cost, large area modules are required. The development of a quad module based on 4 FE-I4 ROIC will be discussed. The FE-I4 ROIC is a large area chip and the yield of the flip-chip process on single chips and the quads is covered. The readout of the quad module for laboratory tests will be reported. To reduce mass of the system the assembly will be required to be as thin as possible and the insensitive edges of the sensors also need to be reduced to a minimum. The thin edge is achieved by reducing the physical edge of the sensor and by the use of through-silicon vias to move the wire bond pads from the edge of ROIC to its backside. Progresses in these areas are discussed.

**Primary author:** BATES, Richard (University of Glasgow (GB))

**Co-authors:** Dr BLUE, Andrew (University of Glasgow); STEWART, Andrew (U); BUTTAR, Craig (University of Glasgow (GB)); FORSHAW, Dean Charles (University of Liverpool-Unknown-Unknown); CASSE, Gianluigi (University of Liverpool (GB)); TSURIN, Ilya (University of Liverpool (GB)); PATER, Joleen (University of Manchester (GB)); Mr ASHBY, Joseph (University of Glasgow); DOONAN, Kate (University of Glasgow (GB)); DERVAN, Paul (University of Liverpool (GB)); Dr BROWN, Simon (University of Manchester (GB))

**Presenter:** BATES, Richard (University of Glasgow (GB))

**Session Classification:** Session8

**Track Classification:** Pixel technologies - Hybrid pixels