



14th HL-LHC Collaboration Meeting
Genoa - 9th October 2024

Update on the Beam Gas Ionisation (BGI) Profile Monitor

J. Storey, W. Andreazza, D. Bodart, H. Bursali, G. Cabrera, W. Devauchelle,
G. Le Godec, S. Jensen, J. Joul, G. Khatri, M. Mclean, C. Pasquino, M. Teresa Ramos Garcia



Thanks to: M. Navarro Baeza, C. Fleisig, S. Gibson, M. Gonzalez Berges, S. Jackson,
S. Levasseur, T. Lefevre, H. Sandberg, G. Schneider, R. Veness, C. Vollinger

Outline

- **Introduction**
 - Functional Specification
 - Principle of Beam Gas Ionisation (BGI) Profile Monitor
- **BGI Design Studies**
 - Field Cage & Ionisation Electron Detector
 - Impedance Studies
 - Magnet
 - Integration
 - Expected Performance
- **PS & SPS BGI Experience & Implications for LHC BGI Design**
 - Performance of the PS & SPS BGI's
 - Technical Issues: Readout Architecture & EMI
- **Milestones & Timeline**

Functional Specification

Independent measurement of transverse **beam profile evolution** throughout the acceleration cycle.

Original functional specification “Measurement of the Beam Transverse Distribution in the LHC Rings (LHC-B-ES-0006)”, reviewed at “[LHC Beam Size Measurement Review](#)” (Oct. 2019.)

Specifications for HL-LHC:


Beam measurements (average over all bunches)

- Accuracy (systematic error) < 5%;
- Precision / reproducibility of about ~1%;
- Frequency > 10 Hz.

Bunch-by-Bunch measurements

- Precision / reproducibility of about ~1%;
- Frequency < 1 min. for all bunches.

Principle of Operation



1. Beam ionises **residual gas**;
2. **Ionisation electron** accelerated & transported by electromagnetic fields onto detector;
3. Electron detector = **Timepix3(/4)** Hybrid Pixel Detector.



Ionisation Electron Detection with Timepix3/4

Timepix3(/4) Hybrid Pixel Detector optimized for **10 keV electron detection** inside the beam pipe

Charge > Threshold → Event, consisting of:




- Pixel position → **Where** ($\sigma_{\text{position}} < 16 \mu\text{m}$)
- Time of Arrival (ToA) → **When** ($\sigma_{\text{time}} = 1.6 \text{ ns} / 200 \text{ ps}$ for TPX4)
- Time-Over-Threshold (ToT) → **~Energy**

Single electron detection & digitisation directly inside the beam pipe.




Beam Profile Measurement

Measure beam profile by **counting** the number of **ionisation electrons** detected in each column.




Existing BGI's based on Timepix3


- PS BGI-Horizontal & BGI-Vertical profile monitors installed in LS2
- SPS BGI-Horizontal installed during YETS 23/24, SPS BGI-Vertical to be installed YETS 24/25



PS BGI-Vertical



Field cage + Faraday cage



UHV compatible Timepix3 electronics

LHC BGI (2007-2018): MCP/Optical Based

BGI's were originally installed in the LHC, but removed in 2017/18 due to damage to the instruments caused by **beam induced heating**.

Original design based on detection of ionisation electrons with a Microchannel Plate (MCP) + Phosphor Screen + Optics + Intensified Camera.

Technical Limitations:

- **Impedance** no problem for beam, but 260W power into instrument;
- **Inhomogeneous ageing** of MCP / Phosphor / Intensified camera

Performance Limitations:

- **Distortion** to measured profile at $E > 4$ TeV;
- **Not an independent measurement**, due to need to cross-calibrate with BWS to remove optical aberrations (PSF of optics).

HL-LHC BGI: Timepix Based

Compact design based on **direct detection of ionisation electrons inside the beam pipe** with a **Timepix HPD**. Electrons guided to detector with **0.6T magnetic field**.

Technical Limitations (HL BGI solution):

- **Impedance** no problem for beam, but 260W power into instrument; → **Compact low impedance design with active cooling**.
- **Inhomogeneous ageing** of MCP / Phosphor / Intensified camera. → **Replaced with Timepix3/4 HPD**.

Performance Limitations (HL BGI solution):

- **Distortion** to measured profile at $E > 4$ TeV; → **Higher strength guiding magnetic field**.
- **Not an independent measurement**, due to need to cross-calibrate with BWS to remove optical aberrations (PSF of optics). → **Direct detection inside beam pipe (no optics)**.



HL-LHC BGI Design Studies

Circular Flange

Circular chamber

Timepix4



1



Rectangular chamber

Timepix4

2





Rectangular Flange

Rectangular chamber

Timepix4



3



Rectangular chamber

Timepix3 or 4

4




HL-LHC BGI Instrument Design

- **Baseline** evolution of PS & SPS BGI design.
- **Familiar design** with known, but hopefully improvable, limitations.
- Beam aperture restriction = 50 mm.
- Compatible with both Timepix3 & Timepix4.

*Instrument mounted
on rectangular flange*

*Cathode with ion
trap (-30kV)*




beam

*Faraday cage for
Timepix electronics*

RF damping rods



Impedance Studies



Best design so far:

- Stainless steel cathode;
- Damping rods;
- Cathode 200 x 200 mm.

Longitudinal impedance & power loss okay.
Optimisation ongoing.




0.6T Magnet - New Triplet Dipole

BGI design presented at [HL BGV/BGI Review in Oct. 2022](#) based on new **self-compensating triplet dipole magnet**.


Separate power converters (Polaris 2P) for Main & Corrector fields.

Recommendation of reviewers to investigate:

- Permanent magnet solution;
- Reducing number of (costly) power converters.



LHC BGI magnet



B field along the beam axis


0.6T Magnet - New Dipole + MDX Correctors

Permanent Magnet


- Designs studied by TE-MSU;
- Instrument integration very challenging;
- Not pursued.

Current Solution: New Dipole + MDX Correctors


- New 0.6T main dipole magnet for instrument;
- Correction with existing MDX magnets;
- Possibility to re-use existing power converters;
- Significant potential budget saving.



Integration at Pt.4




5L4 - BGI-Horizontal & Vertical on B1



5R4 - BGI-Horizontal & Vertical on B2

Integration at Pt.4

Proposed integration layout




Installation planning with TE-VSC:

- Reconfiguration of vacuum components to take place at beginning of LS3, initially with drift tubes in place of the BGI instruments;
- Installation of BGI instruments later in LS3.

Expected Performance: Precision & Accuracy

Simulation Workflow:


- Electrostatic simulation of field cage with CST Studio;
- Simulation of ionisation electron formation & transport to electron detector with Virtual-IPM.



- For each simulation calculate residual = true beam size – measured beam size.


Expected Performance: Precision & Accuracy

Statistical error (precision)
= standard deviation of residual distribution



e.g. single measurement with 2000 ionisation electrons → 2 % statistical error.

Systematic error (accuracy)
= mean of residual distribution



Negligible systematic error due to field cage, space charge, Timepix3 pixel pitch.

Expected Performance

Performance estimates for beam profile measurements with **residual gas pressure** of 1×10^{-10} mbar (**no gas injection**) & assuming same ionisation electron detection efficiency as PS BGI instrument:

HL-LHC protons

- Average beam size: Integration window = 0.5 ms \rightarrow 5000 e^- \rightarrow Precision = 1%
- Bunch-by-bunch beam size: Integration window = 1 s \rightarrow 5000 e^- \rightarrow Precision = 1%
- Accuracy < 2 %

HL-LHC Pb82+


- Average beam size: Integration window = 0.05 ms \rightarrow 5000 e^- \rightarrow Precision = 1%
- Bunch-by-bunch size: Integration window = 100 ms \rightarrow 5000 e^- \rightarrow Precision = 1%
- Accuracy < 2 %

Expected performance meets functional specification.


Accuracy of PS BGI Measurements

In practice - how well does performance meet expectation?

Example: Measurement of **LHC-type beam at flat top** with both **PS BGIs** (1.9 ms int.), **without gas injection**.





PS BGI-Horizontal



PS BGI-Vertical

Accuracy of PS BGI Measurements

- Measure at same moment in the cycle with the Beam Wire Scanners (BWS)'s & then compare the emittance measured by the BGI and BWS:



- Emittances measured by the BGI and BWS are in agreement, as expected from the Virtual-IPM simulation.

Technical Issues

Timepix3 based BGI instruments are not yet operational.

Two main issues: 1) Processing of Timepix3 data; 2) **EMI of SPS BGI Timepix3.**

Recent CERN internal review - "[PS & SPS BGI Review](#)".


(Selected) Review Panel Recommendations:

1. *“Fully support proposal to move [Timepix data] processing from SoC towards a powerful server computer.”* → This is the architecture originally planned for the LHC BGI.
2. *“EMI issues are a significant problem, and we note that the project is taking this seriously and requesting outside expertise from the EMC forum.”* → Highly relevant to the LHC BGI and needs to be solved.

SPS BGI: Results after YETS 23/24

Measurement of single LHC bunch (LHC4) at flat-top

- Integration window = 2 ms;
- Recorded 24,000 electrons in this integration window.



Fit results

Gaussian:

- sigma: 0.751 ± 0.006 mm
- reduced $\chi^2 = 15.6$

q-gaussian:

- sigma = 0.589 ± 0.004 mm
- q = 1.374 ± 0.008
- reduced $\chi^2 = 5.8$

Looks promising...

Loss of Communication with Timepix3 during LHC25 & AWAKE Cycles

Background - Timepix3 data readout

- Data from Timepix3 is readout on 8 x differential pairs (“*dataouts*”) @640 MHz.
- Header (“comma”) sent periodically by Timepix3 on each *dataout* link.

Problem

- During LHC25 & AWAKE cycles synchronisation with the *dataout* links is lost (i.e. comma is not recovered) → can’t readout the data.
- Communication is recovered after reconfiguring the Timepix3’s.

Cause

- Suspect EMI problem is causing the Timepix3 to reset.


SPS BGI EMI Studies

Current Investigations:

1. Beam based measurements (what cycles perturb Timepix3 & when.)
2. Measurements at the **ATS EMC lab**.
3. **Improve Faraday cage** design for the SPS BGI-Vertical, which will be installed during YETS 24/25.

Clue = Communication lost during AWAKE cycle immediately **after bunch rotation**, at which time:

- Bunch length reduced to 0.9ps → Higher frequencies in the power spectrum enhanced;
- Higher frequencies pass through Faraday cage & perturb electronics(?)



CST Simulation of SPS BGI eignemodes. Strong mode at 1.4 GHz inside Faraday cage (Study by Hikmet Bursali)

Milestones & Timeline upto LS3

Milestone	Date
Engineering specification for BGI readout system	End of 25
Installation of SPS BGI-Vertical with improved Faraday cage	YETS 24/25
Installation of new infrastrure at Pt.4 & Timepix3 BLM	YETS 24/25
Global emittance monitoring review	Mid-2025
Installation of prototype HL-LHC BGI instrument	YETS 25/26

Summary & Outlook

The HL-LHC BGI has the potential to provide **independent, non-destructive bunch-by-bunch transverse beam profile measurements throughout the acceleration cycle.**

Building on experience of PS and SPS BGI developments.

Design status:

- Mechanical design & integration well advanced;
- Impedance & beam induced heating under control;
- Magnet design optimised to reduce cost.

Top priority is to solve EMI issue in the SPS.

Thanks!