



KM3NeT deep-sea cabled network: the star-like layout

R. Cocimano

for KM3NeT Consortium
on the behalf of KM3NeT PPM work package H

VLVnT11 12-14 October 2011, Erlangen



Talk Outline

- KM3NeT Seabed Network Star-like layout
 - Input Data and Main Components
 - Electro-Optical Cable Specifications
 - Power System and Calculation Results
- Primary Junction Box Block Diagrams
- Secondary Junction Box Block Diagrams
- ODI Connector Systems
- Medium Voltage Converter



KM3NeT Seabed Network Layout

KM3NeT is a subsea cabled observatory it is designed to operate for 20 years as permanent infrastructure on the sea-floor providing continuous power and communication to scientific instruments for neutrino detection and deep-sea science.

The TDR describes two possible solutions for the sea-bed network :

- STAR LAYOUT
- RING LAYOUT

This presentation focus on the **STAR SOLUTION** and in particular on the **POWER SYSTEM** and the **TECHNOLOGICAL CHOICES** related to it.



Star-like Network Layout: Main Components

✓ ON SHORE :

◆ Power Feeding Equipment (PFE) :

- delivers power to the submarine apparatus
- Voltage Converter: 400Vac 3 phase / 10 kVdc

✓ OFF SHORE :

◆ Main Electro Optical Cable (MEOC):

- transmits power and communication to the apparatus

◆ Primary Junction Box (PJB):

- steps down the voltage from 10 kVdc to 400 Vdc
- distribute power and communication to the secondary nodes

◆ Horizontal Electro-optical Cables (HEOC):


- connects electro-optically the PJB to the SJB

◆ Secondary Junction Boxes (SJB):

- distribute power and communication to 8 DUs

◆ Interlink Cables (IL)

- connects electro-optically the SJB to the DU




Star-like Network Layout: Power System

✓ DC POWER NETWORK:

- ◆ **Transmission** Power System (from the shore station to the PJB) :
DC monopolar @ 10 kV
 - the MEOC copper conductor is energized at -10 KV
 - positive electrode on shore
 - negative electrode off-shore

- ◆ **Distribution** Power System (from the PJB to the DU) :
DC bipolar @ 400 V





Star-like Network Layout: Power Inventory


POWER INVENTORY for a BUILDING BLOCK (104 DUs)

COMPONENT	POWER / COMPONENT	POWER/ BUILDING BLOCK
DOM	8,7 W	
DU (40 DOMs)	348 W	36 kW
DU local control	10 W	1 kW
SJB internal load	100 W	1,3 kW
PJB internal load	300 W	0,3 kW
Associated Science	10 kW	10 kW
		48,6 kW




Star Detector Layout: cable specifications


CABLE	ROUTE	LENGHT	COPPER WIRES	QTY	QTY/km
MEOC MAIN ELECTRO OPTICAL CABLE	shore - PJB	100 km	1 copper conductor 1,5 Ω/km	1	100 km
HEOC HORIZONTAL ELECTRO OPTICAL CABLE	PJB - SJB	1000-2000 m	2 x 16 mm ²	14	20 km
IL INTERLINK CABLE	SJB - DU	100-350 m	2 x 16 mm ²	104	25 km
VEOC VERTICAL ELECTRO OPTICAL CABLE	DU backbone (2 VEOC per DU)	880 m	2 x 18 AWG	208	200 km



HEOC & IL





VEOC






Star Detector Layout: Calculation Results



POWER BUDGET	
Power per DU	360 W
DUs total power	37,4 kW
Associated Science (EMSO)	10 kW
HEOC+IL Joule losses (~6%)	3 kW
Internal loads PJB+SJBs	1,6 kW
MVC joule losses (η= 85%)	9,2 kW
MEOC losses	6,2 kW
TOTAL POWER LOSSES	27%
POWER ON SHORE	67,4 kW




Star Detector Layout: Junction Boxes





Primary Junction Box: block scheme






PJB - Power System Box

MVC System

Optical System Box

Electro-Optical Coupling Box



LEGENDA :

- power
- optical fiber
- - - conveyed waves
- - - signals

INPUT_MVC

400 V

375 V

OUTPUT_SJB1

OUTPUT_SJB7

OUTPUT_SJB13

OUTPUT_EMSSO

power and conveyed waves slow control

LV output power

Power supply 375V/ LV

CAN Bus RS 485/232 Ethernet I2C

Ground Fault Monitor

Analog & Digital I/O

Conveyed waves to/from SJBs

Tx/Rx Copper

Tx/Rx

Tx/Rx f.o.

µC


f.o. to/from shore

slow control

f.o. to/from SJBs



Star Detector Layout: Junction Boxes




Main figures:

- 104 DU
- 8 DU per SJB
- 13 SJB
- 1 SJB for EMSO



Secondary Junction Box: block scheme






SJB - Power System Box

Electro-Optical Splitting Box

Electro-Optical Coupling Box



INPUT_PJB 400 V

INPUT_SPARE 400 V

power and conveyed waves slow control from PJB

OUTPUT_DU1

OUTPUT_DU2

OUTPUT_DU8

OUTPUT_SPARE

power and conveyed waves slow control to DU

LV output power

f.o. to/from PJB

slow control

LEGENDA :

- power
- optical fiber
- conveyed waves
- signals



ODI 10 kV CONNECTOR

Teledyne ODI Nautilus High-Power G2

- 3-Circuit, 10 kV_{DC},
- 150 amps DC / 170 amps AC (subsea)
- Max Operational Pressure: 5,000 psi (3,500 meters)
- Mating Force: < 150 lbs
- Demating Force: < 100 lbs
- Material: Titanium
- Design Life: > 25 Years
- designed using Advanced Materials Science & Materials Certification processes
- is being qualified under the guidelines of IEC 60502-2 for medium voltage connectors
- to validate the 25-year performance life
- has demonstrated a reliability level of greater than 99.9% based on accelerated life testing.





ODI 10 kV CONNECTOR



ODIs 10kV 25 years survival probability based on test results is 0,9998

Several tests have been carried out by ODI in cooperation with Alcatel.

Tests on connector pin did not satisfy Alcatel specification so Alcatel remains cautious about the long term suitability of this connector wet mated.

On the bases of these results, for Alcatel, the connector is qualified for the use in a dry mate configuration

TESTS FOR WET MATE CONFIGURATION ARE IN PROGRESS





ODI MCDU and Wet-mate Connector

TELEDYNE-ODI

Modular Connectorized Distribution Unit

It can provide input connectivity through a variety of sources, such as cable, hose, penetrator

- standardized configurations ranging from 2 up to 8 connector positions.
- 6.5 inch connector spacing
- Stainless Steel or Titanium
- 25 Years design life
- The retrievable MCDU option can be recovered back to the surface for system re-configurations.



TELEDYNE ODI

APC Rolling Seal Connector

wet-mate multichannel optical/electrical hybrid connector

Angled-Physical- Contact (APC)

Max Operational Pressure:

- 10,000 psi ambient
- 5,000 psi differential (bulkhead)

Mating Force: <120 lbs

Demating Force: <100 lbs

Configurations: ROV, Stab & Manual-Mate

Material: Titanium is preferred shell material

Design Life: 25 Years


Number of Circuits: 8 max, optical or electrical

Insertion Loss: <0.5 dB @ 1310/1550 nm

Return Loss: <-45 dB @ 1310/1550 nm

Max Operational Current: 7 amps per circuit

Max Operational Voltage: 700 VAC/1,000 VDC





Medium Voltage Converter:

Alcatel produced a 10 kW, 10kV / 400 V Medium Voltage Converter for submarine application for two projects :

- NEMO: 2 pieces, 1 deployed and working
- NEPTUNE: 6 pieces, 5 deployed and working

As per Alcatel communication they have discontinued MVC product line.

The Alcatel MVC main features:

DC Input Voltage : 5,7kV - 10 kV

DC Output Voltage: 375 V

Power: 10 kW

Input shut down voltage: 5,2 kV

Efficiency @ 10 kV, full load : 87%

Voltage undershoot (10% to 90% step up) @ 10kV: 40 V

Voltage overshoot (90% to 10% step down) @ 10kV: 43 V

Output Ripple Voltage (rms @ 100 kHz) < 1,5 V





Medium Voltage Converter

- An activity of market inquiry finalized to find a new supplier it is on going.
 - ✓ Companies contacted:
 - PBF, OceanWorks, Bruker, Heinzinger
- PFB is a power supply producer, it is interested and It did a feasibility study of a 10 kW/400V
- OceanWorks worked for NEPTUNE and VENUS (Node) and has an experience with subsea cabled network. It is “interested in the development of a 10 kW - 10kV/400V solution in a single stage with firm fixed price and performance guarantees”.
 - ✓ Activities performed:
 - First contacts with OceanWorks (Canada) Jan. 2011
 - Preliminary technical meeting in Rome in July 2011
- Actual status:
 - the MVC is part of OceanWorks roadmap and now they are willing to develop it
 - PFB intend to subscribe to a future tender
 - the activity of inquiry with more suppliers research in still on going



Conclusions

- Summary of talk:
 - Star-like sea floor network for a KM3NeT building block has been described
 - Power inventory and power calculation results have been presented
 - power distribution and its slow control data routing are described schematically for the PJB and SJB
- Achievements:
 - Cables specifications have been defined
 - Contacts with cable suppliers (Alcatel, Nexans, Draka, JDR) and cable terminations are on going
 - MVC specification are ready
 - Contacts with MVC development companies have started to review the possibilities and scan their interest
- Next Steps:
 - Primary and Secondary Junction Box preliminary design will be carried on



Thank you for your attention