



ABT Equipment: Operational Insights and Future Perspective

M. Barnes, W. Bartmann, C. Boucly, C. Bracco, J. Borburgh, P. Burkel, M. Diaz, L. Ducimetière,
Y. Dutheil, **G. Favia**, L. Feliciano, L. Fernandez, T. Kramer, V. Namora, N. Magnin, F. Pelloux,
V. Senaj, D. Standen, T. Stadlbauer, P. Trubacova, F. Velotti, N. Voumard, C. Zannini

Outline

1. Operational insights

- 2024 ABT equipment operation
- 2024 operational experience:
 - KFA71
 - KFA14
 - MKP-L
 - MKI

2. Looking forward

- MKP-S
- MKDH
- AC dipole

3. Conclusions

Outline

1. Operational insights

- 2024 ABT equipment operation
- 2024 operational experience:
 - KFA71
 - KFA14
 - MKP-L
 - MKI


2. Looking forward

- MKP-S
- MKDH
- AC dipole


3. Conclusions

2024 performance in a glance

Injectors (AD, PSB, PS, SPS)



LHC




Courtesy of J. Heron

- **Very reliable operation** with **> 99% availability**, both for injectors and LHC equipment
- Reached ultimate LIU beam intensities in the LHC injectors, without **any limitation from ABT equipment**
- No major HW change, **but continuous effort on improving operation**, relying on experience and enhancing AI and automation

PSB / KFA14

- Four magnet modules per ring, to extract beams from the PSB. The connection boxes, PFL and TX lines are filled with SF6 gas
- On March 29th a **SF6 leak** developed in Ring3 generator, originated by an electrical breakdown in the SF6 feedthrough insulation of the dump switch
 - Likely air bubbles generated during previous oil filling
 - 12 kg out of 100 kg SF6 lost
 - **> 11 hours blocking time**



PSB / KFA14

- Four magnet modules per ring, to extract beams from the PSB. The connection boxes, PFL and TX lines are filled with SF6 gas
- On March 29th a **SF6 leak** developed in Ring3 generator, originated by an electrical breakdown in the SF6 feedthrough insulation of the dump switch
 - Likely air bubbles generated during previous oil filling
 - 12 kg out of 100 kg SF6 lost
 - **> 11 hours blocking time**


Actions:

- **Improved KFA14 SF6 fault prevention** to be implemented:
 - Check status of all generators to identify early signs of deterioration
 - Refine switch maintenance and oil filling procedures
- Improved feedthrough design under study
- **Replace SF6 cables:** R&D campaign ongoing to find alternatives
- Established safety procedure to ensure safe interventions performed on still operational equipment

Dump switch



Broken feedthrough



PE HV Low Attenuation Cable



PS / KFA71-79

- 12 magnet modules: nine located section 71 and three in section 79 used for the fast extraction of all PS beams
- **> 164 hrs downtime in 2021** → Consolidation of generator modules and control systems started during YETS21/22
 - 6 out of 12 modules already upgraded, full renovation expected to be completed by LS3 (2027)
 - Downtime was reduced to **~12 hrs** in 2023

PS / KFA71-79

- 12 magnet modules: nine located section 71 and three in section 79 used for the fast extraction of all PS beams
- **> 164 hrs downtime in 2021** → Consolidation of generator modules and control systems started during YETS21/22
 - 6 out of 12 modules already upgraded, full renovation expected to be completed by LS3 (2027)
 - Downtime was reduced to **~12 hrs** in 2023
- During 2024 run all the **three** recently upgraded **dump switches failed**:
 - **Not blocking**, as operation with less modules still possible
 - Fault originated from TDR discs assembly operations

KFA71 nominal and distorted pulses



PS / KFA71-79

- 12 magnet modules: nine located section 71 and three in section 79 used for the fast extraction of all PS beams
- **> 164 hrs downtime in 2021** → Consolidation of generator modules and control systems started during YETS21/22
 - 6 out of 12 modules already upgraded, full renovation expected to be completed by LS3 (2027)
 - Downtime was reduced to ~12 hrs in 2023
- During 2024 run all the **three** recently upgraded **dump switches failed**:
 - **Not blocking**, as operation with less modules still possible
 - Fault originated from TDR discs assembly operations

Actions:

- New documented **discs validation and assembly procedures**
- **EPA anomaly detection** and forecasting
- Established safety procedure to ensure safe interventions performed on operational equipment


KFA71 nominal and distorted pulses



Broken DS resistor


SPS / MKP-L

- System designed to inject LHC beams in the SPS together with the MKP-S
- MKP-L was identified as a limitation for the HL beam intensity reach:
 - In 2016 **high voltage weaknesses** were addressed by limiting the operational voltage (36.8kV vs 49 kV nominal), increasing MKP-S voltage and introducing transfer line steering
 - New low impedance MKP-L installed during YETS 22/23:
 - **Significantly lower beam induced heating and fast beam conditioning**
 - Kept reduced voltage as no available low-impedance spare
 - Reached LIU intensities in 2024



SPS / MKP-L

- System designed to inject LHC beams in the SPS together with the MKP-S
- MKP-L was identified as a limitation for the HL beam intensity reach:
 - In 2016 **high voltage weaknesses** were addressed by limiting the operational voltage (36.8kV vs 49 kV nominal), increasing MKP-S voltage and introducing transfer line steering
 - New low impedance MKP-L installed during YETS 22/23:
 - **Significantly lower beam induced heating and fast beam conditioning**
 - Kept reduced voltage as no available low-impedance spare
 - Reached LIU intensities in 2024
- During 2024 run the **operating voltage has been increased up to 43 kV**:
 - Planned tests on old module to understand HV weakness
 - Spare assembly ongoing, validation tests will follow → ready in 2025
 - **Expected loss reduction and lighter beam commissioning with full voltage at zero bump**





LHC / MKI

- 2 systems inject counterrotating beams in the LHC
- Significant beam induced heating in Post-LS1 design magnets
- MKI Cool upgrade started during YETS 22/23, to be completed in LS3

LHC / MKI

- 2 systems inject counterrotating beams in the LHC
- Significant beam induced heating in Post-LS1 design magnets
- MKI Cool upgrade started during YETS 22/23, to be completed in LS3

- Two MKI Cool magnets already installed in Pt8
 - Temperature rise, near ferrite yoke, is only 30% of Post-LS1 MKIs
 - Rapid beam conditioning
 - HV Sparks or discharges occurring on screen conductors:
 - **emittance growth and some beam dumps** triggered by BLM losses and BPM





LHC / MKI

- 2 systems inject counterrotating beams in the LHC
- Significant beam induced heating in Post-LS1 design magnets
- MKI Cool upgrade started during YETS 22/23, to be completed in LS3

- Two MKI Cool magnets already installed in Pt8
 - Temperature rise, near ferrite yoke, is only 30% of Post-LS1 MKIs
 - Rapid beam conditioning
 - HV Sparks or discharges occurring on screen conductors:
 - **emittance growth and some beam dumps** triggered by BLM losses and BPM

Actions:

- Improved conditioning of magnets following a beam dump
 - ✓ **Event frequency has drastically reduced, with events almost disappearing in MKI8C**
- HV tests on coated samples to rule out issues related to coating charge-up or deterioration



Outline

1. Operational insights

- 2024 ABT equipment operation
- 2024 operational experience:
 - KFA71
 - KFA14
 - MKP-L
 - MKI


2. Looking forward

- MKP-S
- MKDH
- AC dipole

3. Conclusions


SPS / MKP-S limitations and performance improvement studies

- Observed MKP-S heating since low-impedance MKP-L installation:
 - LHC physics operations not affected
 - it limited the duty cycle of the 2024 scrubbing run
 - It poses potential risks to magnet integrity






SPS / MKP-S limitations and performance improvement studies

- Observed MKP-S heating since low-impedance MKP-L installation:
 - LHC physics operations not affected
 - it limited the duty cycle of the 2024 scrubbing run
 - It poses potential risks to magnet integrity
- Various mitigation strategies are being examined:
 - **Hardware solutions** → new magnet design or implementation of a cooling system
 - **Beam offset** → Power losses expected to be halved by 22mm beam offset



SPS / MKP-S limitations and performance improvement studies


- Observed MKP-S heating since low-impedance MKP-L installation:
 - LHC physics operations not affected
 - it limited the duty cycle of the 2024 scrubbing run
 - It poses potential risks to magnet integrity
- Various mitigation strategies are being examined:
 - **Hardware solutions** → new magnet design or implementation of a cooling system
 - **Beam offset** → Power losses expected to be halved by 22mm beam offset
- **Tests** performed in 2024 **proved the effectiveness of beam offset solution**:
 - 17mm bump used
 - Required 10h stable beam conditions ($\frac{dT}{dt}=0.4^{\circ}\text{C}/\text{h}$)
 - Bump only possible at flat bottom energy, due to limited SPS corrector strength
 - **Complementary magnet re-alignment needed**



Courtesy of C. Zannini

SPS / MKP-S limitations and performance improvement studies

- Observed MKP-S heating since low-impedance MKP-L installation:
 - LHC physics operations not affected
 - it limited the duty cycle of the 2024 scrubbing run
 - It poses potential risks to magnet integrity
- Various mitigation strategies are being examined:
 - **Hardware solutions** → new magnet design or implementation of a cooling system
 - **Beam offset** → Power losses expected to be halved by 22mm beam offset
- **Tests** performed in 2024 **proved the effectiveness of beam offset solution**:
 - 17mm bump used
 - Required 10h stable beam conditions ($\frac{dT}{dt}=0.4^{\circ}\text{C}/\text{h}$)
 - Bump only possible at flat bottom energy, due to limited SPS corrector strength
 - **Complementary magnet re-alignment needed**
- Only 5mm re-alignment possible without venting the sector:
 - Aperture studies still pending
 - Investigate possibility of realignment during LS3
 - Dedicated scrubbing of both MKP and newly installed MKDH



Courtesy of C. Zannini

SPS / MKDH limitations and performance improvement studies

- Three dump kicker magnets used for sweeping SPS particles on TIDVG
- From 2023 operation experience:
 - Long beam conditioning and vacuum interlocks limiting LIU beam intensity reach
 - Significant missing kick from two magnets due to eddy currents → ok for TIDVG
 - **Raised concern about blocking time in case of accident:**
 - ~7 weeks, including ~10days of beam conditioning (assuming 50% availability)

SPS / MKDH limitations and performance improvement studies

- Three dump kicker magnets used for sweeping SPS particles on TIDVG
- From 2023 operation experience:
 - Long beam conditioning and vacuum interlocks limiting LIU beam intensity reach
 - Significant missing kick from two magnets due to eddy currents → ok for TIDVG
 - **Raised concern about blocking time in case of accident:**
 - ~7 weeks, including ~10days of beam conditioning (assuming 50% availability)
- **A mitigation strategy is being examined:**
 - Installation of a coated chamber to improve vacuum performance:
 - **Ti coating** for beam impedance reduction → already tested and validated in LBDS-MKD
 - **aC coating** for SEY reduction → already tested and validated in MKP
 - Replace weaker magnets with lower-eddy current ones:
 - They can be operated at lower voltage → **improvement of HV and vacuum performance as well as relaxed vacuum interlock**



SPS / MKDH limitations and performance improvement studies



- Three dump kicker magnets used for sweeping SPS particles on TIDVG
- From 2023 operation experience:
 - Long beam conditioning and vacuum interlocks limiting LIU beam intensity reach
 - Significant missing kick from two magnets due to eddy currents → ok for TIDVG
 - **Raised concern about blocking time in case of accident:**
 - ~7 weeks, including ~10days of beam conditioning (assuming 50% availability)
- **A mitigation strategy is being examined:**
 - Installation of a coated chamber to improve vacuum performance:
 - **Ti coating** for beam impedance reduction → already tested and validated in LBDS-MKD
 - **aC coating** for SEY reduction → already tested and validated in MKP
 - Replace weaker magnets with lower-eddy current ones:
 - They can be operated at lower voltage → **improvement of HV and vacuum performance as well as relaxed vacuum interlock**
 - Feasibility study ongoing:
 - Beam aperture check for **all beams**
 - Magnets have different apertures: ongoing compatibility check
 - Ongoing beam impedance simulations and tests



SPS / MKDH limitations and performance improvement studies

- Three dump kicker magnets used for sweeping SPS particles on TIDVG
- From 2023 operation experience:
 - Long beam conditioning and vacuum interlocks limiting LIU beam intensity reach
 - Significant missing kick from two magnets due to eddy currents → ok for TIDVG
 - **Raised concern about blocking time in case of accident:**
 - ~7 weeks, including ~10days of beam conditioning (assuming 50% availability)
- **A mitigation strategy is being examined:**
 - Installation of a coated chamber to improve vacuum performance:
 - **Ti coating** for beam impedance reduction → already tested and validated in LBDS-MKD
 - **aC coating** for SEY reduction → already tested and validated in MKP
 - Replace weaker magnets with lower-eddy current ones:
 - They can be operated at lower voltage → **improvement of HV and vacuum performance as well as relaxed vacuum interlock**
 - Feasibility study ongoing:
 - Beam aperture check for **all beams**
 - Magnets have different apertures: ongoing compatibility check
 - Ongoing beam impedance simulations and tests


Upgraded MKDH design



LHC / MKQA spare strategy

- MKQA is used for measuring beam dynamics parameters ('A' or 'Q' mode) and overcome spin resonances ('ACdipole mode')
- From 2024 operational experience:
 - **FPGA failing several times**, temporarily fixed:
 - Not blocking OP
 - 20 years old cards → **need replacement!**
 - **Amplifiers failing** due to aging:
 - All four spares were used, **running out of spare** during reparation
 - **Amplifiers out of production** and reparation possible depending on component availability

Simplified schematics of AC dipole configuration



AC dipole FEC and power amplifiers




LHC / MKQA spare strategy

- MKQA is used for measuring beam dynamics parameters ('A' or 'Q' mode) and overcome spin resonances ('ACdipole mode')
- From 2024 operational experience:
 - **FPGA failing several times**, temporarily fixed:
 - Not blocking OP
 - 20 years old cards → **need replacement!**
 - **Amplifiers failing** due to aging:
 - All four spares were used, **running out of spare** during reparation
 - **Amplifiers out of production** and reparation possible depending on component availability

Actions:

- **New FPGA design already tested, validated** and ready for installation (YETS24/25)
- **Amplifier replacement strategy under definition** (no equivalent solution available):
 - Contact with industries ongoing to find possible technical solutions
 - In house development or outsourcing?
 - Consolidation planned for LS3

Simplified schematics of AC dipole configuration



AC dipole FEC and power amplifiers



Conclusion

- Achieved excellent ABT operational performance, with less than 1% unavailability across both injectors and the LHC
- Successfully managed significant incidents involving KFA71 and KFA14 through prompt expert intervention, alongside ongoing efforts to enhance fault detection and prevention measures
- Conducted interventions during operation shadowing to minimize blocking time. Safety procedures have been established
- Confirmed performance improvements in the recently upgraded MKP-L and MKI systems, with room for further enhancement
- Identified potential limitations in the MKP-S and MKDH systems; upgrade strategies are currently being explored for LS3
- Addressed AC dipole spare limitations, with final consolidation foreseen during LS3

Spare Slides

SMH16 eddy current septum installation

Scope:


- Present system based on direct drive topology, with limited lifetime (magnet exchange every 2yrs)
- Present power converter (SY/EPC) at the end of its life. Regular wrong pulses

Consolidation strategy:


- Novel eddy current topology, under vacuum, with expected longer lifetime
- New power generator design (SY/ABT)
- Planning foresaw installation during YETS 24/25

Current status:

- 2 generators: 1 in lab 867 under test, 1 in blg 151 ready for pulsing with dummy load
- Reliability run not yet completed, generator requiring still minor adjustment to be within specs. Timing and control systems being finalized
- Installation of SMH16CF during YETS 25/26 has been proposed:
 - **1 yr of life left for present SMH16DD, exchange is needed**
 - **The nToF run would need to be concluded earlier** to enable immediate intervention after end of run (in compliance with RP constraints)
 - **Cabling and generator installation done in YETS 24/25 already**



MKP-L losses at 43kV



- Increased aperture due to the reduced bump
- Insufficient data points available to draw a conclusion
- A dedicated measurement campaign is required to better evaluate impact

MKDH impedance measurements

