

Hydrogen Buffer the NA61/SHINE

Bartosz Maksiak and Aleksandr Dmitriev

26.11.2024

Status

- **Buffer:**
these slides
- **Control and gas racks:**
first discussions done, iteration with TE-CRG, EP-DT-DI and EP
Safety/HSE in near future
- **Pipes:**
Exhaust pipe exists
New pipe between the gas rack and the buffer outside is needed – TE-CRG
agreed to handle it

Installation of new Hydrogen Buffer

- **Brief description:**


Installation of Hydrogen Buffer for the NA61/SHINE experiment outside of EHN1 (Jura side) as part of the project related to installation of the Liquid Hydrogen Target in NA61/SHINE.

- **Reason for the change:**


Part of the new Liquid Hydrogen Target for NA61/SHINE

Request of secondary proton beam at 300 GeV/c in 2025 (22.10-19.11) for new pp measurements.

Installation of new Hydrogen Buffer



Installation of new Hydrogen Buffer



- **The area needs refurbishment:**

- Debris of an old installation should be removed. The tail container should stay.
- Old and unused cryo elements should be dismantled
- Unused electrical infrastructure has to be checked, refurbished and prepared to satisfy the needs of the buffer heater (10-16A, max 2kW)

Installation of new Hydrogen Buffer



Afterwards, the cage to contain the buffer should be installed as well as the buffer itself. Our needs require the volume of the buffer to be 2m³.

Thank you!