

# Pushing intensity with LHC-type beams

H. Bartosik, I. Karpov, I. Mases, L. Mether, G. Papotti, K. Paraschou, G. Rumolo, C. Zannini,  
F. Asvesta, X. Buffat, H. Damerau, A. Lasheen, K. Li, M. Barnes, R. Calaga,  
E. de la Fuente, G.P. Di Giovanni, A. Huschauer, G. Iadarola, V. Kain, B. Mikulec, B. Salvant,  
M. Schenk, F.M. Velotti, PSB-PS-SPS OP teams

# Intensity reach in the last three years

Intensity reach at flat top with nominal bunch length [ $10^{11}ppb$ ]		
Year	8b4e (4 x 56 bunches)	LHC25ns (4 x 72 bunches)
2022	1.5	1.52
2023	2.15	2.2
2024	x	2.3

During 2024 scrubbing we demonstrated the LIU intensity

LIU beam (288 bunches with  $\sim 2.3e11$  ppb and  $\sim 1.6$ ns bunch length) accelerated to 450 GeV

LIU beam at  $2.3e11$  ppb never fully restored

Beam availability during MDs, struggling with RF cavity limits, beam readiness from injectors after long gaps, magnet exchanges, ....


**Consolidation of LIU beam and exploration of intensity limits with 8b4e beam**

Key to be well prepared for the 2026 reliability run

# Trasverse stability at injection energy

- **Horizontal instability** studied in detail in 2018 for  $1.8e11$  p/b
  - Mitigation strategy developed in simulations: **high chromaticity + octupoles**
- **Extremely fast vertical coupled bunch instability** predicted in simulations
  - Threshold depends on the set vertical tune and chromaticity

Criticality of short bunches at injection (<4 ns) to ensure stability, also confirmed in simulations




# Transverse stability at injection energy


- **Horizontal instability** studied in detail in 2018 for  $1.8e11$  p/b
  - Mitigation strategy developed in simulations: **high chromaticity + octupoles**
- **Extremely fast vertical coupled bunch instability** predicted in simulations
  - Threshold depends on the set vertical tune and chromaticity

**Criticality of short bunches at injection (<4 ns) to ensure stability, also confirmed in simulations**

With some exceptions 2024 bunch lengths from PS were consistently below 4 ns




**Transverse stability successfully tested in 2024 (~30h with ~2.7e11 ppb injected and 4 x 72 bunches)**



# Observation of vertical instability

Studies with 4 batches in 2024




Experimentally confirmed with 1 batch and low intensity in 2021 and 2022


At tune  $Q_v = 20.18$ , and  $Q_{PV} = 0.6$  (knob), we reduced gradually the gain of the damper

SCAN OF THE VERTICAL CHROMATICITY AT NOMINAL DAMPER GAIN

Vertical chromaticity (knob) needs to be  $Q_{PV} \geq 0.6$




# Observation of vertical instability



At tune  $Q_v = 20.18$ , and  $Q_{PV} = 0.6$  (knob), we reduced gradually the gain of the damper


SCAN OF THE VERTICAL CHROMATICITY AT NOMINAL DAMPER GAIN

Vertical chromaticity (knob) needs to be  $Q_{PV} \geq 0.6$




# Horizontal and vertical chromaticity

SPSBEAM/QPH SPSBEAM/QPH (12-09-2024 12:47:47)



SPSBEAM/QPV SPSBEAM/QPV (12-09-2024 13:40:05)



Higher chroma needed for transverse stability with BCMS beam in both planes due to the smaller emittances



Could **Q22 optics** help to reduce the needed chromaticity for transverse stability?

Investigation with Q22 optics revealed that indeed horizontal stability can be improved as predicted by Xavier (**stability reached for a 0.1-0.15 lower H chromaticity**). Stability become more critical in the vertical plane (**0.1-0.15 higher V chromaticity**)

# SPS injection kicker beam induced heating mitigation

After the optimization of the MKP-L, MKP-S became the major bottleneck in term of beam induced heating  
Scrubbing run 2023 and 2024 had to be modulated to accommodate cool down of the MKP-S magnet

Offsetting the **circulating beam** towards the **ground conductor** is expected to be beneficial in terms of beam induced heating





# Desiderata for 2025

- Consolidation of LIU beam (scrubbing + at least 4-5 MD slots)
  - Standard (during scrubbing) and BCMS (dedicated MD cycle)
- Exploration of intensity margins for LIU beam – at least 2-3 MD slots
- Pushing intensity with 8b4e beam (goal is to give  $2.3 \times 10^{11}$  ppb to LHC for 2026 high intensity studies) - at least 2 MD slots
- Beam quality optimization (emittance, tails, batch-by-batch tune correction)
- Minimization of PS-SPS mismatch (tuning of transfer line optics)

meas. time	Standard				BCMS			
	epsn [ $\mu\text{m}$ ]	Intensity [ $10^{11}\text{ppb}$ ]	Brightness [ $10^{11}\text{ppb}/\mu\text{m}$ ]	Target brightness [ $10^{11}\text{ppb}/\mu\text{m}$ ]	epsn [ $\mu\text{m}$ ]	Intensity [ $10^{11}\text{ppb}$ ]	Brightness [ $10^{11}\text{ppb}/\mu\text{m}$ ]	Target brightness [ $10^{11}\text{ppb}/\mu\text{m}$ ]
PS extr.	2.05	2.64	1.29	-	1.59	2.64	1.66	-
SPS inj.	2.25	2.59	1.15	1.36	1.73	2.59	1.50	1.71

Thank you for your attention

# Additional studies



# SPS Wire scanner failure

**YETS 23/24: installation of ferrites and coupler in all 4 wire scanners tanks**

As predicted from power loss calculations, no issues observed in parking position up to LIU intensities

Development of an **advanced model** that can reproduce the beam induced power loss over the relevant frequency range

An SPS wire scanner get stuck close to beam halo during 2024 operation



Breakage expected for >6.5 W



Beam type	Parking position [W]	Stuck position [W]
Operational	<0.9	<4.5
MD beam (breakage)	<2.4	>6.8
LIU	<5	>14

The stuck wire broke with significantly lower intensity than LIU, consistently with the **advanced model** predictions

# SPS Wire scanners: expectations for coming years



YETS 23/24: installation of ferrites and coupler in all 4 wire scanners tanks

From power loss calculations, no issues are expected if considering **peak power on the wire along the cycle.**




# Appendix

# MKP-S beam induced heating mitigation




# MKP-S beam induced heating mitigation






# MKP-S beam induced heating mitigation



# MKP-S beam induced heating mitigation





# SPS transverse stability

- **Horizontal instability @26 GeV** studied in detail in 2018 for  $1.8e11$  p/b
  - Mitigation strategy developed in simulations: **high chromaticity + octupoles**
- **Extremely fast vertical coupled bunch instability @26 GeV** predicted in simulations
  - Threshold depends on the set vertical tune and chromaticity

**Criticality of short bunches at injection (<4 ns) to ensure stability, also confirmed in simulations**


With some exceptions 2024 bunch lengths from PS were consistently below 4 ns



# Trasverse stability at injection energy

- **Horizontal instability** studied in detail in 2018 for  $1.8e11$  p/b
  - Mitigation strategy developed in simulations: **high chromaticity + octupoles**
- **Extremely fast vertical coupled bunch instability** predicted in simulations
  - Threshold depends on the set vertical tune and chromaticity

**Criticality of short bunches at injection (<4 ns) to ensure stability, also confirmed in simulations**



**Transverse stability successfully tested in 2024 (~30h with  $\sim 2.7e11$  ppb injected and 4 x 72 bunches)**