

XY table issues

Jonathan Aguilar

AGH University of Science and Technology
Institute for Nuclear Physics - Polish Academy of Science

September 14, 2011

Problems

Test beam 1

Weak motors - needed a magnetic spring
Sensor size larger than table range

Test beam 2

Worked well with one sensor
Failed above 60mm with second sensor + tungsten

Testing

We have two Standa motorized positioners:

- 8MTF-100 (2-D)
- 8MT200-100 (1-D) (received after test beam)

Mounted both in vertical position and loaded with 0.867 kg W plates until they stopped moving.



8MTF-100

- Specs say max load ~ 6 kg
- Max load varies!
 - Actual position of load doesn't matter
 - Still underperforming re: specs



8MTF-100

XY table loading behavior



"+"s mark loads



8MT200-100

- Specs say max load ~ 6 kg
- Don't believe the specs!
 - Supports at least 9.5 kg (I ran out of tungsten)
 - Stepping resolution ($10\mu m$ with power cycling, $2.5\mu m$ without) not affected by load.
 - We should probably use this positioner at the next test beam



8MT200-100


Current setup at AGH



Proposals for next test beam

We currently have a 3-D setup at AGH for measuring sensors with a laser.

- We could bring this
 - Need enough space for 8MTF-100 to lie horizontally
 - Software is already prepared
- Alternative: get another 8MT200-100 (→)
 - Software could be adapted easily
 - Solid - it may not make sense to have a telescope plane behind



Alternative setup