

# ISOLDE WORKSHOP AND USERS MEETING 2011

## HIE-ISOLDE BEAM CHARACTERISTICS AND HEFT LAYOUT

Matthew A. Fraser – University of Manchester, Cockcroft Institute and CERN (BE/RF)


mfraser@cern.ch

# CONTENTS

- Brief introduction
- Work this year...
  - REX simulations
  - Longitudinal emittance measurements
  - Deceleration
  - Summary of beam parameters
- HEBT
- Points for discussion
- Future

# INTRODUCTION





- The staged upgrade of some 40 MV of superconducting linac.
- Work focused on the beam dynamics design of the upgrade itself and REX to understand the input parameters and matching.



- HIE-ISOLDE beam dynamics design complete, see e.g. M.A. Fraser et al, Phys. Rev ST Accel. Beams, 14 2 020102 (2011)

# REX SIMULATIONS


- In collaboration with BE/ABP (Piero Posocco et al.) completed an RFQ beam dynamics study.
- To be published internally at CERN.




# REX SIMULATIONS

- RFQ simulations were benchmarked with beam measurements.

Energy spread with voltage:




Transmission with voltage:




# REX SIMULATIONS

- IH structure bead-pull measurements made and used in beam simulations to understand its working point (presented last year).
- 9-gap structure simulations completed, which indicate it will degrade the longitudinal beam properties of the upgrade in the first stages:


Longitudinal phase-space on entry to 9GP:



Longitudinal phase-space on exit to 9GP:



# REX SIMULATIONS



LANA end-to-end simulations.

Longitudinal emittance doubles in the 9GP from 2 to 4  $\pi$  ns keV/u: simulations benchmarked with LORASR.



# LONGITUDINAL EMITTANCE MEASUREMENTS



- Campaign of longitudinal emittance measurements completed, see M.A. Fraser et al, Nucl. Instrum. Methods A663 p.1-9 (2012).

Rebuncher:

$$\epsilon_{86\%} = 1.48 \pm 0.2 \pi \text{ ns keV/u}$$

7-gap 3:


$$\epsilon_{86\%} = 1.55 \pm 0.12 \pi \text{ ns keV/u}$$




# DECELERATION

- In theory, one can decelerate light beams from 1.2 MeV/u to RFQ energy (0.3 MeV/u).
- In practice, due to degradation of the beam quality at low velocity in the cavities we are limited to 0.45 MeV/u.

$A/q = 4.5$ :




$A/q = 3$ :



# DECELERATION


$$\Delta W = q\Delta V_0 \hat{T}(\beta) \cos \phi + \frac{(q\Delta V_0)^2}{W} (\hat{T}^{(2)}(\beta) + \hat{T}_s^{(2)}(\beta) \sin 2\phi)$$



# BEAM PARAMETERS

- Beam parameters for 5.5 MeV/u, 10 MeV/u and 0.45 MeV/u are appended, the emittances are summarised next.
- Design of HEBT is based on these numbers.
- Input taken from emittance measurements and limited by the REX front-end, namely:
  - Longitudinal:  $\epsilon_{95\%} = 2 \pi \text{ ns keV/u}$  (M.A. Fraser et al.)
  - Transverse :  $\epsilon_{90\%} = 0.3 \pi \text{ mm mrad}$  (D. Voulot et al.)
- Comments:
  - SC linac will not significantly degrade existing beam emittance.
  - Adiabatic damping of transverse geometric emittance with velocity:  $\sigma \propto 1 / \sqrt{\beta}$
  - $\Delta W > \pm 0.1 \%$ , therefore depending on A/q, either a lower energy is used and cavities in the main linac used to de/re-bunch or a dedicated de/re-buncher is needed in the HEBT. Emittance is compatible with specification!
  - Low energy beams (<2.4 MeV/u) debunched at 101.28 MHz.

# ENERGY RANGE



# BEAM PARAMETERS

- Emittance given at linac exit and at maximum energy for  $A/q = 4.5$ .


Stage and Energy	95% $\epsilon_{\text{transverse}}$ ( $\pi$ mm mrad) (geometric)	95% $\epsilon_{\text{longitudinal}}$ ( $\pi$ ns keV/u)
Stage 1 at 5.5 MeV/u	$\approx 4$	$\approx 4$
Stage 2b at 10 MeV/u	$\approx 3$	$\approx 2$
Stage 2b at 0.45 MeV/u	$\approx 20$	$\approx 2.6$ (but debunched at 101.28 MHz)

- 95 % of a Gaussian beam equates to the 6-rms emittance, with corresponding projections e.g.:  $\Delta W = \sqrt{6}\sigma_{rms}$
- Assuming the focus can be made with the appropriate optical elements, use e.g.:

$$\Delta x \approx \epsilon / \Delta x'$$


# HEBT

- First iteration of the design, which is currently being taken on by TE/ABT/BTP (Brennan Goddard) and has been allocated a Fellow.
- Without a rebuncher at 5.5 MeV/u:  $\Delta W = \pm 0.6\%$  ( $=\pm\sqrt{6}\sigma$ ) and  $\Delta t < \pm 1.6\text{ ns}$  ( $=\pm\sqrt{6}\sigma$ )
- A rebuncher will reduce the above parameters by a factor of 3.



# HEBT

- With chopper line, difficult to fit rebuncher for Exp Station 1.
- Without a rebuncher at 10 MeV/u ( $A/q = 4.5$ ):  $\Delta W = \pm 0.3\%$  ( $=\pm\sqrt{6}\sigma$ ) and  $\Delta t < \pm 0.6$  ns ( $=\pm\sqrt{6}\sigma$ ) at Exp Stations 1 and 2.
- With rebuncher at 10 MeV/u ( $A/q = 4.5$ ):  $\Delta W = \pm 0.1\%$  ( $=\pm\sqrt{6}\sigma$ ) and  $\Delta t < \pm 0.25$  ns ( $=\pm\sqrt{6}\sigma$ ) at Exp Station 2.




# POINTS FOR DISCUSSION

- Requirement of a rebuncher in the HEBT?
  - beams below  $\approx 2.4$  MeV/u will need rebunching after main linac
  - high energy beams could be bunched in main linac if energy is sacrificed.
  - require upwards of 1 MV at high energy (superconducting QWR).
- Further information/iteration on the footprints of the experiments?
  - in particular for Experimental Station 2.
- Some transverse beam parameters are challenging:
  - spectrometer
  - MINIBALL when beam is decelerated (large geometric emittance)
- Full or half-day meeting will be scheduled for late February to ensure design constraints requirements are understood for HEBT. Brennan Goddard to make the appropriate arrangements.
- A contact person (nuclear physicist) in regular HEBT meetings.

# NEXT YEAR...

- Finalisation of HEBT design early next year.
- 100 ns bunch spacing:
  - Beam dynamics simulations of RFQ with multi-harmonic pre-buncher
  - Development of the pre-buncher.
  - Development of the chopper line and its associated rf structures.





## Schematic:



# APPENDED BEAM PARAMETERS



# STAGE 2B: 10 MeV/u

- At exit to the HIE-LINAC in Stage 2b:



# STAGE 1: 5.5 MeV/u

- At exit to the HIE-LINAC in Stage 1:



# STAGE 2B: 0.45 MeV/u

- At exit to the HIE-LINAC in Stage 2:

