


PSB dump replacement

17th November 2011



LIU-PSB meeting

Alba Sarrió

LOCATION





LOCATION




MAIN CHARACTERISTICS OF THE DESIGN

- EXISTING DUMP:




Historical diagram of peak beam intensities

- Geometry:
 - Sliced design (15 disks)
- Material:
 - Structural Steel (disks)
 - Stainless steel 304/316 (pipes, joints, elbows...)
- Dimensions:
 - L = 483 mm
 - $\varnothing = 220$ mm
- Beam parameters:
 - Designed in the 60's for an 800 MeV energy
 - Current energy: 1.4 GeV
 - Intensity: $8e+12$ particles (p+)
 - Pulse period: 1.2 s
- Total Beam Power:
 - ~ 1.5 kW




NEW DESIGN: constraints and decision-making

- Simplicity: use of classic materials and of simple design principles
- A system easy to access and to repair in case of need
- Low maintenance design
- Minimize any risk of failure (water, vacuum...)
- Constraints in layout, assuming that the current shielding is kept
 - Reasons to remove the concrete blocks: so that they do not constrain the diameter of the dump
 - Reasons to keep the concrete blocks: difficult work in a highly radiated area (more restrictive ALARA procedure)




MAIN CHARACTERISTICS OF THE DESIGN

• EXISTING DUMP:



• NEW DUMP:



• Geometry:

- Sliced design (15 disks)

• Material:

- Structural Steel (disks)
- Stainless steel 304/316 (pipes, joints, elbows...)

• Dimensions:

- L = 483 mm
- \varnothing = 220 mm

• Beam parameters:

- Designed in the 60's for an 800 MeV energy
- Current energy: 1.4 GeV
- Intensity: $8e+12$ particles (p+)
- Pulse period: 1.2 s

• Total Beam Power:

- ~1.5 kW

• Geometry:

- Sliced design (33 disks)

• Material:

- Copper alloy (disks)

• Dimensions:

- L = 1435 mm
- \varnothing = 220 mm

• Beam parameters:

- Energy: 2 GeV
- Intensity: $1e+14$ particles (p+)
- Pulse period: 1.2 s

• Total Beam Power:

- ~26.7 kW

BEAM SIZES

- Need to optimise beam sizes
- Minimum beam sizes:
 - Small values increase thermal load and mechanical stress
 - Need to increase the minimum as much as possible
- Maximum beam sizes:
 - High values increase spread to a point where a large part of the beam misses the target
 - Critical when defining the layout of the dump (position of cooling pipes, shielding...)
 - Need to reduce the maximum as much as possible

1 SIGMA-BEAM SIZES

(by Thomas Hermanns)

		Horizontal Plane --- Beam Sizes [mm]						
	Intensity	Block 1	Block 2	Block 3	Block 4	Block 5	Core	
NORMGPS	$8 \cdot 10^{12}$	6.77	8.07	9.45	10.89	12.35	12.99	
	$4 \cdot 10^{12}$	5.07	6.11	7.19	8.32	9.47	9.97	
	$1 \cdot 10^{12}$	3.07	3.80	4.57	5.37	6.18	6.53	
CNGS	$7.5 \cdot 10^{12}$	6.17	7.50	8.93	10.40	11.90	12.55	
	$3.75 \cdot 10^{12}$	4.71	5.78	6.92	8.09	9.29	9.81	
	$1.5 \cdot 10^{12}$	3.30	4.09	4.92	5.79	6.68	7.06	
LHC-25A	$1.6 \cdot 10^{12}$	3.28	4.01	4.78	5.57	6.39	6.74	

Table 4: 1 σ -beam sizes (horizontal plane) at the PS Booster dump. The contribution of the horizontal dispersion is added.



		Vertical Plane --- Beam Sizes [mm]						
	Intensity	Block 1	Block 2	Block 3	Block 4	Block 5	Core	
NORMGPS	$8 \cdot 10^{12}$	22.49	24.87	27.24	29.62	32.00	33.03	
	$4 \cdot 10^{12}$	15.99	17.67	19.36	21.05	22.73	23.46	
	$1 \cdot 10^{12}$	9.25	10.23	11.21	12.19	13.17	13.60	
CNGS	$7.5 \cdot 10^{12}$	22.10	24.45	26.81	29.16	31.52	32.54	
	$3.75 \cdot 10^{12}$	15.64	17.31	18.98	20.64	22.31	23.03	
	$1.5 \cdot 10^{12}$	10.39	11.50	12.61	13.72	14.82	15.30	
LHC-25A	$1.6 \cdot 10^{12}$	12.33	13.63	14.94	16.25	17.56	18.13	

Table 5: 1 σ -beam sizes (vertical plane) at the PS Booster dump.

Maximum beam size at the dump core:

- 1 sigma horizontal plane: **12.99 mm**
- 1 sigma vertical plane: **33.03 mm**

Minimum beam size at the dump core:

- 1 sigma horizontal plane: **6.53 mm**
- 1 sigma vertical plane: **13.60 mm**

PRELIMINARY ANALYSIS

(BASED ON THE NEW DESIGN)

- Parameters:
 - Sliced geometry
 - $L = 1435$ mm
 - $\varnothing = 220$ mm
 - Copper alloy
 - Energy: 2 GeV
 - Intensity: $1e+14$ particles (p+)
 - 1 sigma-beam size (old values from Thomas Hermanns):
 - Horizontal plane: 6.53 mm
 - Vertical plane: 13.60 mm
- Results (from ANSYS, thermal analysis):
 - ΔT after 1 pulse: 20 °C \Rightarrow ΔT_{max} in steady state ~ 100 °C
 - ΔT steady state: 76 °C \Rightarrow MeltT(~ 1000 °C), Critical T (~ 300 °C)
- Results (from FLUKA):
 - 21% of the PRIMARY (BEAM) particles escape the system (radially)

OPTIONS TO COPE WITH THE ENERGY / PARTICLES LOST?

1. Remove the concrete blocks: change all of the new design, change the ALARA, etc.

→ **'COMPLETE CHANGE'**



2. Impose a certain beam size (**optical focusing**), optimal in terms of layout/ALARA, which has to be checked for thermal stress.
Keep the concrete blocks and adapt the geometry of the new dump to the existing layout


→ **'PARTIAL CHANGE'**

LAYOUT: CROSS SECTION

∅ Hole in the wall = 1000 mm


∅ Concrete block = 960 mm

∅ Hole in the concrete = 300 mm



MAXIMUM BEAM SIZES

(by Wolfgang Bartmann)



Energy = 2 GeV

5 sigma-beam
size (max)


$\frac{1}{2}$ FWHM
(1.17 sigma-beam
size) (max)

MAXIMUM BEAM SIZES

(by Wolfgang Bartmann)

∅ window [mm]	220
∅ dump core [mm]	220
∅ hole in concrete [mm]	300

	at window [mm]		at dump core [mm]	
1.17 sigma-beam size (vertical plane)	51	(∅ = 102)	81	(∅ = 162)
5 sigma-beam size (vertical plane)	141	(∅ = 282)	236	(∅ = 472)




5 sigma-beam size (max)

1.17 sigma-beam size (max)

WHAT IS ACCEPTABLE AS A MAXIMUM BEAM SIZE?

- Cross section (imperfection of the surface, new shielding, cooling pipes...)



- Recommended 5 sigma-beam size:
 - Horizontal plane = 85 mm
 - Vertical plane = 85 mm

REQUIRED BEAM SIZES

REQUIRED MAXIMUM BEAM SIZE:

Acceptable max. beam size [mm]	
Horizontal plane	Vertical plane
85	85



Present values of 5 sigma-beam size (max):

- at dump core
- 1.4 GeV

5 sigma-max.beam size [mm]	
Horizontal plane	Vertical plane
151	265

It needs to be shrunk by a **factor of 5.5**

REQUIRED MINIMUM BEAM SIZE:

Maximum service temperature of Copper $\sim 300 - 350$ °C

Assuming ΔT_{\max} in steady state ~ 300 °C

→ The minimum beam size can shrink up to a **factor of 2.3**:

1 sigma-min.beam size [mm]	
Horizontal plane	Vertical plane
2.82	2.82

OPTIONS

SOLUTION	PROS	CONS
1. FULL CHANGE (remove the dump and the existing concrete blocks)	<ul style="list-style-type: none">- More freedom in elaborating the new design- No constraints regarding the diameter of the dump- If the dump can be bigger in diameter, beam sizes would not be such a constraint- The concrete blocks can be replaced by any other material, one that can act as a more efficient shielding. Reduction in dose rates in the area. Fulfilling RP's requirements	<ul style="list-style-type: none">- Much bigger work load in a highly radiated area- The works would take much longer- More restrictive ALARA procedure- Due to the objects' age and their degraded state, there's no guarantee that the concrete blocks would come out of the wall easily (or at all).- Special tools would be required to dismantle the concrete blocks- Special machines would be required for the transport and disposal of the radioactive waste- A big part of the line (BTM, BTY and ejection) would need to be dismantled temporarily in order to allow the machines to access the area
2. PARTIAL CHANGE (keep the concrete blocks and adapt the geometry of the new dump to the existing layout)	<ul style="list-style-type: none">- Faster and easier dismantling of the old object and assembly of the new one- Less restrictive ALARA procedure- Safer for workers (who would be exposed to much lower dose rates for a shorter time)	<ul style="list-style-type: none">- Beam sizes constrain the design, making it more complicated
3. NEW LOCATION (find a different site for the dump)		

CONCLUSIONS

- Preliminary simulations have been performed
- Some issues have been identified: layout, space, access restrictions, beam sizes...
- A comparative study on the replacement of the PSB dump has been done

WHAT'S NEXT?

- A decision has to be made before March 2012 by the LIU-PSB Working Group
- An opinion from RP is required by the same time

THANK YOU