

March 22, 2012

1130 – 1145

ASIAN REGION DETECTOR HALL DESIGN


Outline


- ◆ Design Concept & Hall Layout
- ◆ Access Tunnel
- ◆ Top heading Tunnel
- ◆ Displacement of detector hall by push-pull operation

Design Concept


- ◆ Ensure the area is for detector assembly
- ◆ Garage space for ILD and SiD
- ◆ Sufficient tunnel section should be ensured for transportation of a part of detector
- ◆ Utility cavern for conventional facilities

A Birds-eye View







- ◆ Assembly area is located in front of the junction of access tunnels
- ◆ Beam tunnel is up to crossing point of access tunnel
- ◆ Garage for ILD and SiD is placed on the both side of cavern
- ◆ Capacity of overhead crane is 250 ton




- ◆ With 11m width access tunnel for SiD and ILD installation
- ◆ Two access tunnels are connected on the same side of cavern
- ◆ Access tunnels are connected at the same floor level of cavern's bottom floor
- ◆ Utility cavern is placed for utility (electric facilities, parking, various rooms...)
- ◆ Small access tunnels are connected to the garages for the pass
- ◆ Ventilation shaft is placed at utility cavern

Access Tunnel

- ◆ The dimension of access tunnels are determined by the transporting maximum component size of detector
- ◆ Small Access Tunnel is used for personal passageway





Top Heading Tunnel for The Hall



- ◆ The tunnel is utilized for initial excavation (arch excavation) during construction phase and for ventilation during operation phase


Displacement analysis by 3D FEM

- ◆ Detector ILD and SiD are heavy
- ◆ Displacement surround detector hall should be confirmed during operation (push-pull)
- ◆ Analysis Condition
 - ◆ Method: 3D Elastic FEM analysis
 - ◆ Cavern shape: simplified shape (I-type cavern)
 - ◆ Model: H500m x W500m x L520m (cover 200m)
 - ◆ Rock properties: based on an investigation at candidate site
 - ◆ Rock support: not considered



Push-Pull

Loading condition Nothing




Before installation

Loading condition LOS




Both off-line

Loading condition LSO




ILD off-line
SiD on-line

Loading condition OLS




ILD on-line
SiD off-line




- ◆ ILD: 14,700 tons
- ◆ SiD: 8,600 tons
- ◆ Detector is sit on a platform (concrete, t=3m)
- ◆ Loaded on the platform as a uniformly-distributed load

Result of analysis (Base concrete slab deformation)


Loading condition LOS




Loading condition LSO




Loading condition OLS




Loading condition LOS








Loading condition LSO




Loading condition OLS




Displacement for each section (Floor Level)




Displacement (Beam line elevation)






Loading condition LOS



Loading condition LSO



Loading condition OLS



Summary

- ◆ Assembly space is ensured
- ◆ Detector garages are placed
- ◆ Utility cavern is constructed separately
- ◆ Sloped access tunnel has a enough size to transport detector parts
- ◆ Top heading tunnel is constructed for excavation and ventilation
- ◆ The maximum displacement at the floor level is under 1.3mm
- ◆ The maximum displacement at the beam tunnel elevation is under 0.4mm