

The MedAustron Project

Conception and Current Status

Thomas Schreiner – Michael Benedikt

PEG MedAustron – CERN

February 11, 2013

MedAustron



Radiation Therapy



- aim:

- highest dose to target volume, to damage tumor cells
- spare healthy tissue and critical organs from high doses

⇒ match dose exactly to tumour shape



- radiation types

- conventional therapy: photons, electrons
- ion-beam therapy: protons, light ions




Radiation Therapy


- aim:
 - highest dose to target volume, to damage tumor cells
 - spare healthy tissue and critical organs from high doses
- ⇒ match dose exactly to tumour shape
- radiation types
 - conventional therapy: photons, electrons
 - ion-beam therapy: protons, light ions




Dose Distribution in Water



Dose Distribution in Water




Dose Distribution in Water



Centre for Ion-Beam Therapy and Research


- radiation therapy and clinical research
 - protons and carbon ions
 - 24 000 single fractions per year
corresponds to about 100 patients/day
corresponds to about 1200 patients/year
 - three medical irradiation rooms
 - two shift operation from Monday to Friday
- non-clinical research
 - protons and light ions
 - one irradiation room dedicated for non-clinical research
 - labs for non-clinical purposes



MedAustron


Centre for Ion-Beam Therapy and Research

- radiation therapy and clinical research
 - protons and carbon ions
 - 24 000 single fractions per year
corresponds to about 100 patients/day
corresponds to about 1200 patients/year
 - three medical irradiation rooms
 - two shift operation from Monday to Friday
- non-clinical research
 - protons and light ions
 - one irradiation room dedicated for non-clinical research
 - labs for non-clinical purposes



MedAustron

Distribution of Beam Time



Non-Clinical Research: Mon – Fri 10:00 p.m. – 6:00 a.m. & Sat – Sun 0:00 a.m. – 12:00 p.m.
 Clinical (Research) Operation: Mon – Fri 6:00 a.m. – 10:00 p.m.



Beam Parameters for Non-Clinical Research

particles:

protons

carbon ions

later additional ions like He or O


Beam Parameters for Non-Clinical Research

particles:	protons	carbon ions
	later additional ions like He or O	
beam intensity particles per pulse:	$\leq 10^{10}$	$\leq 4 \times 10^8$

Beam Parameters for Non-Clinical Research

particles:	protons later additional ions like He or O	carbon ions
beam intensity particles per pulse:	$\leq 10^{10}$	$\leq 4 \times 10^8$
beam energy min – max:	60 – 800 MeV	120 – 400 MeV/A


Beam Parameters for Non-Clinical Research



Beam Parameters for Non-Clinical Research

particles:	protons	carbon ions
	later additional ions like He or O	
beam intensity particles per pulse:	$\leq 10^{10}$	$\leq 4 \times 10^8$
beam energy min – max:	60 – 800 MeV	120 – 400 MeV/A
magnetic rigidity min – max:	1.14 – 4.88 Tm	3.25 – 6.35 Tm

Beam Parameters for Non-Clinical Research




Beam Parameters for Non-Clinical Research

particles:	protons	carbon ions
	later additional ions like He or O	
beam intensity particles per pulse:	$\leq 10^{10}$	$\leq 4 \times 10^8$
beam energy min – max:	60 – 800 MeV	120 – 400 MeV/A
magnetic rigidity min – max:	1.14 – 4.88 Tm	3.25 – 6.35 Tm
extraction duration min – max:	0.1 – 10 s	0.1 – 10 s

Beam Parameters for Non-Clinical Research

particles:	protons	carbon ions
	later additional ions like He or O	
beam intensity particles per pulse:	$\leq 10^{10}$	$\leq 4 \times 10^8$
beam energy min – max:	60 – 800 MeV	120 – 400 MeV/A
magnetic rigidity min – max:	1.14 – 4.88 Tm	3.25 – 6.35 Tm
extraction duration min – max:	0.1 – 10 s	0.1 – 10 s
beam delivery active scanning	horizontal-vertical fast scanning magnets energy variation with synchrotron	

Accelerator Layout



Realisation Strategy – Flexibility for Operation

- injector area with sources accessible during operation
 - allows tuning of source in parallel to operation, change of ion type, etc.
- injector design allows for installation of up to five different ion sources
 - flexibility in the provision of different ion types for medical operation and research
- variable iso-centre optics for irradiation room for non-clinical research
 - allows parallel installation of several experiments
- fully exploit synchrotron capabilities to increase proton beam energy to 800 MeV for non-clinical research with limited additional effort
 - world-wide unique for comparable centres


Facility

Conventional construction:

administration, research, and medical area


Radiation protection:

accelerator and four irradiation rooms



MedAustron

Sandwich Construction – March 2012



- using ground excavation for radiation protection

MedAustron

Injector Hall with Ion Sources




MedAustron

Injector Bunker with Injector Linac



MedAustron

Synchrotron Hall and Main Bending Magnet



Power Converter Hall and Linac RF Amplifier





MedAustron

Main Non-Clinical Research Areas


● Experimental Physics:

- detector development and test
- proton scattering experiments
- high-energy proton-computed tomography




● Medical Radiation Physics:

- basic and applied dosimetry
- dose calculation and optimisation
- treatment planning and plan evaluation



● Radiation Biology:

- radiation induced mechanisms of cell death
- research on biomarkers and bioimaging



● Education and Training

MedAustron


Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres
- removable nozzle for the first isocentre
- same equipment as in the medical irradiation rooms for the first isocentre, i. e. laser, positioning and imaging system
- circuit points for pressurised air and demineralised water
- electrical sockets and power supplies
- room size approximately 8 m × 12 m, i. e. 96 m²
- local control room with control console enabling visual monitoring and display of accelerator parameters

Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres

- removable
- same equi isocentre,
- circuit po
- electrical
- room size
- local cont and displ



the first

monitoring

edAustron

Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres
- removable nozzle for the first isocentre
- same equipment as in the medical irradiation rooms for the first isocentre, i. e. laser, positioning and imaging system
- circuit points for pressurised air and demineralised water
- electrical sockets and power supplies
- room size approximately 8 m × 12 m, i. e. 96 m²
- local control room with control console enabling visual monitoring and display of accelerator parameters

Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres
- removable nozzle for the first isocentre
- same equipment as in the medical irradiation rooms for the first isocentre, i. e. laser, positioning and imaging system
- circuit points for pressurised air and demineralised water
- electrical sockets and power supplies
- room size approximately 8 m × 12 m, i. e. 96 m²
- local control room with control console enabling visual monitoring and display of accelerator parameters

Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres
- removable nozzle for the first isocentre
- same equipment as in the medical irradiation rooms for the first isocentre, i. e. laser, positioning and imaging system
- circuit points for pressurised air and demineralised water
- electrical sockets and power supplies
- room size approximately 8 m × 12 m, i. e. 96 m²
- local control room with control console enabling visual monitoring and display of accelerator parameters

Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres
- removable nozzle for the first isocentre
- same equipment as in the medical irradiation rooms for the first isocentre, i. e. laser, positioning and imaging system
- circuit points for pressurised air and demineralised water
- electrical sockets and power supplies
- room size approximately 8 m × 12 m, i. e. 96 m²
- local control room with control console enabling visual monitoring and display of accelerator parameters

Irradiation Room

- one fixed horizontal beam line
- variable isocentre over 5 metres adjustable, installation of several experiments – two isocentres
- removable nozzle for the first isocentre
- same equipment as in the medical irradiation rooms for the first isocentre, i. e. laser, positioning and imaging system
- circuit points for pressurised air and demineralised water
- electrical sockets and power supplies
- room size approximately 8 m × 12 m, i. e. 96 m²

- local control room with control console enabling visual monitoring and display of accelerator parameters

Specific Rooms for Experimental Physics

- cooling-down room
 - storage of activated material after irradiation
 - $\sim 28 \text{ m}^2$
- preparation room
 - partial installation of experiments and preparation tests outside of the irradiation room
 - $\sim 28 \text{ m}^2$
- storage room
 - safe-keeping of external experimental equipment, material and devices
 - $\sim 55 \text{ m}^2$

Specific Rooms for Experimental Physics

- cooling-down room
 - storage of activated material after irradiation
 - $\sim 28 \text{ m}^2$

- preparation room
 - partial installation of experiments and preparation tests outside of the irradiation room
 - $\sim 28 \text{ m}^2$

- storage room
 - safe-keeping of external experimental equipment, material and devices
 - $\sim 55 \text{ m}^2$

Specific Rooms for Experimental Physics

- cooling-down room
 - storage of activated material after irradiation
 - $\sim 28 \text{ m}^2$

- preparation room
 - partial installation of experiments and preparation tests outside of the irradiation room
 - $\sim 28 \text{ m}^2$

- storage room
 - safe-keeping of external experimental equipment, material and devices
 - $\sim 55 \text{ m}^2$

Overall Project Schedule

- + Dec 2010: environmental impact assessment
- + March 2011: first stone laying
- + Dec 2011: building shell
- + Oct 2012: moving to the new building



Overall Project Schedule

- + Dec 2010: environmental impact assessment
- + March 2011: first stone laying
- + Dec 2011: building shell
- + Oct 2012: moving to the new building

- 2013: accelerator installation and commissioning
- 2014: medical trial operation
- 2015: first patient treatment
- 2016: facility ready for non-clinical research
- 2016: full operation – up to 1200 patients/year



MedAustron




Summary

- MedAustron will be a “state-of-the-art” centre for ion-beam therapy and non-clinical research centre in Austria
- project is based on international collaborations with experienced partners for the conception and construction
- collaboration with CERN is an excellent example for technology transfer and essential for project progress
- construction phase started with accelerator components and civil engineering – initial operation end of 2015

MedAustron

Thank you for your attention!



www.medaustron.at

Excursion to MedAustron on **Wednesday 2:00 p.m.**

MedAustron