

# CMS Trigger Upgrade Synchronization and Link Board (SLB)

Jose C. Da SILVA LIP-Lisboa

Jornadas LIP 2012 José C. Da Silva 1



#### SLB – what is?

#### Article au hasard Contacter Wikipédia

Contribuer
Premiers pas
Aide
Communauté

Modifications récentes

- Faire un don

  Imprimer / exporter
- ▶ Boîte à outils
- Autres langues
   Deutsch
   English
   Esperanto

فارسي

Italiano

日本語

Svenska

#### SLB

Cette page d'homonymie répertorie les différents sujets et articles partageant un même nom.

SLB est un sigle de trois lettres qui signifie :

- Îles Salomon
  - selon la norme ISO 3166-1 alpha-3 (liste des codes pays);
  - selon la liste des codes pays utilisés par l'OTAN, alpha-3;
- Sindikad Labourerien Breizh, un syndicat breton.
- Server Load Balancing, système informatique répartiteur de charge.
- · Sport Lisboa e Benfica, club de football de Lisbonne.
- Schlumberger, SLB est le libellé de l'indice boursier de Schlumberger.
- Synchronization and Link Board, a mezzanine for alignment of trigger primitives of Calorimeter Trigger of the CMS experiment (CERN, LHC)

Catégories : Homonymie | Sigle de 3 caractères

Dernière modification de cette page le 20 décembre 2011 à 13:43.

Droit d'auteur : les textes sont disponibles sous licence Creative Commons paternité partage à l'identique ; d'autres conditions peuvent s'appliquer. Voyez les conditions détails, ainsi que les crédits graphiques. En cas de réutilisation des textes de cette page, voyez comment citer les auteurs et mentionner la licence.

Wikipedia® est une marque déposée de la Wikimedia Foundation, Inc., organisation de bienfaisance régie par le paragraphe 501(c)(3) du code fiscal des États-Un

Politique de confidentialité À propos de Wikipédia Avertissements Affichage mobile








#### **SLB – Functional Description**

- •Receives 9 bit data @ 40 MHz / TT
- •Each SLB houses 8 TT
- •Align Trigger Data using the LHC Orbit bunch structure to determine the BX position using internal histograms
- •FIFO stage to compensate fiber length differences, deserialisers lock delays and to guarantee the alignment of data sent to the RT from both ECAL and HCAL.
- •2 TT data merging + Hamming code prior to send it over the high speed link
- •4 High speed links (1.2Gb/s each)


Jornadas LIP 2012 José C. Da Silva









## **Present TPG path**










#### **SLB Basic Connection**




Jornadas LIP 2012

José C. Da Silva




## "Adopted" oSLB solution for ECAL





## oSLB "hot points"

- •Xloom optical solution under study:
  - •4 TX 4RX (up to 5Gbps) 500 EURO/Piece
- ·Pro's:
  - mechanics, number of channels (4 tx/rx @ 5gbps)
  - •Israeli-CERN fund for (partial) payment || END||
    - •Open window to study TX or RX versions
- •Con's:
  - •Small company issues
  - •Still poor input on these devices (ongoing)
- •Xloom devices production received(4 units)
- •BER measurement tests to be done







#### oSLB "hot points"

- •Fujitsu "microgiga" optical solution under study:
  - •4 TX 4RX (up to 5Gbps) 255 EURO/Piece (!)
- ·Pro's:
  - Price
  - mechanics, number of channels (4 tx/rx @ 5gbps)
  - Optical Module External to the oSLB
  - Fujitsu "company name" (2000 units sold)
- ·Con's:
  - Infiniband connector dimensions
  - Modification on front panels mechanics of TCCs
- •Fujitsu components ordered (4 units)
- •BER measurement tests to be done

#### **IMPORTANT:**

•Both solutions have the same Footprint on the SLBs






#### **Production count:**

- produce ONLY the final count (ECAL) of oSLBs + spares
  - 1 to 1 = 324 EB, 252 EE (576)
  - 2 or 1 = 180 EB, 180 EE (360) = ~200 Links gain!!
  - 3 or 2 = 108 EB (3), 144(2) EE (252) = ~320 Links gain!! •(~500-700 euros savings per oSLB)
- •Cost effective!
  - •~200Euro/ oSLB + 250 EUR/microgiga adaptor
    - •Cost estimate:~ 450 Euro / oSLB/optics
    - •+ 90K USD for optical bundles and adaptors

•production covers the ECAL final needs (400Pcs)






#### **Optical PP connections**

Replace 2 SLBs by one 2slots oSLB **Using 4.8Gb modules** 

4 outputs @5Gbps



1 input @5Gbps

324 x MTP4 female to LC

96 blocks of 12 LC-LC

**oSLB ABCDn** 

**oSLB ABCDn** 

**oSLB ABCDn** 

HTR -uTCA **ABCDn** 







Jornadas LIP 2012


14



#### oSLB proto design

#### •"Dual input" SLB Layout

- •Use latest FPGA technology : Kintex
  - •400x XC7K160T-1FBG676C @160\$
  - •400x XC7K70T-1FBG676C @100\$
  - •3v3 Compatible with present design
  - Reduced impact on design
  - •Reduced the cost by 100 USD Kintex 7 FPGA)



- Kintex7 Available in August 2012
  - •Rev A Prototype validation up to August 2012 (10 units)
    - •Can use a larger but same footprint FPGA for the proto oSLB validation
    - •SLB TEST bench installation in 904 (started)
    - •Optical test bench using also ML605 (Xilinx Dev Kit)

## Production Planning:

- •Finish oSLB prototype Aug. 2012
  - Wisconsin starts design/production of oRMs
- •Validation of Prototype oSLB & ORM complete by end of 2012.
- •Funding required for oSLB & ORM production by Jan. 2013, production starts.
  •No money....all slips down the hill!!!
- Production of oSLB & ORM complete by June 2013
  - •Production testing of first oSLB & ORM production units starts June 2013
    - •Fiber Plant installed by July/August 2013 (purchase in January 2013)!!
  - •ECAL TCC & RCT RC Front Panel Modifications complete by July 2013
- •Installation of oSLBs & ORMs starts July 2013
  - Production testing of oSLB & ORM done by September 2013
    - Installation finished by end of.
      - •System commissioned by May 2014.



#### **OBRIGADO**

#### **Other SLBs:**







SOUNDS LIKE BRISBANE







Jornadas LIP 2012 José C. Da Silva 17